



ANCOR




MARINE
EMERGENCY VEHICLE
INDUSTRIAL
RV



Lighting
Terminals & Lugs
Tools & Testers
Wire Management
Wire & Cable

For decades Ancor, BEP, Blue Sea Systems, CZone, Lenco, Marincor, Mastervolt and ProMariner have worked independently to provide innovative electrical products. Now the eight companies are working together to offer comprehensive electrical solutions for marine and mobile applications.

Providing more than products. Providing Solutions.



ANCOR

- Lighting
- Terminals & Lugs
- Tools & Testers
- Wire Management
- Wire & Cable

BEP

TRUSTED QUALITY

- Battery Management
- Circuit Protection
- Connectors & Insulators
- Custom Panels & Design Services
- Meters
- Power Distribution Panels

BLUE SEA SYSTEMS

- Battery Management
- Circuit Protection & Switches
- Connectors & Insulators
- Custom Panels
- Meters
- Power Conversion & Connection
- Power Distribution

CZONE

- Digital Control & Monitoring
- Integrated Solutions

LENCO

- Actuators & Accessories
- Auto Glide Automatic Boat Leveling
- Electric Hatch Lifts
- Electric Trim Tabs
- Rocker Switch Kits
- Tactile Switch Kits
- Trim Tab Retrofit Kits

ProMariner™

- Inverter / Chargers
- Inverters
- Isolators
- Vented Battery Chargers
- Waterproof Battery Chargers

MASTERVOLT

- Alternators & Regulators
- Batteries
- Battery Chargers
- Digital Control & Monitoring
- Inverter / Chargers
- Inverters
- Transformers

MARINCO

- Battery Management
- DC Power Connections
- Horns
- Lighting
- Power Conversion
- Shore Power
- Ventilation
- Wiper Systems



What makes Ancor different:

Founder's Vision

For over 40 years Ancor has been the industry leader for quality tinned copper Marine Grade® wire and cable. Ancor's comprehensive product line includes everything required to complete a wiring project. This includes Marine Grade® wire and cable, terminals and connectors, wire management products, and hand tools. Ancor designs products to the highest standards that meet UL, ABYC, NMMA and USCG standards. Product selection, quality, and service are the pillars of the brand, and only Ancor can be your single source for wire and accessories.



Selection

Over 1,500 electrical products are designed to work together as a system

Fast Delivery


Products stocked in multiple global locations ensures rapid order fulfillment

Worldwide Access to Product

A distribution network in over 45 countries provides access to products when they are needed

Information

24-hour access to product information, selection tools, and technical articles online at ancorproducts.com



Industry Standards

Industry involvement ensures products meet ABYC, NMMA, and Coast Guard standards

Quality

Product quality is managed in a manner consistent with international standards



2020 **NEW** Products



17

Flat Ribbon Bonded RGB Cable

Color coded wire perfect for installing RGB lighting. Bonded cable simplifies installation.



23

NMEA 2000 Single Device Backbone Starter Kit

Basic starter kit for adding a new NMEA 2000 network to your boat.
Part # 270203



EXPANDED OFFERING



28

Heat Shrink Disconnects

Expanding our line to include .110 and .187 sized female disconnects to follow the market with different sizes for different applications.

- Part # 326899 (100) 22-18 AWG, .110 tab female disconnects
- Part # 336899 (100) 22-18 AWG, .187 tab female disconnects
- Part # 327899 (100) 16-14 AWG, .110 tab female disconnects
- Part # 337899 (100) 16-14 AWG, .187 tab female disconnects
- Part # SPKKIT 90 Pc Kit Assorted Kit

76

NMEA 2000 Display

Simple drop in NMEA 2000 store set. Kit includes everything needed to build a new NMEA network or expand on an existing network.

Part # 270400



21

NMEA 2000 Accessories

New accessories in our comprehensive line of cables and connectors. Ancor now offers everything needed for standard installations or custom applications.

- Part # 270107 Through Bulkhead Adaptor
- Part # 270109 Female Field Serviceable Connector
- Part # 270110 Male Field Serviceable Connector
- Part # 270111 Female Blanking Cap
- Part # 270112 Male Blanking Cap
- Part # 270114 Inline Terminator



50

Cut/Strip/Crimp Tools

Innovative new tools expanding on Ancor's highly popular tool portfolio.

- Part # 702007 Cut/Strip/Crimp Tool
- Part # 702008 Cut/Strip Tool
- Part # 702031 Compact Automatic Wire Stripper
- Part # 702032 Universal Wire Stripper
- Part # 703007 Heavy-duty Wire Scissors
- Part # 703015 Angled 22-8 AWG Single Crimp Ratcheting Crimper
- Part # 703035 Angled 26-10 AWG Single Crimp Ratcheting Crimper



58

Meters

Rounding out the Ancor line of hand tools with new meters.

- Part # 703072 8 Function Digital Multimeter
- Part # 703073 True RMS 12 Function Digital Multimeter
- Part # 703079 True RMS 12 Function Digital Snap-Around Meter


2021 **NEW** Products



16

Bonded Cable

Perfect for installing trolling motor plugs.



17

RGB + Speaker Cable

Save time by only needing to run one cable when installing RGB LED lighted speakers.



EXPANDED OFFERING

30

Nylon Multi-Stack Disconnects and Flag Disconnects

Rounding out the current Ancor line of nylon terminals.

31

Heat Shrink Flag Disconnects

Also available in heat shrink for added safety and security.



34

Angled Battery Cable Lugs

Make your install cleaner and easier with the 90° bend instead of straining the wire and crimp connection.

34

Heavy-duty Butt Connectors

Adding 25 packs to meet customer requests for this popular item.

EXPANDED OFFERING



53

Flag Terminal Die Sets

These die sets are needed to create the proper crimp for our new flag terminals. Works with nylon and heat shrink versions. Compatible with all Ancor ratcheting crimpers.



54

Pliers and Screwdrivers

Insulated pliers and screw drivers for added safety when working on an electrical project.



Table of Contents

WIRE & CABLE

Primary Wire	10
Battery Cable & Assemblies	12
Duplex Cable	14
Triplex Cable	15
Specialty Cable	16
Coax Cable & Assemblies	18
Trailer Cable & Assemblies	19
NMEA 2000 Cables & Connectors	20



p. 10 p. 13 p. 15 p. 17 p. 18 p. 19 p. 20

TERMINALS & LUGS

Adhesive Lined Heat Shrink Terminals	26
Nylon Insulated Terminals	29
Vinyl Insulated Terminals	31
Coax Cable Fittings	32
Tinned Copper Lugs	33
Battery Terminals & Boots	35



p. 26 p. 27 p. 27 p. 29 p. 30
 p. 31 p. 31 p. 32 p. 33 p. 34 p. 35 p. 35

WIRE MANAGEMENT

Adhesive Lined Heat Shrink Tubing	38
Adhesive Lined Heavy Wall Heat Shrink Tubing	39
Repair Tape	40
Electrical Tape	40
Cable Ties	41
Cable Clamps	45
Wire Seals	46
Grommets	46
Split Loom & Spiral Wrap	46
Wire Management Kits	47



p. 38 p. 39 p. 40 p. 40
 p. 41 p. 42 p. 43 p. 45
 p. 46 p. 46 p. 47


TOOLS & TESTERS

Cut/Strip/Crimp Tools	50
Crimpers	52
Mini Fish Tape	54
Pliers & Screwdrivers	54
Tool Kits	55
Heat Tools	56
Digital Multimeters	58
Snap-Around Meters	59



LIGHTING

Incandescent Bulbs	62
Miniature Halogen Bulbs	63
Festoon Bulbs	63
Medium Screw Base Bulbs	64
Fluorescent Tubes	64



DISPLAYS

Display Racks	68
Gondola Displays	74
NMEA 2000	76
Planogram Assortment	76



APPENDIX & INDEX

Technical Data	77
Part Number Index	82

WIRE & CABLE

Primary Wire

10



Manufactured from tinned copper stranding for maximum protection against corrosion and electrolysis. Ultra flexible (Type 3) stranding resists fatigue due to vibration and flexing.

Battery Cable & Assemblies

12



Premium, fine stranded UL1426 tinned copper battery cable for maximum conductivity and flexibility. All assemblies come with tinned copper lugs to avoid corrosion and extend life.

Multiconductor Cables

14



Duplex and triplex wire in a variety of gauge and spool sizes; including UL 1426 tinned duplex boat cable in flat and round configurations.

Specialty Cable

16



Ancor offers a broad range of cable for specialty applications to meet all of your marine and mobile wiring needs.



WIRE & CABLE

Coax Cable & Assemblies

18



Premium tinned copper features signal loss ratios of up to 50% less than other coaxial cables. All assemblies come with Ancor adhesive lined heat shrink to seal out moisture, provide strain relief and fight corrosion.

Trailer Cable & Assemblies

19



Made from our standard Ancor primary wire made specifically for trailer wiring. Assemblies with molded connectors for a wide range of applications.

NMEA 2000 Cables & Connectors

20



Ancor now carries NMEA 2000 cables and connectors for creating or expanding an NMEA 2000 network quickly and easily. Couplers are color coded to make identifying the power cable or connector easy. Premium quality. Universal fit.



Wire and cable are the backbone of every electrical system and properly selected wire will ensure a safe and reliable system.

Ancor Marine Grade® Wire & Cable

- Ancor Marine Grade® wire and cable is manufactured from tinned copper stranding for maximum protection against corrosion and electrolysis. Ultra flexible (Type 3) stranding resists fatigue due to vibration and flexing.
- Ancor's proprietary premium vinyl insulation stays flexible even in extreme cold (-40°F / -40°C) and resists salt water, battery acid, oil, gasoline and ultra-violet radiation. Exclusive insulation is rated at 600 volts, 221°F / 105°C dry and 167°F / 75°C wet, and is resistant to heat and abrasion.
- Exceeds all UL 1426, US Coast Guard Charter boat (CFR Title 46) and ABYC standards.
- See pages 77-81 for ABYC wiring guidelines and technical data.

Primary Wire 18-14 AWG

18 AWG (0.8 mm²)

Color	Ft	Part #
Black	35	180003
	100	100010
	250	100025
	500	100050
	1000	100099
Red	35	180803
	100	100810
	250	100825
	500	100850
	1000	100899
Yellow	35	181003
	100	101010
	250	101025
	500	101050
	1000	101099
Green	35	180303
	100	100310
	250	100325
	500	100350
	1000	100399
White	35	180903
	100	100910
	250	100925
	500	100950
	1000	100999
Dk Blue	35	180103
	100	100110
	250	100125
	500	100150
	1000	100199
Brown	35	180203
	100	100210
	250	100225
	500	100250A
	1000	100299
Orange	35	180503
	100	100510
	250	100525
	500	100550
	1000	100599
Pink	35	180603
	100	100610
	250	100625
	500	100650
	1000	100699

18 AWG (0.8 mm²)

Color	Ft	Part #
Purple	35	180703
	100	100710
	250	100725
	500	100750
	1000	100799
Grey	35	180403
	100	100410
	250	100425
	500	100450
	1000	100499

16 AWG (1 mm²)

Color	Ft	Part #
Black	25	182003
	100	102010
	250	102025
	500	102050
	1000	102099
Red	25	182803
	100	102810
	250	102825
	500	102850
	1000	102899
Yellow	25	183003
	100	103010
	250	103025
	500	103050
	1000	103099
Green	25	182303
	100	102310
	250	102325AA
	500	102350
	1000	102399
White	25	182903
	100	102910
	250	102925
	500	102950
	1000	102999
Dk Blue	25	182103
	100	102110
	250	102125
	500	102150
	1000	102199

16 AWG (1 mm²)

Color	Ft	Part #
Brown	25	182203
	100	102210
	250	102225
	500	102250
	1000	102299
Orange	25	182503
	100	102510
	250	102525
	500	102550
	1000	102599
Pink	25	182603
	100	102610
	250	102625
	500	102650
	1000	102699
Purple	25	182703
	100	102710
	250	102725
	500	102750
	1000	102799
Grey	25	182403
	100	102410
	250	102425
	500	102450
	1000	102499
Tan	100	101810
	250	101825
	500	101850
	1000	101899
	Lt Blue	100
250		101925
500		101950

14 AWG (2 mm²)

Color	Ft	Part #
Black	18	184003
	100	104010
	250	104025
	500	104050
	1000	104099
Red	18	184803
	100	104810
	250	104825
	500	104850
	1000	104899

14 AWG (2 mm²)

Color	Ft	Part #
Yellow	18	185003
	100	105010
	250	105025
	500	105050
	1000	105099
Green	18	184303
	100	104310
	250	104325
	500	104350
	1000	104399
White	18	184903
	100	104910
	250	104925
	500	104950
	1000	104999
Dk Blue	18	184103
	100	104110
	250	104125
	500	104150
	1000	104199
Brown	18	184203
	100	104210
	250	104225
	500	104250
	1000	104299
Orange	18	184503
	100	104510
	250	104525
	500	104550
	1000	104599
Pink	18	184603
	100	104610
	250	104625
	500	104650
	1000	104699
Purple	18	184703
	100	104710
	250	104725
	500	104750
	1000	104799
Grey	18	184403
	100	104410
	250	104425
	500	104450
	1000	104499
Tan	100	103810
	250	103825
	500	103850
	1000	103899
	Lt Blue	100
250		103925
500		103950



Primary Wire 12-6 AWG

12 AWG (3 mm²)

Color	Ft	Part #
Black	12	186003
	25	106002
	100	106010
	250	106025
	400	106040
Red	1000	106099
	12	186803
	25	106802
	100	106810
	250	106825
Yellow	400	106840
	1000	106899
	12	187003
	25	107002
	100	107010
Green	250	107025
	400	107040
	1000	107099
	12	186303
	25	106302
White	100	106310
	250	106325
	400	106340
	1000	106399
	12	186903
Dk Blue	25	106902
	100	106910
	250	106925
	400	106940
	1000	106999
Brown	25	106102
	100	106110
	250	106125
	400	106140
	1000	106199
Orange	25	106202
	100	106210
	250	106225
	400	106240
	1000	106299
Pink	25	106502
	100	106510
	250	106525
	400	106540
	1000	106599
Purple	25	106602
	100	106610
	250	106625
	400	106640
	1000	106702
Grey	100	106710
	250	106725
	400	106740
Tan	1000	106499
	100	105810
	250	105825
400	105840	

10 AWG (5 mm²)

Color	Ft	Part #
Black	8	188003
	25	108002
	100	108010
	250	108025
	500	108050
Red	1000	108099
	8	188803
	25	108802
	100	108810
	250	108825
Yellow	500	108850
	1000	108899
	25	109002
	100	109010
	250	109025
Green	500	109050
	1000	109099
	25	108302
	100	108310
	250	108325
White	500	108350
	1000	108399
	25	108902
	100	108910
	250	108925
Dk Blue	500	108950
	1000	108999
	25	108102
	100	108110
	250	108125
Brown	500	108150
	1000	108199
	25	108202
	100	108210
	250	108225
Orange	500	108250
	1000	108299
	25	108502
	100	108510
	250	108525
Grey	500	108550
	1000	108599
	1000	108499
	25	109302
	100	109310
Green w/ Yellow Stripe	250	109325
	500	109350
	1000	109399

8 AWG (8 mm²)

Color	Ft	Part #
Black	25	111002
	50	111005
	100	111010
	250	111025
	500	111050
Red	1000	111099
	25	111502
	50	111505
	100	111510
	250	111525
Yellow	500	111550
	1000	111599
	25	111902
	50	111905
	100	111910
Green	250	111925
	500	111950
	1000	111999
	25	111302
	50	111305
White	100	111310
	250	111325
	500	111350
	1000	111399
	25	111702
Dk Blue	50	111705
	100	111710
	250	111725
	500	111750
	1000	111799

6 AWG (13 mm²)

Color	Ft	Part #
Black	25	112002
	50	112005
	100	112010
	250	112025
	500	112050
Red	750	112075
	25	112502
	50	112505
	100	112510
	250	112525
Yellow	500	112550
	750	112575
	25	112902
	50	112905
	100	112910
Green	250	112925
	500	112950
	750	112975
	25	112302
	50	112305
White	100	112310
	250	112325
	500	112350
	750	112375
	25	112702
Dk Blue	50	112705
	100	112710
	250	112725
	500	112750
	750	112775

TECH tip™

Wire Flexibility Explained

Wire flexibility is influenced by two major factors: wire strand size and jacket hardness.

Wire strand size has the largest impact on overall wire flexibility. As individual wire strand size decreases, wire flexibility increases. For boat cable, UL 1426 requires at least 19 individual strands for cables 16 AWG and larger. Ancor wire uses type 3 stranding which consists of individual 30 AWG (0.010") strands, regardless of the wire gauge. Ancor's 16 AWG wire consists of 26 individual strands, while the 4/0 AWG wire consists of 2,109 individual strands.

Jacket hardness is most commonly measured by durometer, with lower measurements reflecting a more flexible material. Ancor wire measures 7 points lower than competitive product (on a scale of 1-100), resulting in a more flexible product.



Battery Cable 4-4/0 AWG

4 AWG (21 mm²)

Color	Ft	Part #
Black	25	113002
	50	113005
	100	113010
	250	113025
	500	113050
Red	25	113502
	50	113505
	100	113510
	250	113525
	500	113550
Yellow	25	113902
	50	113905
	100	113910
	250	113925
	500	113950

2 AWG (34 mm²)

Color	Ft	Part #
Black	25	114002
	50	114005
	100	114010
	250	114025
	400	114040
Red	25	114502
	50	114505
	100	114510
	250	114525
	400	114540
Yellow	25	114902
	50	114905
	100	114910
	250	114925
	400	114940

1 AWG (42 mm²)

Color	Ft	Part #
Black	25	115002
	50	115005
	100	115010
	300	115030
Red	25	115502
	50	115505
	100	115510
	300	115530
Yellow	25	115902
	50	115905
	300	115930

1/0 AWG (53 mm²)

Color	Ft	Part #
Black	25	116002
	50	116005
	100	116010
	250	116025
Red	25	116502
	50	116505
	100	116510
	250	116525
Yellow	25	116902
	50	116905
	250	116925

2/0 AWG (68 mm²)

Color	Ft	Part #
Black	25	117002
	50	117005
	100	117010
	200	117020
Red	25	117502
	50	117505
	100	117510
	200	117520
Yellow	25	117902
	50	117905
	200	117920

3/0 AWG (85 mm²)

Color	Ft	Part #
Black	25	118002
	50	118005
	100	118010
	150	118015
Red	25	118502
	50	118505
	100	118510
	150	118515
Yellow	25	118902
	50	118905
	150	118915

4/0 AWG (107 mm²)

Color	Ft	Part #
Black	25	119002
	50	119005
	100	119010
	250	119025
Red	25	119502
	50	119505
	100	119510
	250	119525
Yellow	25	119902
	50	119905
	250	119925

Related Products



Battery
Terminals
page 35



Lugs
page 33



Heat Shrink
Tubing
page 38



Premium
Electrical Tape
page 40



Cutting &
Crimping Tools
pages 50-53

18-4/0 AWG Wire and Cable Specifications

Wire Size	Nominal O.D.	Wire Diameter	Minimum Bend Radius	Stranding No. of 30 AWG	Cir. Mil Area	Ohms per 1000'	mm ²	Wt. per 1000'				
18 AWG	.08 mm ²	7/64"	2.8 mm	1.0 mm	7/8"	2.3 cm	16	1600	6.48	.08	12 lbs	5.4 kg
16 AWG	1 mm ²	1/8"	3.2 mm	1.5 mm	31/32"	2.5 cm	26	2600	4.00	1.31	16 lbs	7.3 kg
14 AWG	2 mm ²	9/64"	3.6 mm	2.0 mm	1-3/32"	2.8 cm	41	4100	2.53	2.08	23 lbs	10.4 kg
12 AWG	3 mm ²	5/32"	4.0 mm	2.6 mm	1-1/4"	3.2 cm	65	6500	1.75	3.31	31 lbs	14 kg
10 AWG	5 mm ²	7/32"	5.6 mm	3.3 mm	1-29/64"	3.7 cm	105	10,500	1.00	5.26	44 lbs	20 kg
8 AWG	8 mm ²	5/16"	7.9 mm	4.3 mm	2-1/32"	5.2 cm	168	16,800	0.62	8.37	86 lbs	39 kg
6 AWG	13 mm ²	11/32"	8.7 mm	5.5 mm	2-35/64"	6.5 cm	266	26,600	0.40	13.30	118 lbs	53.5 kg
4 AWG	21 mm ²	13/32"	10.3 mm	7.0 mm	3-3/32"	7.9 cm	420	42,000	0.24	21.15	178 lbs	81 kg
2 AWG	34 mm ²	15/32"	11.9 mm	8.0 mm	3-1/2"	8.9 cm	665	66,500	0.16	33.62	277 lbs	126 kg
1 AWG	42 mm ²	17/32"	13.5 mm	9.0 mm	4-9/64"	10.4 cm	836	83,690	0.13	42.38	350 lbs	159 kg
1/0 AWG	53 mm ²	9/16"	14.3 mm	10.5 mm	4-1/2"	11.4 cm	1064	105,600	0.10	53.49	437 lbs	198 kg
2/0 AWG	68 mm ²	5/8"	15.9 mm	12.0 mm	4-59/64"	12.4 cm	1330	133,000	0.08	67.43	549 lbs	249 kg
3/0 AWG	85 mm ²	11/16"	17.5 mm	13.0 mm	5-23/64"	13.7 cm	1665	167,800	0.06	85.01	675 lbs	306 kg
4/0 AWG	107 mm ²	13/16"	20.6 mm	14.0 mm	5-7/8"	15.0 cm	2109	211,600	0.05	107.20	837 lbs	380 kg



Premium Battery Cable Assemblies


UL1426 Tinned Boat Cable

- Premium, fine stranded UL 1426 tinned copper battery cable for maximum conductivity and flexibility
- Flame retardant, UV inhibited cable rated at 600V and 221°F / 105°C
- Tinned copper lugs to avoid corrosion and extend life
- 3:1 heat shrink tubing over the electrical connection to seal out moisture and provide strain relief

Color	Length	Stud Size	Part #
4 AWG (21 mm²)			
Black	18"	45.7 cm	5/16" 7.93 mm 189130
	32"	81.2 cm	5/16" 7.93 mm 189134
	48"	121.9 cm	5/16" 7.93 mm 189136
Red	18"	45.7 cm	3/8" 9.5 mm 189131
	32"	81.2 cm	3/8" 9.5 mm 189135
	48"	121.9 cm	3/8" 9.5 mm 189137

Color	Length	Stud Size	Part #
2 AWG (34 mm²)			
Black	18"	45.7 cm	5/16" 7.93 mm 189140
	32"	81.2 cm	5/16" 7.93 mm 189144
	48"	121.9 cm	5/16" 7.93 mm 189146
Red	18"	45.7 cm	3/8" 9.5 mm 189141
	32"	81.2 cm	3/8" 9.5 mm 189145
	48"	121.9 cm	3/8" 9.5 mm 189147

For continuous current draws up to:	Use battery cable assemblies
136 amps	4 AWG
178 amps	2 AWG



Safety Duplex Cable

UL 1426 Tinned Boat Cable

Conductor colors: red and yellow

Flat Cable



Spool Length	Part #	Nominal O.D.	Wt. per 1000'
18/2 AWG (2x0.8 mm²)			
100'	124910		
250'	124925	3/16"x9/32"	49 lbs
500'	124950	5x7 mm	22.2 kg
1000'	124999		
16/2 AWG (2x1 mm²)			
25'	124702		
100'	124710	3/16"x5/16"	51 lbs
250'	124725	5x8 mm	23.1 kg
500'	124750		
1000'	124799		
14/2 AWG (2x2 mm²)			
25'	124502		
100'	124510	7/32"x11/32"	65 lbs
250'	124525	6x9 mm	29.5 kg
500'	124550		
1000'	124599		

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
12/2 AWG (2x3 mm²)			
25'	124302		
100'	124310	7/32"x3/8"	82 lbs
250'	124325	6x10 mm	37.3 kg
500'	124350		
10/2 AWG (2x5 mm²)			
25'	124102		
100'	124110	1/4"x15/32"	128 lbs
250'	124125	6x12 mm	58.2 kg
400'	124140		
800'	124180		
8/2 AWG (2x8 mm²)			
50'	123905		
100'	123910	11/32"x5/8"	230 lbs
500'	123950	9x16 mm	104.5 kg
6/2 AWG (2x13 mm²)			
50'	123705	13/32"x3/4"	364 lbs
100'	123710	10x19 mm	165.5 kg

Round Cable



Spool Length	Part #	Nominal O.D.	Wt. per 1000'
16/2 AWG (2x1 mm²)			
100'	126710	5/16"	49 lbs
250'	126725	8 mm	22.2 kg
500'	126750		
14/2 AWG (2x2 mm²)			
100'	126510	11/32"	63 lbs
250'	126525	9 mm	28.6 kg
500'	126550		

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
12/2 AWG (2x3 mm²)			
100'	126310	13/32"	80 lbs
250'	126325	10 mm	36.3 kg
500'	126350		

Duplex Cable

Conductor colors: black and red

Flat Cable



Spool Length	Part #	Nominal O.D.	Wt. per 1000'
18/2 AWG (2x0.8 mm²)			
100'	121910		
250'	121925	3/16"x9/32"	49 lbs
500'	121950	5x7 mm	22.2 kg
16/2 AWG (2x1 mm²)			
100'	121710		
250'	121725	3/16"x5/16"	51 lbs
500'	121750	5x8 mm	23.1 kg
1000'	121799		
14/2 AWG (2x2 mm²)			
100'	121510		
250'	121525	7/32"x11/32"	65 lbs
500'	121550	6x9 mm	29.5 kg
1000'	121599		

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
12/2 AWG (2x3 mm²)			
100'	121310		
250'	121325	7/32"x3/8"	82 lbs
500'	121350	6x10 mm	37.3 kg
10/2 AWG (2x5 mm²)			
100'	121110		
250'	121125	1/4"x15/32"	128 lbs
400'	121140	6x12 mm	58.2 kg
800'	121180		
8/2 AWG (2x8 mm²)			
50'	120905		
100'	120910	11/32"x5/8"	230 lbs
250'	120925	9x16 mm	104.5 kg
6/2 AWG (2x13 mm²)			
50'	120705	13/32"x3/4"	364 lbs
100'	120710	10x19 mm	165.5 kg

Triplex Cable

Conductor colors: black, green and white

Flat Cable



Spool Length	Part #	Nominal O.D.	Wt. per 1000'
16/3 AWG (3x1 mm ²)			
100'	131710		
250'	131725	3/16"x15/32"	75 lbs
500'	131750	5x12 mm	34 kg
1000'	131799		
14/3 AWG (3x2 mm ²)			
100'	131510		
250'	131525	7/32"x1/2"	96 lbs
500'	131550	6x13 mm	43.6 kg
900'	131590		
12/3 AWG (3x3 mm ²)			
25'	131302		
100'	131310	7/32"x17/32"	125 lbs
250'	131325	6x14 mm	56.8 kg
700'	131370		

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
10/3 AWG (3x5 mm ²)			
100'	131110		
300'	131130	1/4"x21/32"	186 lbs
500'	131150	6x17 mm	84.5 kg
8/3 AWG (3x8 mm ²)			
25'	130902		
50'	130905	3/8"x1"	287 lbs
100'	130910	10x25 mm	130.4 kg
6/3 AWG (3x13 mm ²)			
50'	130705	7/16"x1-3/16"	470 lbs
100'	130710	11x30 mm	213.6 kg

Round Cable



Spool Length	Part #	Nominal O.D.	Wt. per 1000'
16/3 AWG (3x1 mm ²)			
100'	133710	11/32"	75 lbs
250'	133725	9 mm	34 kg
14/3 AWG (3x2 mm ²)			
100'	133510		
250'	133525	13/32"	96 lbs
900'	133590	10 mm	43.6 kg

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
12/3 AWG (3x3 mm ²)			
100'	133310	7/16"	125 lbs
250'	133325	11 mm	56.8 kg

Related Products



Cutting & Stripping Tools pages 51-53



Wire Seals page 46

TECH tip™

Round versus Flat Duplex/Triplex

Duplex and triplex cable have many different advantages to help installers. The grouped wires save time and effort by having to run only one group instead of multiple individual wires and also provides extra protection for the wire itself. But they have different advantages based on the shape too. Round cable for instance is easier to install through bulk heads, walls, panels or holes, while flat cable is easier to route long distances since it can be moved through a smaller space.



Specialty Cable



Bonded Cable **NEW**

Tinned Copper

Color conductors: red and black

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
8/2 AWG (2x8 mm²)			
25'	121802	5/8"x5/16"	172 lbs
100'	121810	15.9x7.9 mm	78.0 kg
250'	121825		
6/2 AWG (2x13 mm²)			
25'	121602A	11/16"x11/32"	236 lbs
100'	121610	17.5x8.7 mm	107.0 kg
250'	121625		



Twisted Pairs w/ Shield

Premium Tinned Copper

Color conductors: red and black

- For all metal boats and around sensitive electronics
- 93% tinned copper shield for maximum EMI and RFI rejection
- 2-3" lay for interference cancellation

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
14/2 AWG (2x2 mm²)			
100'	141410	.330"	73.2 lbs
250'	141425	8.4 mm	33.3 kg



Flat Ribbon Bonded Cable

Premium Tinned Bonded Copper

Conductor colors: red and black

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
16/2 AWG (2x1 mm²)			
100'	153110	1/8"x1/4"	32 lbs
250'	153125	3.2x6.4 mm	14.5 kg
500'	153150		



Round Mast

UL 1426 Tinned Boat Cable

Color conductors: black, blue, green, brown and red

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
14/5 AWG (5x2 mm²)			
100'	155010	1/2"	160 lbs
500'	155050	12.7 mm	79.5 kg



Round Instrument Cable

100% Mylar Foil Shield & Drain Wire

UL 1426 Tinned Boat Cable

Color conductors: red, black and bare

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
20/3 AWG (3x0.5 mm²)			
100'	153010	7/32"	30 lbs
500'	153050	5.6 mm	13.6 kg



Round Signal

100% Mylar Foil Shield and Drain Tinned Boat Cable

Conductor colors: black, red, green, blue, brown, orange, purple and yellow

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
20/8 AWG (8x0.5 mm²)			
100'	158010	5/16"	63 lbs
250'	158025	7.9 mm	28.6 kg
1000'	158099		



Signal Cable

Tinned Boat Cable

Conductor colors: red and black

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
20/2 AWG (2x0.5 mm²)			
25'	189303		
100'	122010	5/32"x1/4"	18 lbs
250'	122025	4x6.4 mm	8.1 kg
500'	122050		



European Color Code AC Cable

Premium Tinned Copper, Class K Stranding

Conductor colors: blue, brown and green with yellow stripe

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
10/3 AWG (3x5 mm²)			
500'	131151	1/4"x21/32" 6x17 mm	186 lbs 84.5 kg



Bilge Pump Cable

Premium Tinned Copper

Color conductors: black, brown and red
Insulation: grey

- Conductors specifically for bilge pumps
- Oil resistant
- SJTOW-A water resistant jacket

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
16/3 AWG (3x1 mm ²)			
100'	156610	.348"	78 lbs
250'	156625	8.85 mm	35.5 kg
14/3 AWG (3x2 mm ²)			
100'	156410	.377"	99 lbs
250'	156425	9.6 mm	45.0 kg
500'	156450		



Flat Ribbon Bonded RGB Cable

Tinned Bonded Copper

NEW

Conductor colors: red, light blue, green, and white

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
18/4 AWG (4x0.08 mm ²)			
100'	160010	3/32"x3/8"	48 lbs
1000'	160099	2.3x9.3 mm	21.8 kg
16/4 AWG (4x1 mm ²)			
100'	160110	1/8"x15/32"	64 lbs
1000'	160199	2.6x10.5 mm	29.0 kg
14/4 AWG (4x2 mm ²)			
100'	160210	7/64"x15/32"	92 lbs
1000'	160299	3.0x11.9 mm	41.7 kg



Super Flex Audio Cable

Premium Tinned Copper

- Super flexible, easy to run
- Clear jacket to blend into the environment
- Drawn copper, unidirectional lay for ultimate in sound quality
- Tinned copper for corrosion resistance in the marine environment

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
18/2 AWG (2x0.8 mm ²)			
100'	142810	.265" 6.7 mm	29 lbs 13 kg
16/2 AWG (2x1 mm ²)			
100'	142610	.319"	51 lbs
250'	142625	8.1 mm	23.1 kg
500'	142650		
14/2 AWG (2x2 mm ²)			
100'	142410	.345"	65 lbs
250'	142425	8.8 mm	29.5 kg
1000'	142499		



RGB + Speaker Cable

NEW

Tinned Bonded Copper

18 AWG conductors for RGB lighting: yellow, red, blue, green

16 AWG conductors for speaker connections: black and red

- Saves time by running only one cable
- Meets ABYC standards

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
18/4 AWG (4x0.08 mm ²) + 16/2 AWG (2x1 mm ²)			
25'	170002		
100'	170010	.352"	69.9 lbs
250'	170025	8.9 mm	31.7 kg




GTO 15 High Voltage Cable (15000V)

Color conductors: white

- Coupler output to antenna

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
14 AWG (2 mm ²)			
25'	150102	1/4"	38 lbs
100'	150110	6.4 mm	17.2 kg





Shore Power Cord

Conductor colors: black, white, green (and red 100319 only)

- High visibility yellow jacket is weather and sunlight resistant
- Ultra flexible insulation is abrasion resistant for "hard service" applications
- 600 volt rated for extra heavy-duty service
- 16/3 is 300 volt cable
- Temp rating: 140°F / 60°C

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
16/3 Phone			
100'	153510	5/16"	75 lbs
300'	153530	6 mm	34 kg
10/3 STOW			
100'	153710	21/32"	284 lbs
250'	153725	17 mm	129 kg
10/3 STW			
250'	SPC103	21/32" 17 mm	284 lbs 129 kg

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
6/3 STOW			
100'	153910	31/32" 24.4 mm	540 lbs 254.4 kg
6/3 STW			
per/ft**	100320F	31/32" 24.4 mm	540 lbs 254.4 kg
6/4 STW			
per/ft**	100319F	1-5/64" 27.4 mm	695 lbs 316 kg

SPC103, 100320F and 100319F are not tinned wire
**50 ft minimum

Coaxial Cable & Assemblies

Coaxial Cable

Premium Tinned Copper

- Features signal loss ratios of up to 50% less than other coaxial cables
- Tinned copper center conductor as well as tinned copper outer braid for corrosion resistance and easy soldering
- 96% braid for best signal strength and least interference with UV inhibited white jacket for longest life

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
RG 58CU			
100'	150510	3/16"	26 lbs
250'	150525	4.8 mm	11.8 kg
RG 59U			
250'	151025	1/4"	36 lbs
500'	151050	6.4 mm	16.3 kg
RG 8X			
100'	151510		
250'	151525	1/4"	40 lbs
500'	151550	6.4 mm	18.1 kg
1000'	151560		
RG 213			
100'	151710		
250'	151725	13/32"	110 lbs
500'	151750	10.3 mm	50 kg



Related Products
Coaxial Cable Fittings
page 32



Coaxial Cable Assemblies

Premium Tinned Copper

- All assemblies come with Ankor adhesive lined heat shrink to seal out moisture, provide strain relief and fight corrosion
- 96% tinned copper braid for optimum protection against signal loss
- 100% tinned copper center conductor and braid
- No solder or special tools required
- Special low loss SAT NAV extensions



Wire Type	RG58C/U	RG59U	RG8X	RG213
Insulation Material	PVC*	PVC	PVC	PVC*
Nominal O.D.	3/16" 4.8 mm	1/4" 6.4 mm	1/4" 6.4 mm	13/32" 10.3 mm
AWG	20	23	16	13
Conductor Stranding	19/33	Solid**	19/29	7/21
Braid Coverage	96%	96%	96%	96%
Wt. per 1000'	26 lbs 11.8 kg	36 lbs 16.3 kg	40 lbs 18.1 kg	110 lbs 50 kg
Impedance (Ohms)	50	75	50	50
Capacitance/Ft.	30.8 pF	20.5 pF	26.0 pF	30.8pF
Attenuation/100'				
@50MHz	3.3db	2.4db	2.5db	1.3db
@100MHz	4.9db	3.4db	3.7db	1.9db
@1000MHz	21.5db	12.0db	13.5db	8.0db
Velocity of Propagation	66%	66%	78%	66%

* non-contaminating insulation ** copperweld

Ends Description	Wire Length	Part #
RG58CU Two ends assembled	3'	189800
RG8X One end assembled	50'	189849



Anchor Recommends

- RG 58CU for interconnecting electronic equipment
- RG 59U for TVs and some SAT NAVs
- RG 213 for VHF runs more than 50 feet
- RG 8X for VHF runs less than 50 feet

Trailer Cable & Assemblies



Flat Ribbon Bonded Trailer Cable

Premium Tinned Bonded Copper

Conductor colors: brown, green, white, and yellow

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
16/4 AWG (4x1 mm²)			
100'	154510	1/8"x1/2"	29.2 lbs
250'	154525	3.2x12.7 mm	13.2 kg



Flat Trailer Cable

Tinned Boat Cable

Conductor colors: yellow, white, green, and brown

Spool Length	Part #	Nominal O.D.	Wt. per 1000'
16/4 AWG (4x1 mm²)			
100'	154010	3/16"x9/16"	105 lbs
300'	154030	4x14 mm	47.7 kg

Trailer Assemblies


- Molded trailer connectors are made with 16 gauge wire
- Color coding in accordance with SAE recommended practices
- Male Connector = Trailer Side / Female Connector = Vehicle Side
- 4-contact connectors are molded with an EasyGrip® for fast and easy disconnect
- Loops can be cut to the desired length for splicing into an existing wire assembly

2-wire




length	style	part #
8"	male	249111
8"	female	249112
12"	loop	249102
48"	loop	249106

3-wire




length	style	part #
8"	male	249113
8"	female	249114
12"	loop	249103
48"	loop	249107

4-wire



length	style	part #
8"	male	249115
8"	female	249116
48"	male	249117
48"	female	249118
12"	loop	249101
48"	loop	249105
72"	loop	249109

5-wire



length	style	part #
8"	male	249119
8"	female	249120
48"	male	249121
48"	female	249122
12"	loop	249104
48"	loop	249108
72"	loop	249110

NMEA 2000® Cables and Connectors

Premium Quality. Universal Fit.

Ancor NMEA 2000 approved cables and connectors simplify creating or expanding an NMEA 2000 network. Couplers are color coded to make identifying the power cable or connector easy once installed as part of an NMEA 2000 network. The color coded couplers connect to the corresponding Ancor cables and connectors creating an easy to identify network.

- NMEA 2000 Approved, 100% universal and compatible with other manufacturers' products
- NMEA micro-size



NMEA 2000 Power Cable With Tee

For power connection to an NMEA 2000 network.

The tee is color coded red to make identifying the power cable easy once installed as part of an NMEA 2000 network. The yellow couplers connect to the corresponding Ancor backbone cables and tees creating a simplified, color coded network installation.

- Includes a tee for direct connection to backbone cables
- Large 18 AWG power conductors to reduce voltage drop, provide better reliability and meet the requirements of ABYC and the USCG for minimum size power conductors

Part # 270000 3.3 ft 1 m

Ancor NMEA 2000 Color Key:

- = power connection
- = backbone connection
- = drop connection
- = power isolation
- = inline termination

Backbone vs Drop Cables



Backbone Cables:

- yellow coupler
- low loss cable

Drop Cables:

- black coupler
- slim, flexible cable



NMEA 2000 Backbone Cables

For connection to an NMEA 2000 tee connector.

The yellow couplers connect to the corresponding Ancor tees creating a simplified, color coded network installation.

- Large 18 AWG power conductors to reduce voltage drop and provide better reliability for critical backbone cables

Part # 270001 1.6 ft .5 m
 Part # 270002 6.5 ft 2 m
 Part # 270005 16 ft 5 m
 Part # 270010 32 ft 10 m



NMEA 2000 Drop Cables

For connection between an NMEA 2000 device and tee connector.

The black couplers connect to the corresponding Ancor tees creating a simplified, color coded network installation. The drop cables are smaller in diameter and more flexible than backbone cables for easy connection to NMEA 2000 devices.

- Super flexible 22 AWG power conductors for ease of installation and wire routing

Part # 270300 1.6 ft .5 m
 Part # 270301 3.3 ft 1 m
 Part # 270302 6.5 ft 2 m
 Part # 270305 16 ft 5 m



APPROVED

NMEA 2000 Tee Connectors

For connection between NMEA 2000 drop cables and backbone cables.

The yellow couplers connect to the corresponding Ancor tees and backbone cables, creating a simplified, color coded network installation. The connectors are offered in four configurations for maximum installation flexibility. The two way and four way tee connectors allow for multiple drop cables to be connected without additional backbone cable.

Part # 270101 Single Tee Connector

Part # 270103 2 Way Tee Connector

Part # 270104 4 Way Tee Connector



270101



270103



270104



APPROVED

NMEA 2000 Terminators

For proper termination of an NMEA 2000 network.

The yellow couplers connect to the corresponding Ancor tees, creating a simplified, color coded network installation. One male and one female terminator is required for each NMEA 2000 network.

Part # 270105 Female

Part # 270106 Male



270105



270106

NMEA 2000 Inline Terminator **NEW**

For proper termination of a network in a single piece, space saving design.

The inline terminator connects between a backbone cable and a drop cable, while still maintaining proper termination for the end of the network.

Part # 270114



NMEA 2000 Blanking Caps **NEW**

Cover unused couplers.

Protects unused tee connectors from dust and water. 2-pack.

Part # 270111 Female

Part # 270112 Male



270111

270112



APPROVED

NMEA 2000 90° Elbow Connector

Makes cable routing easier.

The connector is installed between two cables to reduce stress on the cables and create a compact installation.

Part # 270108



NMEA 2000 Field Serviceable Connectors **NEW**

For termination of bare NMEA cable.

Securely terminate bulk cable, or replace a broken end.

Part # 270109 Female

Part # 270110 Male



270109



270110

NMEA 2000 Through Bulkhead Adaptor **NEW**

Use for transitions through bulk heads or panels.

Simplifies installation when routing through a waterproof bulkhead or panel. Creates a connectoin point for removable equipment such as a computer interface.

Part # 270107



NMEA 2000 Power Isolator

Isolating power within a NMEA 2000 network.

The power isolator connects between NMEA 2000 tees and backbone cables while isolating the power supply within the network.

Part # 270113



NMEA 2000 Starter Kits



NMEA 2000 Single Device Starter Kit

Kit include all components needed to create a single device NMEA 2000 network.

Kit includes:

- (1) Power Cable with Tee, 3.3 ft (1m), part # 270000
- (1) Male Terminator, part # 270106
- (1) Female Terminator, part # 270105
- (1) Single Tee Connector, part # 270101
- (1) Drop Cable, 6.5 ft (2m), part # 270302

Part # 270201





NMEA 2000 Dual Device Starter Kit

Kit include all components needed to create a dual device NMEA 2000 network.

Kit includes:

- (1) Power Cable with Tee, 3.3 ft (1m), part # 270000
- (1) Male Terminator, part # 270106
- (1) Female Terminator, part # 270105
- (1) Dual Tee Connector, part # 270103
- (2) Drop Cable, 6.5 ft (2m), part # 270302

Part # 270202






NMEA 2000 Single Device Backbone Starter Kit **NEW**

Basic starter kit for adding a new NMEA 2000 network to your boat.

Kit includes:

- (1) Power Cable with Tee, 3.3 ft (1m), part # 270000
- (1) Male Terminator, part # 270106
- (1) Female Terminator, part # 270105
- (1) Single Tee Connector, part # 270101
- (1) Drop Cable, 1.64 ft (.5m), part # 270300
- (1) Backbone Cable, 16.4 ft (5m), part # 270005

Part # 270203



TECH tip™

Approved vs Certified

NMEA Components—cables and connectors must pass NMEA approval to guarantee that they are manufactured to standards which allow them to be universally used with any manufacturers approved components and certified devices.

NMEA Devices—must be certified to run the universal NMEA 2000 communications protocols to be used universally between different manufacturers devices.



TERMINALS & LUGS

Adhesive Lined Heat Shrink Terminals

26



Includes a heat activated adhesive built into the sleeve of the tubing for improved seal and strain relief.

Nylon Insulated Terminals

29



Marine Grade® Nylon terminals are designed for harsh boating applications. Nylon insulators are ideal for crimping and will not split.

Vinyl Insulated Terminals

31



Ideal for non-waterproof applications.



TERMINALS & LUGS

Coax Cable Fittings

32



Ancor's complete line of coax fittings allows custom cable lengths to fit any application.

Tinned Copper Lugs

33



Ancor Marine Grade® lugs are made from heavy-duty annealed tinned copper for maximum current flow and corrosion resistance.

Battery Terminals, Covers & Clips

35



Provides proper connections to batteries for maximum conductivity.

Electrical systems rely on Ancor terminals and lugs to securely connect a vessel's electrical system so current-carrying loads swiftly move from the source of power to the loads.

Adhesive Lined Heat Shrink Terminals EXPANDED OFFERING

- Heat activated adhesive built into the sleeve of the heat shrink tubing
- Shrinks to form a water tight seal and ultimate vibration and strain relief
- Tinned for corrosion resistance
- Pure copper for maximum current flow
- Brazed seam for maximum strength
- UL listed and CSA recognized
- Shrinks at 275°F / 135°C



Heat Shrink Ring Terminals

- UL 486A

AWG	Screw Size	Qty/ Pkg	Part #	
22-18 0.3-0.8 mm ²	#8 4 mm	3	310203	
		25	310225	
		100	310299	
	#10 4.8 mm	3	310303	
		25	310325	
		100	310399	
	1/4" 6.4 mm	3	310403	
		25	310425	
		100	310499	
		5/16" 7.9 mm	25	310525
		100	310599	
		3/8" 9.5 mm	25	310603
100	310625			
100	310699			
16-14 1-2 mm ²	#8 4 mm	3	311203	
		25	311225	
		100	311299	
	#10 4.8 mm	3	311303	
		25	311325	
		100	311399	
	1/4" 6.4 mm	3	311403	
		25	311425	
		100	311499	
		5/16" 7.9 mm	25	311503
		100	311525	
		3/8" 9.5 mm	25	311603
100	311625			
100	311699			

AWG	Screw Size	Qty/ Pkg	Part #	
12-10 3-5 mm ²	#8 4 mm	3	312203	
		25	312225	
		100	312299	
	#10 4.8 mm	3	312303	
		25	312325	
		100	312399	
	1/4" 6.4 mm	3	312403	
		25	312425	
		100	312499	
		5/16" 7.9 mm	25	312503
		100	312525	
		3/8" 9.5 mm	25	312525
100	312599			
3/8" 9.5 mm	3	312603		
	25	312625		
	100	312699		
	#10 4.8 mm	3	321303	
		25	321325	
		100	321325	
1/4" 6.4 mm	3	321403		
	25	321425		
	100	321425		
8 8 mm ²	5/16" 7.9 mm	3	321503	
	25	321525		
	3/8" 9.5 mm	3	321603	
25	321625			
1/2" 12.7 mm	3	321703		
25	321725			

Heat Shrink Snap Plugs



AWG	Gender	Qty/ Pkg	Part #
22-18 0.3-0.8 mm ²	Female	3	318803
		25	318825
		100	318899
	Male	3	318903
		25	318925
		100	318999
16-14 1-2 mm ²	Female	3	319803
		25	319825
		100	319899
	Male	3	319903
		25	319925
		100	319999

Heat Shrink Spade Terminals

- UL 486A



AWG	Screw Size	Qty/ Pkg	Part #
22-18 0.3-0.8 mm ²	#8 4 mm	3	313203
		25	313225
		100	313299
16-14 1-2 mm ²	#8 4 mm	3	314203
		25	314225
		100	314299
	#10 4.8 mm	3	314303
		25	314325
		100	314399
12-10 3-5 mm ²	#8 4 mm	3	315203
		25	315225
		100	315299
	#10 4.8 mm	3	315303
		25	315325
		100	315399

Related Products



Crimping Tools
pages 51-53



Heat Tools
page 56

Heat Shrink Butt Connectors

- UL 486C



AWG	Qty/ Pkg	Part #
22-18 0.3-0.8 mm ²	3	309003
	25	309025
	100	309099
	500	309002
16-14 1-2 mm ²	3	309103
	25	309125
	100	309199
	500	309102
12-10 3-5 mm ²	3	309203
	25	309225
	100	309299
	500	309202
8 8 mm ²	3	309303
	25	309325
	500	309302

Heat Shrink Butt Connector Packs

- Reusable jar is clear for easy identification and has a flip lid for ease of use
- Reusable compact case (6.625"L x 3.125"W x 1.375"D) fits easily in most storage areas

AWG	Qty/ Pkg	Pkg	Part #
22-18 0.3-0.8 mm ²	250	jar	309001
16-14 1-2 mm ²	250	jar	309101
12-10 3-5 mm ²	200	jar	309201
Assorted (50) 22-18, (150) 16-14, (50) 12-10 AWG	250	jar	309000
Assorted (25) each	75	case	220011
Assorted (10) 22-18, (20) 16-14, (10) 12-10 AWG	40	clam	220012



309000



220011

Heat Shrink Step-Down/Multi-Wire Connectors


- 4:1 shrink ratio tubing to ensure a watertight seal between wires
- Flared barrel with uniform copper wall ensures an easy and proper mechanical crimp
- Crimp indicator on barrel for proper placement of installation tool
- Clear heat shrink tubing ensures crimp accuracy
- Colored stripes on the barrel indicate which crimp die to use, regardless of application

AWG	Tubing Color	Pkg Qty	Part #	Barrel End 1	Barrel End 2
24-22 0.2-0.3 mm ²	Clear tube w/ white dashes □□□□□	3	320003	(1) 24-22 AWG	(1) 22-18 AWG or (2) 24-22 AWG
		25	320025		
22-18 0.3-0.8 mm ²	Clear tube w/ red dashes ■ ■ ■ ■ ■	3	320103	(1) 22-18 AWG	(1) 16-14 AWG or (2) 22-18 AWG
		25	320125		
16-14 1-2 mm ²	Clear tube w/ blue dashes ■ ■ ■ ■ ■	3	320203	(1) 16-14 AWG	(1) 12-10 AWG or (2) 16-14 AWG
		25	320225		
12-10 3-5 mm ²	Clear tube w/ yellow dashes ■ ■ ■ ■ ■	3	320303	(1) 12-10 AWG	(1) 8 AWG or (2) 12-10 AWG
		25	320325		

Kit

AWG	Qty/ Pkg	Pkg	Part #
Assorted (5) 24-22 AWG, (10) 22-18 AWG, (10) 16-14 AWG, (5) 12-10 AWG	30	jar	320000

16-14 AWG Step-Down Connector Example



320000

Related Products



Crimping Tools
pages 51-53



Heat Tools
page 56

Heat Shrink Disconnects

EXPANDED OFFERING



AWG	Tab Size	Gender	Qty/ Pkg	Part #	
22-18 0.3-0.8 mm ²	NEW .110	Female	100	326899	
	NEW .187	Female	100	336899	
			3	316803	
		.250	Female	25	316825
			100	316899	
			3	316903	
16-14 1-2 mm ²	NEW .110	Female	100	327899	
	NEW .187	Female	100	337899	
			3	317803	
		.250	Female	25	317825
			100	317899	
			3	317903	
12-10 3-5 mm ²			3	320803	
		.250	Female	25	320825
			100	320899	
			3	320903	
		.250	Male	25	320925
			100	320999	

Heat Shrink Flag Disconnects **NEW**

- 90° angle simplifies wire routing and connections
- .250 (6.4mm) tab size



AWG	Gender	Qty/ Pkg	Part #
22-18 0.3-0.8 mm ²	Female	NEW 3	356803
		NEW 25	356825
16-14 1-2 mm ²	Female	NEW 3	357803
		NEW 25	357825



SPK1614



SPK2218

Universal Speaker Connector Kits

Ancor's universal speaker connector kits include all the connectors required to install speakers regardless of manufacturer. Heat shrink disconnects provide a sealed connection for the harsh marine environment.

AWG	Qty/ Pkg	Pkg	Part #
22-18 0.3-0.8 mm ²	6	clam	SPK2218
16-14 1-2 mm ²	6	clam	SPK1614

6 pc Kits include:

- (2) .250 tab
- (2) .187 tab
- (2) .110 tab

AWG	Qty/ Pkg	Pkg	Part #
Assorted NEW	90	case	SPKKIT

90 pc Kit includes:

- 22-18 AWG:
(10) .110 tab
(10) .187 tab
(10) .250 tab
- 16-14 AWG:
(20) .110 tab
(20) .187 tab
(20) .250 tab
- Reusable compact case



SPKKIT

Related Products



Crimping Tools
pages 51-53



Heat Tools
page 56

Marine Grade® Terminals EXPANDED OFFERING

- Ancor's Marine Grade® terminals differ from automotive terminals by being designed for the harsh marine environment
- Tinned copper gives the least electrical resistance but the most corrosion protection
- Nylon insulators are easy to crimp and will not split
- Barrels are designed to tightly grip the wire with the least effort



Nylon Ring Terminals

- Nylon insulated with insulation grip
- Double crimp, funnel entry
- UL 486A

AWG	Screw Size	Qty/ Pkg	Part #	
22-18 0.3-0.8 mm ²	#6 3.6 mm	6	230201	
		25	210201	
	#8 4 mm	6	230202	
		100	220202	
	#10 4.8 mm	6	230203	
		25	210203	
			100	220203
			500	222203
	1/4" 6.4 mm	5	230204	
		25	210204	
			100	220204
			5	230205
5/16" 7.9 mm	25	210205		
	100	220205		
3/8" 9.5 mm	5	230206		
	25	210206		
	100	220206		
16-14 1-2 mm ²	#6 3.6 mm	6	230211	
		25	210211	
	#8 4 mm	6	230212	
		100	220212	
	#10 4.8 mm	6	230213	
		25	210213	
			100	220213
			500	222213
	1/4" 6.4 mm	5	230214	
		25	210214	
			100	220214
			5	230215
5/16" 7.9 mm	25	210215		
	100	220215		
3/8" 9.5 mm	5	230216		
	25	210216		
	100	220216		

AWG	Screw Size	Qty/ Pkg	Part #	
12-10 3-5 mm ²	#6 3.6 mm	5	230221	
		25	210221	
	#8 4 mm	5	230222	
		100	220222	
	#10 4.8 mm	5	230223	
		25	210223	
			100	220223
			500	222223
	1/4" 6.4 mm	4	230224	
		25	210224	
			100	220224
			4	230225
5/16" 7.9 mm	25	210225		
	100	220225		
3/8" 9.5 mm	4	230226		
	25	210226		
	100	220226		
8 8 mm ²	1/2" 12.7 mm	3	230227	
		25	210227	
			100	220227
			2	230233
	#10 4.8 mm	25	210233	
		100	222233	
	1/4" 6.4 mm	2	230234	
		25	210234	
			100	222234
			2	230235
	5/16" 7.9 mm	25	210235	
		100	222235	
3/8" 9.5 mm	2	230236		
	25	210236		
	100	222236		
1/2" 12.7 mm	1	230237		
	25	210237		
	100	222237		

AWG	Screw Size	Qty/ Pkg	Part #	
6 13 mm ²		1	230243	
		25	210243	
	#10 4.8 mm	100	222243	
		1	230244	
	1/4" 6.4 mm	25	210244	
		100	222244	
	5/16" 7.9 mm	1	230245	
		25	210245	
			100	222245
			1	230246
	3/8" 9.5 mm	25	210246	
		100	222246	
1/2" 12.7 mm	1	230247		
	25	210247		
	100	222247		
4 21 mm ²		1	230253	
		25	210253	
	#10 4.8 mm	100	222253	
		1	230254	
	1/4" 6.4 mm	25	210254	
		100	222254	
	5/16" 7.9 mm	1	230255	
		25	210255	
			100	222255
			1	230256
	3/8" 9.5 mm	25	210256	
		100	222256	
1/2" 12.7 mm	1	230257		
	25	210257		
	100	222257		

Related Products



Crimping Tools
pages 51-53

Nylon Flanged Spades

- Nylon insulated with insulation grip
- Double crimp, funnel entry
- UL 486A



AWG	Screw Size	Qty/ Pkg	Part #
22-18 0.3-0.8 mm ²	#6 3.6 mm	6	230301
		25	210301
		6	230302
	#8 4 mm	25	210302
		100	220302
		6	230303
16-14 1-2 mm ²	#10 4.8 mm	25	210303
		100	220303
		6	230311
	#6 3.6 mm	25	210311
		6	230312
		25	210312
12-10 3-5 mm ²	#8 4 mm	100	220312
		6	230313
		25	210313
	#10 4.8 mm	100	220313
		5	230321
		25	210321
12-10 3-5 mm ²	#8 4 mm	5	230322
		100	220322
		25	210322
	#10 4.8 mm	5	230323
		25	210323
		100	220323

Nylon Single Crimp Butt Connectors

- Nylon insulated seamless
- UL 486C



AWG	Qty/ Pkg	Part #
22-18 0.3-0.8 mm ²	7	230100
	25	210100
	100	220100
	500	222100
16-14 1-2 mm ²	7	230110
	25	210110
	100	220110
	500	222110
12-10 3-5 mm ²	5	230120
	25	210120
	100	220120
	500	222120

Nylon Double Crimp Butt Connectors

- Nylon insulated with insulation grip
- Funnel entry
- UL 486C



AWG	Qty/ Pkg	Part #
22-18 0.3-0.8 mm ²	3	230161
	25	210161
	100	220161
	500	222161
16-14 1-2 mm ²	3	230162
	25	210162
	100	220162
	500	222162
12-10 3-5 mm ²	2	230163
	25	210163
	100	220163
	500	222163

Nylon Fully Insulated Disconnects

- .250 (6.4 mm) tab size
- Nylon insulated with insulation grip
- Double crimp, funnel entry
- UL 310



AWG	Gender	Qty/ Pkg	Part #
22-18 0.3-0.8 mm ²	Female	4	231408
		25	211408
		100	221408
	Male	4	231409
		25	211409
		100	221409
16-14 1-2 mm ²	Female	4	231418
		25	211418
		100	221418
	Male	4	231419
		25	211419
		100	221419
12-10 3-5 mm ²	Female	3	231428
		25	211428
		100	221428
	Male	3	231429
		25	211429
		100	221429

Nylon Disconnects

- .250 (6.4 mm) tab size
- Nylon insulated with insulation grip
- Double crimp, funnel entry
- UL 310



AWG	Gender	Qty/ Pkg	Part #
22-18 0.3-0.8 mm ²	Female	4	230808
		25	210808
		100	220808
	Male	4	230809
		25	210809
		100	220809
16-14 1-2 mm ²	Female	4	230818
		25	210818
		100	220818
	Male	4	230819
		25	210819
		100	220819
12-10 3-5 mm ²	Female	3	230828
		25	210828
		100	220828
	Male	3	230829
		25	210829
		100	220829

Nylon Flag Disconnects **NEW**

- .250 (6.4 mm) tab size
- Nylon insulated with insulation grip



AWG	Gender	Qty/ Pkg	Part #
22-18 0.3-0.8 mm ²	Female	NEW 4	231601
		NEW 25	211601
16-14 1-2 mm ²	Female	NEW 4	231611
		NEW 25	211611
12-10 3-5 mm ²	Female	NEW 3	231621
		NEW 25	211621

Nylon Multi-Stack Connectors

EXPANDED OFFERING

- .250 (6.4mm) tab size
- Nylon insulated with insulation grip
- Double crimp, funnel entry
- UL 310



AWG		Qty/ Pkg	Part #
22-18 0.3-0.8 mm ²	NEW	3	230602
	NEW	25	210602A
	NEW	100	220602
16-14 1-2 mm ²		3	230612
		25	210612
		100	220612
12-10 3-5 mm ²	NEW	3	230622
	NEW	25	210622
	NEW	100	220622

Nylon 3-Way Connectors

- Nylon insulated with insulation grip
- Double crimp, funnel entry



AWG		Qty/ Pkg	Part #
16-14 1-2 mm ²		1	230510
		25	210510
12-10 3-5 mm ²		1	230520
		25	210520

Nylon Snap Plugs

- Nylon insulated with insulation grip
- Double crimp, funnel entry



AWG	Gender	Qty/ Pkg	Part #
22-18 0.3-0.8 mm ²	Female	4	230709
		25	210709
		100	220709
	Male	4	230708
		25	210708
		100	220708
16-14 1-2 mm ²	Female	4	230719
		25	210719
		100	220719
	Male	4	230718
		25	210718
		100	220718

Splash Proof Snap Plugs with Inserts

- Includes both female and male plugs



AWG		Qty/ Pkg	Part #
22-18 0.3-0.8 mm ²		4	231480
		25	211480
16-14 1-2 mm ²		4	231490
		25	211490

Vinyl Step Down Butt Connectors

- Vinyl insulated
- UL 486C



AWG		Qty/ Pkg	Part #
16-14 to 22-18 1-2 to 0.3-0.8 mm ²		3	230164
		25	210164
		100	220164
12-10 to 16-14 3-5 to 1-2 mm ²		3	230165
		25	210165
8 to 12-10 8 to 3-5 mm ²		3	230166
		25	210166

Vinyl Butt Connectors

- Vinyl insulated
- UL 486C



AWG		Qty/ Pkg	Part #
8 8 mm ²		2	230130
		25	210130
		100	222130
6 13 mm ²		1	230140
		25	210140
		100	222140
4 21 mm ²		1	230150
		25	210150
		100	222150

Splice Connects



AWG		Qty/ Pkg	Part #
18-14 0.8-2 mm ²		4	230615
		25	210615
		100	220615

Double Male-Female Adapter

- .250 (6.4mm) tab size








Qty/ Pkg	Part #
5	230613
25	210613

Related Products



Crimping Tools
pages 51-53

Coax Cable Fittings

	Description	Hex	Wire Size	Qty/ Pkg	Part #
BNC Connectors					
	Crimp-On Male Plug	.320/.250	RG59	1	203100
UHF Connectors					
	Twist UHF Male Plug (PL259)		RG58	1	202175
			RG8X	1	202176
	Solder On UHF Male Plug (PL259)		RG8U/ RG213	1	200259
	Double Female (PL258)			1	200258
	Deck Bulkhead Feed (PL258)			1	200250

Related Products



Coaxial Cable
page 18

TECH tip™

Installation Instructions for Twist-on Connectors

1. To install Ancor twist-on connectors, strip the cable to expose 9/16" of the center conductor. Strip the outer jacket to expose 1/4" of the braid. Make sure that the braided shield does not touch the inner conductor.
2. Insert the cable into the connector until the center conductor protrudes through the center of the connector.
3. Twist the small knurled end while gently pushing the connector onto the cable until resistance is felt. Crimp or solder the center conductor.
4. Cut off any excess. It is strongly recommended that a piece of Ancor 3/4" heat shrink be installed on all exterior UHF connectors to waterproof and relieve strain.

Tinned Copper Lugs


- Ancor Marine Grade® lugs are manufactured from heavy-duty annealed tinned copper, providing for maximum current flow
- 100% tin plated copper resists corrosion from salt and moisture
- Seamless barrel design allows for maximum strength when crimped
- Closed end design seals out moisture so cables stay dry and corrosion free
- UL 486A



AWG	Screw Size	Qty/ Pkg	Part #	
8 8 mm ²	#10 4.8 mm	2	252233	
		25	242233	
		100	244233	
	1/4" 6.4 mm	2	252234	
		25	242234	
	5/16" 7.9 mm	25	242235	
		100	244235	
	3/8" 9.5 mm	2	252236	
		25	242236	
	1/2" 12.7 mm	2	252237	
		10	242237	
	5/16" & 3/8"	7.9 & 9.5 mm	1/1	252231
	6 13 mm ²	#10 4.8 mm	2	252243
			25	242243
100			244243	
1/4" 6.4 mm		2	252244	
		25	242244	
5/16" 7.9 mm		25	242245	
		100	244245	
3/8" 9.5 mm		2	252246	
		25	242246	
1/2" 12.7 mm		2	252247	
		10	242247	
5/16" & 3/8"		7.9 & 9.5 mm	1/1	252241

AWG	Screw Size	Qty/ Pkg	Part #	
4 21 mm ²	#10 4.8 mm	2	252253	
		25	242253	
		100	244253	
	1/4" 6.4 mm	2	252254	
		25	242254	
	5/16" 7.9 mm	25	242255	
		100	244255	
	3/8" 9.5 mm	2	252256	
		25	242256	
	1/2" 12.7 mm	2	252257	
		10	242257	
	5/16" & 3/8"	7.9 & 9.5 mm	1/1	252251
	2 34 mm ²	1/4" 6.4 mm	2	252264
			25	242264
100			244264	
5/16" 7.9 mm		25	242265	
		100	244265	
3/8" 9.5 mm		2	252266	
		25	242266	
1/2" 12.7 mm		2	252267	
		10	242267	
5/16" & 3/8"		7.9 & 9.5 mm	1/1	252261
1 42 mm ²		1/4" 6.4 mm	2	252274
			25	242274
			100	244274
		5/16" 7.9 mm	2	252275
	25		242275	
	3/8" 9.5 mm	2	252276	
		25	242276	
	1/2" 12.7 mm	2	252277	
		10	242277	
	5/16" & 3/8"	7.9 & 9.5 mm	1/1	252271

AWG	Screw Size	Qty/ Pkg	Part #	
1/0 53 mm ²	1/4" 6.4 mm	2	252284	
		25	242284	
	5/16" 7.9 mm	2	252285	
		25	242285	
	3/8" 9.5 mm	25	242286	
		100	244286	
	1/2" 12.7 mm	2	252287	
		10	242287	
	5/16" & 3/8"	7.9 & 9.5 mm	1/1	252281
	2/0 68 mm ²	1/4" 6.4 mm	2	252294
			25	242294
		5/16" 7.9 mm	2	252295
			25	242295
		3/8" 9.5 mm	2	252296
25			242296	
1/2" 12.7 mm		2	252297	
		10	242297	
5/16" & 3/8"		7.9 & 9.5 mm	1/1	252291
3/0 85 mm ²		5/16" 7.9 mm	2	252715
			10	242715
		3/8" 9.5 mm	2	252716
			10	242716
		1/2" 12.7 mm	2	252717
	10		242717	
	5/16" 7.9 mm	2	252725	
	4/0 107 mm ²	5/16" 7.9 mm	2	252725
			10	244725
		3/8" 9.5 mm	2	252726
			10	242726
		1/2" 12.7 mm	2	252727
			10	242727



Lug Dimensions

AWG	A	B	C
8	0.465"	0.190"	1.313"
6	0.540"	0.232"	1.512"
4	0.545"	0.280"	1.606"
2	0.650"	0.336"	1.622"-1.772"
1	0.645"	0.360"	1.718"-1.845"

AWG	A	B	C
1/0	0.725"	0.410"	1.845"
2/0	0.825"	0.460"	2.236"-2.268"
3/0	0.910"	0.510"	2.323"
4/0	1.015"	0.560"	2.563"

Related Products



Crimping Tools
pages 51-53

90° Tinned Copper Lugs **NEW**

90° bend for ease of wire routing

AWG	Screw Size	Qty/ Pkg	Part #
6 13 mm ²	5/16" 7.9 mm	2	262245
	3/8" 9.5 mm	2	262246
4 21 mm ²	5/16" 7.9 mm	2	262255
	3/8" 9.5 mm	2	262256
2 34 mm ²	5/16" 7.9 mm	2	262265
	3/8" 9.5 mm	2	262266
1 42 mm ²	5/16" 7.9 mm	2	262275
	3/8" 9.5 mm	2	262276
1/0 53 mm ²	5/16" 7.9 mm	2	262285
	3/8" 9.5 mm	2	262286
2/0 68 mm ²	5/16" 7.9 mm	2	262295
	3/8" 9.5 mm	2	262296
3/0 85 mm ²	5/16" 7.9 mm	2	262715
	3/8" 9.5 mm	2	262716
4/0 107 mm ²	5/16" 7.9 mm	2	262725
	3/8" 9.5 mm	2	262726



**EXPANDED
OFFERING**

Heavy-duty Butt Connectors

100% Tinned Copper

AWG	Qty/ Pkg	Part #
8 8 mm ²	2	252130
	25	242130 NEW
6 13 mm ²	2	252140
	25	242140 NEW
4 21 mm ²	2	252150
	25	242150 NEW
2 34 mm ²	2	252160
	25	242160 NEW
1 42 mm ²	2	252170
	25	242170 NEW
1/0 53 mm ²	2	252180
	25	242180 NEW
2/0 68 mm ²	2	252190
	25	242190 NEW



Anti-Corrosion Rings

- Prevents acid leak corrosion
- Chemically treated to prevent terminal corrosion
- Made from non-woven felt and saturated in a battery corrosion preventative compound.

Color	Qty/ Pkg	Part #
Red/Black	1/1	260405



260010

260012

Tinned Brass Battery Terminals

Description	Positive/ Negative	Stud Size	Qty/ Pkg	Part #
Wing Nut Style Yellow Brass Nut	Negative	5/16" (8 mm)	1	260010
	Positive	3/8" (10 mm)	1	260012
	Pos/Neg	5/16" & 3/8" (8 & 10 mm)	1/1	260322



260100

260200

Lead Battery Terminals

Description	Positive/ Negative	Stud Size	Qty/ Pkg	Part #
Wing Nut Style Yellow Brass Nut	Negative	5/16" (8 mm)	1	260100
	Positive	3/8" (10 mm)	1	260200
	Pos/Neg	5/16" & 3/8" (8 & 10 mm)	1/1	260325



Battery Clips

Color	Size	Qty/ Pkg	Part #
Red/Black	10A	1/1	260505



260350

260381

Battery Terminal Boots

Description	Size	Color	Qty/ Pkg	Part #
Wing Nut Style	4 & 2 (19 & 32 mm ²)	Black/Red	1/1	260350
Right Angle	8-2 (8-32 mm ²)	Red	1	260381

Related Products



Battery Terminal Cleaner
page 57




Adhesive Lined Heavy Wall
Battery Cable Tubing
page 39

WIRE MANAGEMENT

Adhesive Lined Heat Shrink Tubing

38



Ancor uses crosslinked polyolefin material for its superior strength and burn resistance. A heat activated adhesive lining creates an impervious seal and provides strain relief.

Repair & Electrical Tape

40



A wide range of repair tape and electrical tape in multiple colors.

Cable Ties

41



Ancor offers a wide variety of materials, sizes and styles including the innovative Self-Cutting Cable Tie which is now available in a mounting version.

Wire Seals

46



Overlapping clamping spines allow for superior pull-out resistance and protection. Strain relief fittings are resistant to salt water, acids, oil, and are not corrosive for marine applications.



WIRE MANAGEMENT

Cable Clamps

45



Stainless steel and Nylon cable clamps are corrosion resistant for marine applications. They absorb shock and vibrations; reducing unwanted noise.

Grommets

46



Provides abrasion resistance for wires passing through panel holes. Flexible construction makes installation simple.

Split Loom & Spiral Wrap

46



Allows flexible routing of cable harnesses and provides abrasion resistance for wire and cable.

Wire Management Kits

47



Ancor offers a wide variety of preassembled kits for all of your wire management projects.



Wire management is integral in making sure that wires and connections are kept organized and protected per ABYC

Adhesive Lined Heat Shrink Tubing (ALT)

- Cross Linked polyolefin tubing is much stronger than PVC tubing and will not burn like PVC
- Heat activated adhesive lining provides impervious seal to salt water, oil, acids, and sunlight as well as providing strain relief
- Highest shrink ratio - shrinks to 1/3 original size
- Shrinks at 257°F / 125°C
- Operating temperature range of -40°F to 230°F / -40°C to 110°C



Wire Range	ALT Dia	Color	Length	Qty/ Pkg	Part #
<18 AWG <0.8 mm ²	<1/8" <3.2 mm	Black	3" 7.6 cm	3	301103
			6" 15.2 cm	10	301106
			12" 30.5 cm	10	301124
			48" 122 cm	1	301148
20-12 AWG 0.5-3 mm ²	3/16" 4.8 mm	Black	3" 7.6 cm	3	302103
			6" 15.2 cm	10	302106
			12" 30.5 cm	10	302124
			48" 122 cm	1	302148
		Red	3" 7.6 cm	3	302603
			6" 15.2 cm	10	302606
			12" 30.5 cm	10	302624
			48" 122 cm	1	302648
16-10 AWG 1-5 mm ²	1/4" 6.4 mm	Black	3" 7.6 cm	3	303103
			6" 15.2 cm	10	303106
			12" 30.5 cm	10	303124
			48" 122 cm	1	303148
		Black/Red	3" 7.6 cm	1/1	303602
			6" 15.2 cm	5	303606
			12" 30.5 cm	10	303624
			48" 122 cm	1	303648
12-8 AWG 3-8 mm ²	3/8" 9.5 mm	Black	3" 7.6 cm	3	304103
			6" 15.2 cm	5	304106
			12" 30.5 cm	5	304124
			48" 122 cm	1	304148
		Black/Red	3" 7.6 cm	1/1	304602
			6" 15.2 cm	5	304606
			12" 30.5 cm	5	304624
			48" 122 cm	1	304648
8-4 AWG 8-19 mm ²	1/2" 12.7 mm	Black	3" 7.6 cm	3	305103
			6" 15.2 cm	5	305106
			12" 30.5 cm	5	305124
			48" 122 cm	1	305148
		Black/Red	3" 7.6 cm	1/1	305602
			6" 15.2 cm	5	305606
			12" 30.5 cm	5	305624
			48" 122 cm	1	305648

Wire Range	ALT Dia	Color	Length	Qty/ Pkg	Part #
8-2/0 AWG 13-62 mm ²	3/4" 19 mm	Black	3" 7.6 cm	3	306103
			6" 15.2 cm	4	306106
			12" 30.5 cm	4	306124
			48" 122 cm	1	306148
		Black/Red	3" 7.6 cm	1/1	306602
			6" 15.2 cm	3	306603
			12" 30.5 cm	4	306606
			48" 122 cm	1	306648
2-4/0 AWG 32-103 mm ²	1" 25.4 mm	Red	3" 7.6 cm	3	306903
			6" 15.2 cm	4	306906
			12" 30.5 cm	4	306924
			48" 122 cm	1	306948
		Yellow	3" 7.6 cm	3	306903
			6" 15.2 cm	4	306906
			12" 30.5 cm	4	306924
			48" 122 cm	1	306948
8-2/0 AWG 8-62 mm ²	3/4" 19 mm	Black	3" 7.6 cm	3	307103
			6" 15.2 cm	3	307106
			12" 30.5 cm	3	307124
			48" 122 cm	1	307148
		Black/Red	3" 7.6 cm	1/1	307602
			6" 15.2 cm	3	307603
			12" 30.5 cm	3	307606
			48" 122 cm	1	307648
Red	3" 7.6 cm	3	307603		
	6" 15.2 cm	3	307606		
	12" 30.5 cm	3	307624		
	48" 122 cm	1	307648		
Yellow	3" 7.6 cm	3	307903		
	6" 15.2 cm	4	307906		
	12" 30.5 cm	4	307924		
	48" 122 cm	1	307948		

Kits

Wire Range	ALT Dia	Color	Length	Qty/ Pkg	Part #
20-2/0 AWG .5-62 mm ²	3/16"-3/4" 4.8-19 mm	Black	3" 7.6 cm	8	301503
			6" 15.2 cm	8	301506
12-8 AWG 3-8 mm ²	3/8" 9.5 mm	Assorted (yw, wh, bl, gr, rd)	3" 30.5 cm	5	304503
			6" 122 cm	5	304506
8-2/0 AWG 8-62 mm ²	3/4" 19 mm	Assorted (yw, wh, bl, gr)	3" 7.6 cm	4	306503

Adhesive Lined Tubing Specifications (3:1 ratio)

Size	Shrinks to	Wire Range (AWG)
1/8" 3.2 mm	1/32" 0.8 mm	<18 < 0.8 mm ²
3/16" 4.8 mm	1/16" 1.6 mm	20-12 0.5-3 mm ²
1/4" 6.4 mm	5/64" 2 mm	16-10 1-5 mm ²
3/8" 9.5 mm	1/8" 3.2 mm	12-8 3-8 mm ²
1/2" 12.7 mm	5/32" 4 mm	8-4 8-19 mm ²
3/4" 19 mm	1/4" 6.4 mm	8-2/0 13-62 mm ²
1" 25.4 mm	5/16" 7.9 mm	2-4/0 32-103 mm ²

Related Products




Nylon terminals
page 29



Heat Tools
page 56

Adhesive Lined Heavy Wall Battery Cable Tubing (BCT)

- 3:1 ratio
- Shrinks at 257°F / 125°C
- UL 224



BCT Dia.	BCT Color	Length	Qty/ Pkg	Part #	
3/4" 19 mm	Black	3"	7.6 cm	3	326103
		6"	15.2 cm	3	326106
		12"	30.5 cm	3	326124
		48"	122 cm	1	326148
	Black/Red	3"	7.6 cm	1/1	326202
		6"	15.2 cm	3	326603
		12"	30.5 cm	3	326606
		48"	122 cm	1	326624
	Red	3"	7.6 cm	3	326648
		6"	15.2 cm	3	326903
		12"	30.5 cm	3	326906
		48"	122 cm	1	326924
Yellow	3"	7.6 cm	3	326903	
	6"	15.2 cm	3	326906	
	12"	30.5 cm	3	326924	

BCT Dia.	BCT Color	Length	Qty/ Pkg	Part #	
1" 25 mm	Black	3"	7.6 cm	2	327103
		6"	15.2 cm	2	327106
		12"	30.5 cm	2	327124
		48"	122 cm	1	327148
	Black/Red	3"	7.6 cm	1/1	327202
		6"	15.2 cm	2	327603
		12"	30.5 cm	2	327606
		48"	122 cm	1	327624
	Red	3"	7.6 cm	2	327648
		6"	15.2 cm	2	327903
		12"	30.5 cm	2	327906
		48"	122 cm	1	327924
Yellow	3"	7.6 cm	2	327903	
	6"	15.2 cm	2	327906	
	12"	30.5 cm	2	327924	

Adhesive Lined Heavy Wall Tubing Specifications (3:1 ratio)

Size	Shrinks to	Wire Range (AWG)
3/4" 19 mm	1/4" 6 mm	8-2/0 13-62 mm ²
1" 25 mm	3/8" 9 mm	2-4/0 32-103 mm ²



TECH tip

Properly Shrinking Heat Shrink Tubing

To properly shrink heat shrink tubing, start by selecting a heat source that will apply the appropriate temperature. Heat shrink tubing will state the shrink temperature, while heat tools are rated based on flame temperatures. Once a heat tool is selected, apply heat gradually to avoid shrinking the tubing inconsistently or burning the tubing. Additionally, continually moving the heat source along the length of the tube will reduce the likelihood of burning the tubing during installation.

Related Products



Lugs
page 33




Heat Tools
page 56

Repair Tape

Repair tape fuses only to itself when applied under tension. No sticky residue remains on wrapped surfaces.

- Operates and remains flexible from -60°F to 500°F / -51°C to 260°C
- Stretches up to 300% its original length with 60 ppi tear strength
- A permanent air and water tight seal
- Excellent UV resistance
- Begins to bond immediately on contact with itself

Color	Length	Part #	Pkg Qty
Black	1"x10'	341010	1/roll
Blue	1"x10'	342010	1/roll
Clear	1"x10'	343010	1/roll
Green	1"x10'	344010	1/roll
Grey	1"x10'	345010	1/roll
Red	1"x10'	346010	1/roll
White	1"x10'	347010	1/roll
Yellow	1"x10'	348010	1/roll



Premium Electrical Tape

Quality electrical tape designed for general purpose electrical applications.

- Made from low-lead 7-mil PVC material
- For applications up to 600V
- Temp rating up to 176°F / 80°C
- UV and moisture resistant

Color	Length	Part #	Pkg Qty
Black	3/4"x66'	331066	1/roll
Blue	3/4"x66'	332066	1/roll
Brown	3/4"x66'	333066	1/roll
Orange	3/4"x66'	334066	1/roll
Green	3/4"x66'	335066	1/roll
Red	3/4"x66'	336066	1/roll
White	3/4"x66'	337066	1/roll
Yellow	3/4"x66'	338066	1/roll
Assorted (1 ea of black, red, white, green & yellow)	1/2"x20'	339066	5/roll




Cable Ties

Ancor offers a wide variety of materials, styles, and sizing options.

With a unique design and high-quality construction, Ancor cable ties provide a great solution for bundling wire, cable, hoses, cords, and countless other applications.




Standard Cable Ties

Length	Color	Unit Qty	Part #		Bundle Dia Max	Tensile Strength
4"	natural	25	199200	yes	13/16"	18 lbs
		100	199201	yes	13/16"	18 lbs
		1000	199344	yes	13/16"	18 lbs
	UVB*	25	199202	yes	13/16"	18 lbs
		100	199203	yes	13/16"	18 lbs
		1000	199349	yes	13/16"	18 lbs
6"	natural	25	199246	yes	1-3/8"	45 lbs
		100	199247	yes	1-3/8"	45 lbs
		1000	199345	yes	1-3/8"	45 lbs
	UVB*	25	199248	yes	1-3/8"	45 lbs
		100	199249	yes	1-3/8"	45 lbs
		1000	199350	yes	1-3/8"	45 lbs
8"	natural	25	199204	yes	2"	75 lbs
		100	199205	yes	2"	75 lbs
		1000	199346	yes	2"	75 lbs
	UVB*	25	199206	yes	2"	75 lbs
		100	199207	yes	2"	75 lbs
		1000	199254	yes	2"	75 lbs
11"	natural	25	199208	yes	3"	75 lbs
		100	199209	yes	3"	75 lbs
		1000	199347	yes	3"	75 lbs
	UVB*	25	199210	yes	3"	75 lbs
		100	199211	yes	3"	75 lbs
		1000	199351	yes	3"	75 lbs
14"	natural	25	199212	yes	4"	75 lbs
		100	199213	yes	4"	75 lbs
		1000	199348	yes	4"	75 lbs
	UVB*	25	199214	yes	4"	75 lbs
		100	199215	yes	4"	75 lbs
		1000	199352	yes	4"	75 lbs

* UV Resistant



Heavy-duty Cable Ties

Length	Color	Unit Qty	Part #		Bundle Dia Max	Tensile Strength
15"	UVB*	25	199259	yes	4"	175 lbs
		100	199260	yes	4"	175 lbs
17"	natural	10	199216	yes	4-9/10"	175 lbs
	UVB*	10	199217	yes	4-9/10"	175 lbs
24"	natural	10	199218	yes	7"	175 lbs
	UVB*	10	199219	yes	7"	175 lbs
36"	natural	10	199220	yes	10-3/10"	175 lbs
	UVB*	10	199221	yes	10-3/10"	175 lbs
48"	natural	10	199222	yes	14-3/10"	175 lbs
	UVB*	10	199223	yes	14-3/10"	175 lbs

* UV Resistant

Related Products



NEW Diagonal Cutting Pliers
page 54



Mounting Bases
page 42



Mounting Cable Ties

Length	Color	Unit Qty	Part #		Bundle Dia Max	Tensile Strength
4"	UVB*	25	199245	yes	3/4"	18 lbs
	natural	25	199250	yes	1-3/8"	30 lbs
6"	natural	100	199251	yes	1-3/8"	30 lbs
	UVB*	25	199252	yes	1-3/8"	30 lbs
		100	199253	yes	1-3/8"	30 lbs
	8"	natural	25	199226	yes	2"
natural		100	199227	yes	2"	50 lbs
UVB*		25	199228	yes	2"	50 lbs
		100	199229	yes	2"	50 lbs
14"	natural	25	199230	yes	4"	50 lbs
	UVB*	25	199257	yes	4"	50 lbs
		100	199258	yes	4"	50 lbs

* UV Resistant




199224

199261

199225

Cable Tie Kits

Length	Description	Unit Qty	Part #		Bundle Dia Max	Tensile Strength
8"	assorted colors	24	199224	yes	2"	75 lbs
4", 6", 8"	natural/UVB*	25	199261	yes	13/16", 2"	18, 75 lbs
4", 6", 8"	natural color	500	199225	yes	13/16", 1-1/2", 2"	18, 45, 75 lbs

* UV Resistant

▲ DoubleLock™ on 6" and 8" ties only

Low Profile/Hose Cable Ties

- Reduced head height and contour design conforms to the shape of the wire bundle or hose
- Round design and side tail entry creates a round shape optimal for hoses
- Trimmed tail retracts into cavity leaving a clean, low profile installation
- Tamper-proof pawl is inaccessible after installation
- 50 lbs tensile strength exceeds industry standards



Length	Color	Unit Qty	Part #	Tensile Strength
8"	UVB*	20/bag	199324	50 lbs
		100/bag	199325	50 lbs
11"	UVB*	20/bag	199328	50 lbs
		100/bag	199329	50 lbs

* UV Resistant

Screw Mounting Bases

- #8 bases, 7/10" x 1/2"
- #10 bases, 1" x 5/8"

Description	Unit Qty	Part #
#8 screw, natural	25	199231
#8 screw, natural	100	199232
#10 screw, natural	25	199262
#10 screw, natural	100	199263



199262

Adhesive Lined Mounting Bases

- 1" x 1"

Description	Unit Qty	Part #
Natural	5	199233
Natural	25	199234
UVB*	5	199235
UVB*	25	199236

* UV Resistant

199233



199235

Self-cutting Cable Ties

Save time and frustration using the latest innovation from Ancor, a self-cutting cable tie. Simply lock and twist to finish the job, with no need for additional tools! Integrated stainless steel blade leaves a clean flush cut, which improves appearance and eliminates the sharp tail while maintaining a tensile strength above industry standards.



Standard Self-cutting Cable Ties

Length	Color	Unit Qty	Part #	Tensile Strength	
4"	Natural	50/bag	199333	35 lbs	
		500/bag	199334	35 lbs	
	UVB*	50/bag	199336	35 lbs	
		500/bag	199337	35 lbs	
6"	Natural	50/bag	199339	35 lbs	
		500/bag	199340	35 lbs	
	UVB*	50/bag	199342	35 lbs	
		500/bag	199343	35 lbs	
8"	Natural	20/bag	199274	50 lbs	
		50/bag	199275	50 lbs	
		500/bag	199267	50 lbs	
	UVB*	20/bag	199276	50 lbs	
		50/bag	199277	50 lbs	
		500/bag	199264	50 lbs	
	11"	Natural	20/bag	199278	50 lbs
			50/bag	199279	50 lbs
500/bag			199268	50 lbs	
UVB*		20/bag	199280	50 lbs	
		500/bag	199265	50 lbs	
14"	Natural	20/bag	199282	50 lbs	
		50/bag	199283	50 lbs	
		500/bag	199269	50 lbs	
	UVB*	20/bag	199284	50 lbs	
		500/bag	199285	50 lbs	
			199266	50 lbs	

* UV Resistant



Heavy-duty Self-cutting Cable Ties

Length	Color	Unit Qty	Part #	Tensile Strength
15"	Natural	20/bag	199320	120 lbs
		100/bag	199321	120 lbs
	UVB*	20/bag	199318	120 lbs
		100/bag	199319	120 lbs
17"	Natural	10/bag	199323	120 lbs
	UVB*	10/bag	199322	120 lbs

* UV Resistant



TECH tip

Wire Bundling Per ABYC Guidelines

ABYC states: "Conductors shall be supported throughout their length or shall be secured at least every 18 inches (455mm) by one of the following methods:


- By means of non-metallic clamps sized to hold the conductors firmly in place. The material shall be resistant to oil, gasoline, and water and shall not break or crack within a temperature range of 30°F (-34°C) to 250°F (121°C)

All of Ancor's cable ties are resistant to oil, gasoline, and water and are rated for use within the ABYC specified range.

Related Products



Mounting Bases
page 42



Mounting Self-cutting Cable Ties

Length	Color	Unit Qty	Part #	Tensile Strength
8"	Natural	20/bag	199309	50 lbs
		50/bag	199310	50 lbs
		500/bag	199311	50 lbs
	UVB*	20/bag	199300	50 lbs
		50/bag	199301	50 lbs
		500/bag	199302	50 lbs
11"	Natural	20/bag	199312	50 lbs
		50/bag	199313	50 lbs
		500/bag	199314	50 lbs
	UVB*	20/bag	199303	50 lbs
		50/bag	199304	50 lbs
		500/bag	199305	50 lbs
14"	Natural	20/bag	199315	50 lbs
		50/bag	199316	50 lbs
		500/bag	199317	50 lbs
	UVB*	20/bag	199306	50 lbs
		50/bag	199307	50 lbs
		500/bag	199308	50 lbs


* UV Resistant

TECH tip™

Cable Ties and Moisture

To prevent brittleness and cracking, a certain amount of moisture is incorporated into the Nylon 6/6 material that makes cable ties. Over time, this added moisture can evaporate; especially in dry conditions with low relative humidity. The following steps will help cable ties maintain their pliability and tensile strength:

- Cable ties should be stored in the manufacturer's original packaging until ready for use.
- Partial cable tie bags should be closed or sealed if at all possible. Several drops of water can be added to the bag to provide moisture.
- Cable ties should not be stored in an unheated warehouse or similar location.
- Cable ties inventory should be rotated frequently and used within one year of purchase.



Stainless Steel Cushion Clamps

- Prevents corrosion
- Resistant to oils, acids, salt water
- Temperatures range from -50° to 300°F / -46°C to 149°C
- Absorbs shock and vibration
- Reduces unwanted noise
- 1/4" clearance mounting hole
- 304 stainless steel



Wire Bundling per ABYC Guidelines

ABYC states: Conductors shall be supported throughout their length or shall be secured at least every 18 inches (455mm) by one of the following methods:

- By means of non-metallic clamps sized to hold the conductors firmly in place. The material shall be resistant to oil, gasoline, and water and shall not break or crack within a temperature range of 30°F to 250°F (-34°C to 121°C)
- By means of metal clamps lined with an insulating material resistant to the effects of oil, gasoline, and water

All of Ancor's cable clamps are resistant to oil, gasoline, and water and are rated for use within the ABYC specified range. Stainless steel cushion clamps are designed to perform within a wider temperature range and provide additional shock, vibration and noise protection compared to nylon cable clamps.

Nominal I.D.	Qty/ Pkg	Part #	Band Thickness	Width w/ Cushion	Screw Size
3/16"	5 mm	10	403182	0.04	3/8" 10 mm #8 4 mm
1/4"	6 mm	10	403252	0.04	3/8" 10 mm #8 4 mm
5/16"	8 mm	10	403312	0.04	3/8" 10 mm #8 4 mm
3/8"	10 mm	10	403372	0.04	3/8" 10 mm #8 4 mm
1/2"	13 mm	10	403502	0.06	1/2" 13 mm #10 5 mm
9/16"	14 mm	10	403562	0.06	1/2" 13 mm #10 5 mm
5/8"	16 mm	10	403622	0.06	1/2" 13 mm #10 5 mm
3/4"	19 mm	10	403752	0.06	1/2" 13 mm #10 5 mm
7/8"	22 mm	10	403872	0.06	1/2" 13 mm #10 5 mm
1"	25 mm	10	403892	0.06	1/2" 13 mm #10 5 mm
1-1/4"	32 mm	10	403902	0.06	1/2" 13 mm #10 5 mm
1-1/2"	38 mm	10	404152	0.06	1/2" 13 mm #10 5 mm
1-3/4"	44 mm	10	404172	0.06	1/2" 13 mm #10 5 mm
2"	51 mm	10	404202	0.06	1/2" 13 mm #10 5 mm
2-1/2"	64 mm	10	404252	0.06	1/2" 13 mm #10 5 mm
3"	76 mm	10	404302	0.06	1/2" 13 mm #10 5 mm
3-1/2"	89 mm	10	404352	0.06	1/2" 13 mm #10 5 mm

#8 = 0.167" / #10 = 0.203"

Nylon Cable Clamps

- Made from nylon for maximum strength
- Resistant to solvents, oils, acids and moisture
- Unique screw hole alignment feature to speed installation
- Absorbs shock and vibration; reduces unwanted noise



Nominal I.D.	Color	Qty/ Pkg	Part #
1/8"	3 mm	Natural	25 401122
3/16"	5 mm	Natural	25 401182
1/4"	6 mm	Natural	6 401251
		Natural	25 401252
		UV Black	100 401255
5/16"	7 mm	Natural	25 401312
		UV Black	25 402312
3/8"	9 mm	Natural	25 401372
		UV Black	100 401375
7/16"	11 mm	Natural	25 402372
1/2"	12 mm	Natural	25 401432
		UV Black	25 401502
		UV Black	25 402502

Nominal I.D.	Color	Qty/ Pkg	Part #
5/8"	15 mm	Natural	25 401622
		UV Black	25 402622
3/4"	19 mm	Natural	25 401752
		UV Black	25 402752
1"	25 mm	Natural	25 401892
		UV Black	25 402892
1-1/4"	32 mm	Natural	25 401912
1-1/2"	38 mm	Natural	25 401932

Kit

- (9) of each 1/8", 3/16", 1/4", 5/16", 3/8" & 1/2"

Nominal I.D.	Color	Qty/ Pkg	Part #
1/8"-1/2"	3-12 mm	Natural	54 400000

Wire Seals

- Made of Nylon 6/6 flame resistant, self extinguishing Buna-N form seal
- All seals exceed NEMA Type 4X and Type 6 specs
- Overlapping clamping spines allow for superior pull-out protection and resistance
- Strain relief fittings are resistant to salt water, acids, alkalis, alcohol, oils and are non-corrosive for use in the marine environment
- Good underwater to 300 feet / 91.4 m (150 PSIG) provided there is a liquid tight seal between body and housing
- Provide low cost cable entries into panels and junction boxes
- UL 94 v-0



Description	For Use with	Thread Size	Cable Range	Clearance Hole	Body Length	Thread Length	Qty/ Pkg	Part #
Round Cable	18-10 AWG	3/8" NPT	.08"--.24" 2-6 mm	.68"	.87"	.59"	1	764998
Round Cable	10-2 AWG	1/2" NPT	.20"-.47" 5-12 mm	.83"	1.06"	.51"	1	765000
Round or Flat Cable	4-1, 14/3-12/3 & 12/2-10/2 AWG	1/2" NPT	.24"-.55" 6-14 mm	.83"	1.10"	.51"	1	765002
Round Cable	1-3/0 AWG	3/4" NPT	.51"-.71" 13-18 mm	1.05"	1.22"	.51"	1	765004
Round Cable	4/0 AWG	1" NPT	.71"-.98" 18-25 mm	1.35"	1.53"	.75"	1	765006
Flat Cable	14/3-12/3 & 12/2-10/2	1/2" NPT	.31"-.56" 8-14 mm	.83"	1.10"	.51"	1	765010
Flat Cable	14/3-12/3 & 12/2-10/2	3/4" NPT	.31"-.56" 8-14 mm	1.05"	1.22"	.51"	1	765012

Grommets

- Provide instant abrasion resistance to wires passing through panel holes
- Flexible black vinyl makes installation simple

Hole Size	Inside Diameter	Panel Width	Qty/ Pkg	Part #	
3/8"	10 mm	1/4" 6 mm	3/32" 2 mm	5	760375
1/2"	13 mm	3/8" 10 mm	1/16" 2 mm	5	760500
1/4-3/4" Assortment Combo Pack (10 each of 1/4", 5/16", and 3/8", 5 each of 1/2", 11/16", and 3/4")			45	750000	



Spiral Wrap & Split Loom

- Permits flexible routing of cable harnesses
- Provides abrasion protection for wire and cable
- Allows lead outs at any point for greatest ease of installation
- Split loom temperature range is -40°F to 275°F / -40°C to 135°C

TECH tip

Wire Bundling per ABYC Guidelines

ABYC states: "Conductors that may be exposed to physical damage shall be protected by loom, conduit, tape, raceways, or other equivalent protection. When AC and DC conductors are run together, the AC conductors shall be sheathed, bundled, or otherwise kept separate from the DC conductors. Loom used to cover conductors shall be self-extinguishing. The base product (or resin) shall be classified as V-2 or better, in accordance with UL 94, Tests For Flammability Of Plastic Materials."

Marine Grade® Spiral Wrap



Diameter	Ft/Pkg	Part #	Bundle Range
			Min Max
1/4"	6 mm	10'	3/16" 2"
			4.8 mm 5 cm
3/8"	10 mm	10'	5/16" 3"
		100'	8 mm 7.6 cm
1/2"	13 mm	10'	25/64" 4"
		100'	10 mm 10.2 cm
3/4"	19 mm	10'	3/4" 5"
		100'	19 mm 12.7 cm
1"	25 mm	5'	1" 7"
		100'	25 mm 17.8 cm



Self-extinguishing Split Loom

Diameter	Ft/Pkg	Part #	
3/8"	10 mm	10'	453382
		100'	453386
1/2"	13 mm	10'	453502
		100'	453506
3/4"	19 mm	10'	453752
		100'	453756
1"	25 mm	5'	453901
		100'	453906

Wire Management Kits



160 Piece Heat Shrink Connectors and Terminals Kit

Butt Connectors

- (10) 22-18 AWG, (20) 16-14 AWG, (10) 12-10 AWG

Ring Terminals

- (15) 22-18 AWG #10, (15) 16-14 AWG #8, (15) 16-14 AWG #10, (15) 16-14 AWG 1/4", (10) 12-10 AWG #10, (10) 12-10 AWG 1/4", (10) 12-10 AWG 3/8"

Disconnects

- (20) 16-14 AWG female, (10) 16-14 AWG male

Part # 320101



440 Piece Nylon Connectors and Terminals Kit

Butt Connectors

- (40) 22-18 AWG, (75) 16-14 AWG, (40) 12-10 AWG

Ring Terminals

- (25) 22-18 AWG #8, (25) 16-14 AWG #8, (50) 16-14 AWG #10, (25) 12-10 AWG #8, (25) 12-10 AWG #10

Disconnects

- (50) 16-14 AWG fully insulated female, (30) 16-14 AWG fully insulated male, (25) 16-14 AWG female, (30) 16-14 AWG male

Part # 250101



100 Piece Tinned Copper Lug Kit

- (10) 8 AWG, 5/16", (10) 8 AWG, 3/8"
- (10) 6 AWG, 5/16", (10) 6 AWG, 3/8"
- (10) 4 AWG, 5/16", (10) 4 AWG, 3/8"
- (10) 2 AWG, 5/16", (10) 2 AWG, 3/8"
- (5) 1/0 AWG, 5/16", (5) 1/0 AWG, 3/8"
- (5) 2/0 AWG, 5/16", (5) 2/0 AWG, 3/8"

Part # 255101



47 Piece Adhesive Lined Heat Shrink Tubing Kit

Black

- (10) 3/16" x 6"
- (10) 1/4" x 6"
- (10) 3/8" x 6"
- (5) 1/2" x 6"
- (3) 3/4" x 3"
- (3) 1" x 3"

Red

- (3) 3/4" x 3"
- (3) 1" x 3"

Part # 330101



Promotional Storage Rack

Part # P33407

Individual Empty Trays

Part # P33406 6 compartment

Part # P33412 12 compartment

TOOLS & TESTERS

Cut/Strip/Crimp Tools

50



Ancor offers a broad range of wire management and termination tools for all of your wiring projects.

Crimpers

52



Ancor offers other speciality tools to provide users with everything needed for any project.

Pliers and Screwdrivers

54



Insulated pliers and screw drivers for added safety when working on an electrical project.

TOOLS & TESTERS

Tool Kits

55



Pre assembled kits provide the tools and materials you need for wiring projects.

Heat Tools

56



Ancor offers a range of heat tools, including the new dual setting heat gun, that are perfect for multiple projects from heat shrink tubing to paint stripping.

Digital Multimeters

58



Multimeters to suit any electrical testing requirements.



Every vessel requires quality tools and testing devices to ensure quick projects and larger refits can be accomplished accurately and to ABYC standards.



Wire & Cable Cutter

- Steel forged blades easily cut 22 AWG to 2/0 AWG copper wire and cable
- Contoured cushion grips for comfort and ease of use
- Length: 9.25" (23.5 cm)

Part # 703005



Heavy-duty Wire & Cable Cutter

- Steel forged blades easily cut up to 350MCM (2 sizes larger than 4/0 AWG) copper wire and cable
- Strong fiberglass handles with thermoplastic rubber grips for comfort and slip resistance
- Length: 17.5" (44.4 cm)

Part # 703006



Heavy-duty Wire Scissors **NEW**

- Corrosion resistant stainless steel blades
- Ergonomic overmolded handles for comfort and safety
- Cut wire up to 6 AWG (13 mm²)
- Includes safety holster with belt clip
- Length: 5.9" (15 cm)

Part # 703007



Cut/Strip Tool **NEW**

- Precision ground cutter and stripping stations
- Strips wire from 24 AWG to 10 AWG (0.5 to 2.6 mm²)
- Length: 6.6" (16.7 cm)

Part # 702008



Stainless Steel Cut/Strip/Crimp Tool

- Crimp 10 to 22 AWG insulated and non-insulated terminals and coaxial connectors
- Cut and strip 22 AWG to 8 AWG solid and 24 AWG to 10 AWG stranded wire
- Cut and rethread 4-40, 5-40, 6-32, 8-32, 10-24, 10-32 screws
- Stainless steel blade resists corrosion and nicking
- Precision ground plier nose
- Length: 8.3" (21.0 cm)

Part # 701009



Cut/Strip/Crimp Tool **NEW**

- Precision ground cutters and stripping station
- Capacity: Crimps 22 AWG to 10 AWG / 0.3 to 5 mm² insulated and non-insulated terminals, connectors and spark plug terminals in special cavities
- Strips insulation from 22 AWG to 10 AWG / 0.3 to 5 mm² solid and stranded wires
- Cuts (4) 40/2 mm, (6) 32/4 mm, (8) 32/4.8 mm, (10) 32/6.4 mm and 10-24/6.4 mm bolts
- Length: 8.6" (20.3 cm)

Part # 702007

Premium Battery Cable Stripper

- Punctures the cable's insulation, breaks the insulation free and pulls the cut insulation from the wire in one efficient motion
- Strips 8 AWG through 400 MCM cable
- Heavy-duty construction
- Length: 5.3" (13.0 cm)

Part # 703075



Compact Automatic Wire Stripper **NEW**

- Compact design perfect for use in tight spaces
- Strips without damage or marking of conductors
- Strips and cuts wire from 20 AWG to 10 AWG (0.05-5.0mm²)
- Length: 6.3" (16 cm)

Part # 702031



Automatic Wire Stripper

- Automatically adjusts to different wire sizes
- Strips without damage or marking of conductors, slim jaw for easy access, steel side cutter
- Strips and cuts wire from 24 AWG to 12 AWG / 0.02-5.0mm²
- Wire stop adjusts length of strip from 3/8" to 1/2" (9.5 to 12.7 mm)
- Length: 6.7" (17.0 cm)

Part # 702030



Universal Wire Stripper **NEW**

- Two different cutting methods to cut either small gauge wire or large gauge battery cable
- Wire stripping from 20 AWG to 10 AWG (0.05-5.0mm²)
- Battery cable stripping from 8 AWG to 4/0 AWG (8 to 107mm²)
- Length: 5.7" (14.5 cm)


Part # 702032



Wire Strip Crimp Tool

- Strips 26 AWG to 10 AWG stranded wire
- Automatic jaw-load wire stripper self-adjusts to strip wire
- Crimps 22 AWG to 10 AWG insulated terminals
- Length: 8.1" (20.6 cm)


Part # 702033



8 to 4/0 AWG Heavy-duty Hex Lug & Terminal Crimper

- Uses revolving dies to create a hex style crimp for 8 AWG to 4/0 AWG
- Length: 24.4" (62 cm)

Part # 703040



8 to 1/0 AWG Hex Lug & Terminal Crimper

- Uses revolving dies to create a hex style crimp for 8 AWG to 1/0 AWG
- For portable use
- Length: 15.4" (39 cm)

Part # 703050



22 to 8 AWG Single Crimp Ratcheting Crimper

- Ideal for crimping heat shrink terminals
- Can also be used with vinyl and nylon insulated terminals and connectors
- Must be fully closed before tool allows itself to open ensuring a proper crimp
- Includes lever to release jaws mid-cycle in the event of an incorrectly placed terminal
- Ratcheting operation with ergonomic handle to prevent hand fatigue
- 4 color-coded cavities for different wire sizes
- Length: 10.9" (27.6 cm)

Part # 703010



26 to 10 AWG Double Crimp Ratcheting Crimper

- Ideal for crimping nylon and vinyl terminals
- Double crimp mechanism crimps stranding and insulation portion of Ancor connectors in one motion for superior strain relief of vinyl and nylon terminals
- Must be fully closed before tool allows itself to open ensuring a proper crimp
- Includes lever to release jaws mid-cycle in the event of an incorrectly placed terminal
- Ratcheting operation with ergonomic handle to prevent hand fatigue
- 4 color-coded cavities for different wire sizes
- Length: 10.9" (27.6 cm)

Part # 703030



Angled 22 to 8 AWG Single Crimp Ratcheting Crimper **NEW**

- For crimping heat shrink terminals
- Angled head design is ideal for use in tight spaces
- Self-releasing mechanism ensures a proper crimp
- Ratcheting operation and ergonomic handles prevent fatigue
- Length: 9.5" (24 cm)

Part # 703015



Angled 26 to 10 AWG Double Crimp Ratcheting Crimper **NEW**

- For crimping nylon and vinyl terminals
- Angled head design is ideal for use in tight spaces
- Self-releasing mechanism ensures a proper crimp
- Ratcheting operation and ergonomic handles prevent fatigue
- Length: 9.5" (24 cm)

Part # 703035

Flag Terminal Die Sets

- Works with all Ancor ratcheting crimpers; 703010, 703015, 703030, 703035

Part # 703041 22-18 & 16-14 AWG

Part # 703042 12-10 AWG



703041



703042




Tool Selection per ABYC Guidelines

ABYC recommends that the tool used to crimp connectors be manufactured by the same brand as the connectors themselves. The reason behind this is that the barrel and insulation thickness varies by connector manufacturer. Therefore having a crimping tool designed for specific connectors ensures a secure and safe crimp.

Mini Fish Tape

- Durable, high-impact housing
- Low-memory 15 ft tape does not curl during extension—perfect for non-conduit situations
- Compact, rugged design can be stored in tool belt or box
- Feed under carpet, behind walls or through panels
- Perfect for short runs, installing speakers, instrument clusters or other common electrical uses

Part # 703112



6" Long Nose Pliers **NEW**

- Insulated to 1000V
- Ideal for use in tight spaces
- Chrome Vanadium
- Length: 6" (15.2 cm)


Part # 710010



7" Combination Pliers **NEW**

- Insulated to 1000V
- Combines both gripping jaws and wire cutter
- Chrome Vanadium
- Length: 7" (17.8 cm)

Part # 710020



6" Bent Nose Pliers **NEW**

- Insulated to 1000V
- Ideal for use in tight spaces
- Chrome Vanadium
- Length: 6" (15.2 cm)

Part # 710030



6" Diagonal Cutting Pliers **NEW**

- Insulated to 1000V
- Ergonomic cutter for wire or cable ties
- Chrome Vanadium
- Length: 6" (15.2 cm)

Part # 710040

7 Pc Insulated Screwdriver Set **NEW**

- Kit includes:
 - (1) 1/8" x 3" Slotted (1) #0 x 3" Phillips
 - (1) 7/32" x 5" Slotted (1) #1 x 3" Phillips
 - (1) 1/4" x 6" Slotted (1) #2 x 4" Phillips
 - (1) Test probe
- Insulated to 1000V
- Includes convenient storage/carrying case

Part # 711000



Premium Connector Kits

- Nylon insulated with insulation grip
- Double crimp, funnel entry
- All kits include assorted butt connectors, ring terminals, spade terminals, and disconnects (18-10 AWG)

Description	Part #
31 pcs with crimp tool	220002
121 pcs with crimp tool	220004
120 pcs	220003



225 Piece Twin Kit Electrical Repair Kit with Strip/Crimp Tool

- 55 pcs assorted butt connectors
- 95 pcs assorted ring terminals
- 35 pcs assorted disconnects
- 35 pcs assorted nylon cable ties
- Assorted, 10' spools of UL 1426 boat cable
- 5 pcs (3" x 3/8") 3:1 shrink ratio, colored heat shrink tubing
- Case opens both sides

Part # 220020



Mini Pocket Butane Torch

- Piezo electronic ignition system
- Flame temperature up to 2500°F / 1300°C
- Windproof and waterproof flame
- Pocket size allows the unit to fit easily into any tool kit
- Powered by disposable cigarette lighter or refillable butane fuel cell (included)

Part # 703024



Pro Torch

- Up to 90 minutes of time on each filling
- Flame temperature up to 2500°F / 1300°C
- Adjustable flame control
- Compact size with ergonomic grip
- Includes removable solder tip and removable base for added flexibility
- Refillable

Part # 703060



120V Two Setting Heat Gun

- Two settings—Low: 572°F / 300°C, 10 CFM / 17 CMH and High: 1,000°F / 538°C, 17 CFM / 29 CMH (cubic meters per hour)
- 6.5' cord, 120V AC
- Great for heat shrink tubing and connectors, stripping paint and more
- Lightweight, under two pounds
- Stands on end for hands free operation
- Includes three nozzles and carrying case

Part # 703023

Three nozzles for a variety of applications



Carrying case included



Stands on end for hands free operation



Micro Therm Heat Gun

- Features Piezo electronic ignition system, providing flame less heat, safe to use around chemicals or by wire bundles when using deflector
- Powered by refillable cell
- Flame temperature up to 1300°F / 650°C
- Ideal for work in the bilge where open flame should not be used
- Refillable

Part # 702027



Battery Terminal Cleaner

- High impact construction
- Wide, easy grip
- Excellent for hard-to-reach batteries

Part # 700103



Dielectric Silicone Compound

- Fights oxidation to improve conductivity
- Penetrates aluminum oxide to maintain current paths
- Temperature rated at 40° to 500°F / 4°C to 260°C
- 1/3 oz tube

Part # 700115



8 Function Digital Multimeter **NEW**

- Auto ranging capability allows the meter to automatically determine the resolution based on the application
- Clear LCD display
- Lightweight, ergonomic design
- Comfortable protective cover, with test lead hanging groove
- Loud buzzer sound
- Batteries: two AAA Batteries (not included)
- Continuity ✓, Diode Test ✓

Specifications	Range	Accuracy
DC Voltage (V)	200.0mV, 2000mV/2.000V, 20.00V, 200.0V, 250V	200.0mV, 20.00V, 200.0V, 250V (0.7% + 3) 2000mV/2.000V (0.5% + 2)
AC Voltage (V)	200.0mV, 2000mV/2.000V, 20.00V, 200.0V, 250V	200.0mV, 20.00V (1.0% + 2) 2000mV/2.000V (0.7% + 3) 200.0V, 250V (1.2% + 3)
DC Current (A)	200.0µA, 2000µA, 20.00mA, 200.0mA, 2.000A, 10.00A	200.0µA, 2000µA, 20.00mA, 200.0mA (1.0% + 2) 2.000A, 10.00A (1.2% + 5)
AC Current (A)	200.0µA, 2000µA, 20.00mA, 200.0mA, 2.000A, 10.00A	200.0µA, 2000µA, 20.00mA, 200.0mA (1.2% + 3) 2.000A, 10.00A (1.5% + 5)
Resistance (Ω)	200.0, 2000/2.000k, 20.00k, 200.0k, 20.00M, 200.0M	200 (1.0% + 2) 2000/2.000k, 20.00k, 200.0k (0.8% + 2) 20.00M (1.2% + 3) 200.0M (5.0% + 10)
Capacitance (F)	2.000nF, 20.00nF, 200.0nF, 2.000µF, 20.00µF, 200.0µF, 2.000mF	2.000nF (REL Mode: 5.0% + 5) 20.00nF, 200.0nF, 2.000µF, 20.00µF, 200.0µF (4.0% + 8), 2.000mF (10%)
Overload Protection	250V rms	
CAT Rating	CAT II 250V	

703072



5 YEAR WARRANTY   

True RMS 12 Function Digital Multimeter **NEW**

- Auto ranging capability allows the meter to automatically determine the resolution based on the application
- Clear LCD display
- Comfortable protective cover, with test lead hanging groove
- High voltage warning
- Auto power off functionality to save battery life
- Batteries: two AAA Batteries (not included)
- Continuity ✓, Diode Test ✓, NCV ✓

Specifications	Range	Accuracy
DC Voltage (V)	600.0mV, 6000mV/6.000V, 60.00V, 600.0V	600.0mV, 60.00V, 600.0V (0.7% + 3) 6000mV/6.000V (0.5% + 2)
AC Voltage (V)	600.0mV, 6000mV/6.000V, 60.00V, 600.0V	600.0mV, 60.00V (1.0% + 2) 6000mV/6.000V (0.7% + 3) 600.0V (1.2% + 3)
DC Current (A)	600.0µA, 6000µA, 60.00mA, 600.0mA, 6.000A, 10.00A	600.0µA, 6000µA, 60.00mA, 600.0mA (1.0% + 3) 6.000A, 10.00A (1.2% + 5)
AC Current (A)	600.0µA, 6000µA, 60.00mA, 600.0mA, 6.000A, 10.00A	600.0µA, 6000µA, 60.00mA, 600.0mA (1.2% + 3) 6.000A, 10.00A (1.5% + 5)
Resistance (Ω)	600.0, 6000/6.000k, 60.00k, 600.0k, 60.00M	600 (1.0% + 2) 6000/6.000k, 60.00k, 600.0k (0.8% + 2) 60.00M (2.0% + 5)
Capacitance (F)	9.999nF, 99.99nF, 999.9nF, 9.999µF, 99.99µF, 999.9µF, 9.999mF	9.999nF (REL Mode: 4.0% + 10) 99.99nF, 999.9nF, 9.999µF, 99.99µF, 999.9µF (4.0% + 5), 9.999mF (10%)
Frequency (Hz)	10.00Hz–1.000MHz	10.00Hz–1.000MHz (0.1% + 5)
Temperature (°F)	-40°F to 1832°F	-40 to 104°F (5%) 104°F to 932°F (1.5% + 5) 932°F to 1832°F (2.5% + 5)
Temperature (°C)	-40°C to 1000°C	-40 to 40°C (4°C) 40°C to 500°C (1.0% + 4) 500°C to 1000°C (2.0% + 4)
Overload Protection	600V rms	
CAT Rating	CAT III 600V	

703073



5 YEAR WARRANTY   

True RMS 12 Function Digital Snap-Around Meter **NEW**

- Easy to read backlit OLED screen
- Non-contact AC voltage testing
- Provides accurate readings for both pure sine wave and modified sine wave electrical circuits
- Zeroing function
- Flashlight for use in dark compartments
- Includes convenient carrying case
- Batteries: three AAA Batteries (not included)
- Continuity ✓, Diode Test ✓, NCV ✓

Specifications	Range	Accuracy
DC Voltage (V)	600.0mV, 6000mV, 6.000V, 60.00V, 600.0V, 1000V	600.0mV (1.0% + 8) 6000mV/6.000V (0.8% + 1) 60V, 600V (0.8% + 3) 1000V (1.0% + 3)
AC Voltage (V)	6.000V, 60.00V, 600.0V, 750V	6.000V, 60.00V, 600.0V (1.2% + 5) 750V (1.5% + 5)
DC Current (A)	60.00A, 600.0A	60.00A, 600.0A (2.5% + 5)
AC Current (A)	60.00A, 600.0A	60.00A, 600.0A (2.5% + 5)
Resistance (Ω)	600.0, 6000/6.000k, 60.00k, 600.0k, 6.000M, 60.00M	600.0, 6.000M (1.2% + 2) 6000/6.000k, 60.00k, 600.0k (1.0% + 2) 60.00M (1.5% + 5)
Capacitance (F)	60.00nF, 600.0nF, 6.000μF, 60.00μF, 600.0μF, 6.000mF	60.00nF (4.0% + 25) 600.0nF, 6.000μF, 60.00μF, 600.0μF (4.0% + 5) 6.000mF (10%)
Frequency (Hz)	10.00Hz-1.000MHz	10.00Hz-1.000MHz (0.1% + 4)
Temperature (°F)	-40°F to 1832°F	-40°F to 104°F (3.0% + 10) 104°F to 752°F (3.0% + 10) 752°F to 1832°F (2.0% + 10)
Temperature (°C)	-40°C to 1000°C	-40°C to 40°C (3.0% + 5) 40°C to 400°C (3.0% + 5) 400°C to 1000°C (2.0% + 5)
Overload Protection	1000V DC, 750V AC	
CAT Rating	CAT II 1000V, CAT III 600V	

703079



5 YEAR WARRANTY




TECH tip

Measuring AC Current


Typically, a standard multimeter is accurate and reliable when measuring DC current. However, the same cannot be said for AC current. This is because AC current travels in the shape of a true or modified sine wave. When current is non-linear, you'll need a meter that can measure the current with the highest level of accuracy. This is achievable through Root Mean Square (RMS). True RMS is an advanced calculation used by digital multimeters which provides accurate values of AC levels. It doesn't matter if the current is distorted. A true RMS multimeter adjusts itself accordingly to deliver accurate results.

LIGHTING


Bayonet Base




Index Base



Mini Halogen



Festoon




Marine grade bulbs and lamps are available for a variety of applications. Each light bulb is constructed with a heavy-duty glass envelope to resist breakage, a nickel-plated brass base to prevent corrosion and has been tested to ensure durability and dependability.



LIGHTING

Screw Base

64



Fluorescent Tubes

64




Proper lighting is necessary for safety and operational activities aboard vessels and creates a soothing and functional atmosphere.










Incandescent Bulbs

Drawings are Actual Size

Single Contact Bayonet



Double Contact Bayonet



Double Contact Bayonet

Index Base Bulbs

Wedge Base Bulbs

Figure Letter	Trade #	Contact	System Volts	Design Volts	Design Amps	Design Watts	CP	Life	Qty/Pkg	Dimensions	Part #
Bayonet											
A	97	Single	12	13.50	.69	9.30	4.00	5,000	2	.75" x 1.44"	520097
B	90	Double	12	13.00	.58	7.50	6.00	750	2	.75" x 1.37"	520090
C	1004	Double	12	12.80	.94	12.00	15.00	200	2	.78" x 1.75"	521004
D	1142	Double	12	12.80	1.44	18.40	21.00	1,000	2	1" x 2"	521142
E		Double	12	2.50	30.00	26.00	1200	2,500	1	1" x 2.65"	529300
F		Double	120	120.00	.25	30.00	20.00	2,500	1	1" x 2.85"	521164
Index Base Bulbs											
G	1157	Double	12	12.8/14	2.1/.59	27/8	32/3	200/5,000	2	1" x 2"	521157
		Double	12	12.00	2.08	25.00	24.00	1,200	1	1" x 2.65"	529340
H		Double	12	13.50	.83	10.00	12.00	1,000	1	1" x 2.65"	521158
		Double	24	24.00	1.04	25.00	24.00	1,200	1	1" x 2.65"	529341
Wedge Base Bulbs											
J	194	Wedge	12	14.00	.27	3.80	2.00	1,500	2	.4" x 1.06"	520194
K	906	Wedge	12	13.00	.69	9.00	6.00	1,000	2	.62" x 1.38"	520906

Miniature Halogen Bulbs

Drawings are Actual Size




Figure Letter	System Volts	Design Volts	Design Amps	Design Watts	CP	Life	Qty/ Pkg	Dimensions	Part #
L	12	12.00	.42	5	5.00	2,000	2	.35" x 1.18"	529361
	12	12.00	.83	10	11.00	2,000	1	.35" x 1.18"	529362
	12	12.00	1.67	20	20.00	2,000	1	.35" x 1.18"	529367
	24	24.00	.42	10	11.00	2,000	1	.35" x 1.18"	529338
	24	24.00	.83	20	20.00	2,000	1	.35" x 1.18"	529368
M	12	12.00	.83	10	11.00	2,000	2	.46" x 1.93"	529385
	12	12.00	1.67	20	20.00	2,000	1	.35" x 1.18"	529337
N	12	12.00	.42	5	5.00	2,000	1	.35" x 1.18"	529355
	12	12.00	.83	10	11.00	1,000	2	.35" x 1.18"	529370
O	12	13.50	8.30	100	100.00	100	1	.85" x 1.55"	529386

Festoon Bulbs

Drawings are Actual Size





Figure Letter	Trade #	System Volts	Design Volts	Design Amps	Design Watts	CP	Life	Qty/ Pkg	Dimensions	Part #
P	—	12	13.50	.83	10.00	8.00	1,000	2	.46" x 1.22"	529102
	—	24	24.00	.41	10.00	8.00	1,000	2	.46" x 1.22"	522129
Q	—	12	13.50	.50	6.00	2.00	1,000	2	.46" x 1.46"	529095
R	211-2	12	12.80	.97	15.00	12.00	1,000	2	.46" x 1.60"	522112
	212-2	12	13.50	.74	10.00	6.00	2,000	2	.46" x 1.60"	522122
S	—	12	13.50	.83	10.00	8.00	2,000	2	.46" x 1.73"	529333

Medium Screw Base Bulbs

Drawings are Actual Size


Figure Letter	Trade #	System Volts	Design Volts	Design Amps	Design Watts	Life	Qty/Pkg	Dimensions	Part #
T	25A17/12	12	13.50	2.08	25	1000	2	2.34" x 4.2"	531025
	50A17/12	12	13.50	4.17	50	1000	2	2.34" x 4.2"	531050
	75A17/12	12	13.50	6.25	75	1000	2	2.34" x 4.2"	531075
	25A17/24	24	27.00	1.04	25	1000	2	2.34" x 4.2"	532025
	25A17/24	24	27.00	1.04	50	1000	2	2.34" x 4.2"	532050
	50A17/34	32	36.00	1.47	50	1000	2	2.34" x 4.2"	533050



Fluorescent Tubes


Drawings are Actual Size

Figure Letter	Trade #	Volts	Watts	M.O.L.	M.O.D.	Life	Qty/Pkg	Dimensions	Part #
U	F8T5/CW	13.5	8	11.3"	.5"	7500	2	.5" x 11.63"	529405





Actual Size



DISPLAYS

Heat Shrink Terminal, Connector & Tubing Displays

68



Ancor's most popular consumer packages of adhesive lined heat shrink tubing, heat shrink terminals, and butt connectors.

Nylon Connectors & Terminals Displays

69



A selection of our most popular nylon butt connectors, disconnects and ring terminals to fit wire sizes from 22 to 10 AWG.

Tinned Copper Lug Displays

70



24 sizes of heavy-duty tinned copper lugs, 8 AWG to 4/0. Includes combo packs, battery terminals, and heavy-duty lug crimper.

Mini Lamps Displays

71



Blister packs of Ancor's most popular nickel-plated, corrosion resistant mini lamps and standard base lamps to cover common applications.



DISPLAYS

Marine Grade® Tinned Wire Displays

72



This compact counter top display consists of 60 spools of the 12 most common wire sizes and colors. All wire is Premium UL 1426 Tinned Copper Primary Wire.

Complete Wire Merchandiser


73



This display offers the most popular colors and sizes of primary wire, battery cable, duplex, triplex, coaxial cable, instrument, ribbon, trailer and safety cable. Also included are our top-selling, professional grade tools.

Complete Electrical Merchandiser


74



Designed as an end cap or free standing gondola, this eye catching 4' wide x 6' high heavy-duty display provides the retail dealers with a complete selection of our most popular Marine Grade® products.

NMEA 2000 Display

76



Simple drop in NMEA 2000 store set. Kit includes everything needed to build a new NMEA network or expand on an existing network.

Anchor product displays can quickly and effectively increase sales by providing an assortment of products to customers in an easy to shop layout



Heat Shrink Terminal, Connector & Tubing Display

Part # DR1230

Part #	Description	Qty/ Pkg	# of Pkgs
301103	1/8" x 3" Black Heat Shrink	3	10
302103	3/16" x 3" Black Heat Shrink	3	10
303103	1/4" x 3" Black Heat Shrink	3	10
304103	3/8" x 3" Black Heat Shrink	3	5
305103	1/2" x 3" Black Heat Shrink	3	5
306103	3/4" x 3" Black Heat Shrink	3	5
301503	3/16"-3/4" x 3" Heat Shrink Assortment Pack	8	5
304503	3/8" x 3" Heat Shrink Assortment BL-GR-RD-WH-YW	5	5
306503	3/4" x 3" Heat Shrink Assortment BL-GR-WH-YW	4	4
300000	Heat Shrink Butt Connector Kit	10	5
309003	22-18 Heat Shrink Butt	3	5
309103	16-14 Heat Shrink Butt	3	5
309203	12-10 Heat Shrink Butt	3	5
310203	22-18 #8 Heat Shrink Ring	3	5
310303	22-18 #10 Heat Shrink Ring	3	5
311203	16-14 #8 Heat Shrink Ring	3	5
311303	16-14 #10 Heat Shrink Ring	3	5
311503	16-14 5/16" Heat Shrink Ring	3	5
311603	16-14 3/8" Heat Shrink Ring	3	5
312203	12-10 #8 Heat Shrink Ring	3	5
312303	12-10 #10 Heat Shrink Ring	3	5
312503	12-10 5/16" Heat Shrink Ring	3	5
312603	12-10 3/8" Heat Shrink Ring	3	5
701009	Stainless Steel Cut/Strip/Crimp Tool	1	2



Heat Shrink Terminal, Connector & Tubing Display

Part # DR2230

Part #	Description	Qty/ Pkg	# of Pkgs
309003	22-18 AWG Heat Shrink Butt	3	3
309103	16-14 AWG Heat Shrink Butt	3	3
309125	16-14 AWG Heat Shrink Butt	25	3
309203	12-10 AWG Heat Shrink Butt	3	3
300000	22-10 AWG Heat Shrink Butt	10	3
310203	22-18 #8 Heat Shrink Ring	3	3
310303	22-18 #10 Heat Shrink Ring	3	3
320003	24-22/24-18 Step-Down, Heat Shrink Butt	3	3
320103	22-18/22-14 Step-Down, Heat Shrink Butt	3	3
320203	16-14/16-10 Step-Down, Heat Shrink Butt	3	3
320303	12-10/12-8 Step-Down, Heat Shrink Butt	3	3
311203	16-14 #8 Heat Shrink Ring	3	3
311303	16-14 #10 Heat Shrink Ring	3	3
311503	16-14 5/16" Heat Shrink Ring	3	3
311603	16-14 3/8" Heat Shrink Ring	3	3
SPK2218	22-18 AWG Heat Shrink, Speaker Connector Kit	6	3
SPK1614	16-14 AWG Heat Shrink, Speaker Connector Kit	6	3
312203	12-10 #8 Heat Shrink Ring	3	3
312303	12-10 #10 Heat Shrink Ring	3	3
312503	12-10 5/16" Heat Shrink Ring	3	3
312603	12-10 3/8" Heat Shrink Ring	3	3
304503	3/8" x 3" Heat Shrink Tubing Assortment	5	3
301103	1/8" x 3" Heat Shrink Tubing, Black	3	3
302103	3/16" x 3" Heat Shrink Tubing, Black	3	3
303103	1/4" x 3" Heat Shrink Tubing, Black	3	3
304103	3/8" x 3" Heat Shrink Tubing, Black	3	3
305103	1/2" x 3" Heat Shrink Tubing, Black	3	3
306103	3/4" x 3" Heat Shrink Tubing, Black	3	3
301503	3/16"-3/4" x 3" Heat Shrink Tubing Asst, Black	8	3

All displays come with matching header, hooks, planogram and re-order tags.



Nylon Connectors & Terminals Display

Part # DR1243

Part #	Description	Qty/ Pkg	# of Pkgs
230100	22-18 Nylon Butt	7	10
230110	16-14 Nylon Butt	7	10
230120	12-10 Nylon Butt	5	10
230202	22-18 #8 Nylon Ring	6	10
230203	22-18 #10 Nylon Ring	6	10
230212	16-14 #8 Nylon Ring	6	10
230213	16-14 #10 Nylon Ring	6	10
230215	16-14 5/16" Nylon Ring	5	10
230216	16-14 3/8" Nylon Ring	5	10
230222	12-10 #8 Nylon Ring	5	10
230223	12-10 #10 Nylon Ring	5	10
230224	12-10 1/4" Nylon Ring	4	10
230225	12-10 5/16" Nylon Ring	4	10
230226	12-10 3/8" Nylon Ring	4	10
230235	#8 5/16" Nylon Ring	2	10
230236	#8 3/8" Nylon Ring	2	10
230312	16-14 #8 Nylon Flanged Spade	6	10
230313	16-14 #10 Nylon Flanged Spade	6	10
230323	12-10 #10 Nylon Flanged Spade	5	10
230615	18-14 Splice Connect	4	5
230818	16-14 Female Nylon Disconnect	5	10
230828	12-10 Female Nylon Disconnect	4	10
231418	16-14 Female Nylon Fully Insulated Disconnect	4	10
231419	16-14 Male Nylon Fully Insulated Disconnect	4	10
231428	12-10 Female Nylon Fully Insulated Disconnect	3	10
231429	12-10 Male Nylon Fully Insulated Disconnect	3	10
701009	Stainless Steel Cut/Strip/Crimp Tool	1	2



Nylon Connectors & Terminals Display

Part # DR2243

Part #	Description	Qty/ Pkg	# of Pkgs
230100	22-18 Nylon Butt	7	5
230110	16-14 Nylon Butt	7	5
230120	12-10 Nylon Butt	5	5
230202	22-18 #8 Nylon Ring	6	5
230203	22-18 #10 Nylon Ring	6	5
230212	16-14 #8 Nylon Ring	6	5
230213	16-14 #10 Nylon Ring	6	5
230215	16-14 5/16" Nylon Ring	5	5
230216	16-14 3/8" Nylon Ring	5	5
230222	12-10 #8 Nylon Ring	5	5
230223	12-10 #10 Nylon Ring	5	5
230224	12-10 1/4" Nylon Ring	4	5
230225	12-10 5/16" Nylon Ring	4	5
230226	12-10 3/8" Nylon Ring	4	5
230235	#8 5/16" Nylon Ring	2	5
230236	#8 3/8" Nylon Ring	2	5
230302	22-18 #8 Nylon Flanged Spade	6	5
230312	16-14 #8 Nylon Flanged Spade	6	5
230313	16-14 #10 Nylon Flanged Spade	6	5
230322	12-10 #8 Nylon Flanged Spade	5	5
230323	12-10 #10 Nylon Flanged Spade	5	5
230615	18-14 Splice Connector	4	5
230510	16-14 Nylon 3-Way Connector	1	5
230520	12-10 Nylon 3-Way Connector	1	5
230818	16-14 Nylon Disconnect, Female	5	5
231418	16-14 Nylon Fully Insulated Disconnect, Female	4	5
231419	16-14 Nylon Fully Insulated Disconnect, Male	4	5
230828	12-10 Nylon Disconnect, Female	4	5
231428	12-10 Nylon Fully Insulated Disconnect, Female	3	5
231429	12-10 Nylon Fully Insulated Disconnect, Male	3	5
230719	16-14 Nylon Snap Plug, Female	4	5
230718	16-14 Nylon Snap Plug, Male	4	5

All displays come with matching header, hooks, planogram and re-order tags.



Tinned Copper Lug Display

Part # DR1425

Part #	Description	Qty/ Pkg	# of Pkgs
252233	#8 #10 Tinned Lug	2	10
252234	#8 1/4" Tinned Lug	2	10
252235	#8 5/16" Tinned Lug	2	10
252236	#8 3/8" Tinned Lug	2	10
252243	#6 #10 Tinned Lug	2	10
252244	#6 1/4" Tinned Lug	2	10
252245	#6 5/16" Tinned Lug	2	10
252246	#6 3/8" Tinned Lug	2	10
252254	#4 1/4" Tinned Lug	2	10
252255	#4 5/16" Tinned Lug	2	10
252256	#4 3/8" Tinned Lug	2	10
252265	#2 5/16" Tinned Lug	2	10
252266	#2 3/8" Tinned Lug	2	10
252275	#1 5/16" Tinned Lug	2	10
252276	#1 3/8" Tinned Lug	2	10
252285	#1/0 5/16" Tinned Lug	2	5
252286	#1/0 3/8" Tinned Lug	2	5
252295	#2/0 5/16" Tinned Lug	2	5
252296	#2/0 3/8" Tinned Lug	2	5
252726	#4/0 3/8" Tinned Lug	2	10
252241	#6 5/16" & 3/8" Combo Pack	1/1	10
252251	#4 5/16" & 3/8" Combo Pack	1/1	10
252261	#2 5/16" & 3/8" Combo Pack	1/1	10
260325	Battery Terminal, Wing Nut, 5/16" & 3/8" Combo	1/1	2



Tinned Copper Lug Display

Part # DR2425

Part #	Description	Qty/ Pkg	# of Pkgs
252233	#8 #10 Tinned Lug	2	2
252234	#8 1/4" Tinned Lug	2	2
252235	#8 5/16" Tinned Lug	2	2
252236	#8 3/8" Tinned Lug	2	2
252243	#6 #10 Tinned Lug	2	2
252244	#6 1/4" Tinned Lug	2	2
252245	#6 5/16" Tinned Lug	2	2
252246	#6 3/8" Tinned Lug	2	2
252254	#4 1/4" Tinned Lug	2	2
252255	#4 5/16" Tinned Lug	2	2
252256	#4 3/8" Tinned Lug	2	2
252265	#2 5/16" Tinned Lug	2	2
252266	#2 3/8" Tinned Lug	2	2
252275	#1 5/16" Tinned Lug	2	2
252276	#1 3/8" Tinned Lug	2	2
252285	#1/0 5/16" Tinned Lug	2	2
252286	#1/0 3/8" Tinned Lug	2	2
252295	#2/0 5/16" Tinned Lug	2	2
252296	#2/0 3/8" Tinned Lug	2	2
252726	#4/0 3/8" Tinned Lug	1/1	2
252241	#6 5/16" & 3/8" Combo Pack	1/1	2
252251	#4 5/16" & 3/8" Combo Pack	1/1	2
252261	#2 5/16" & 3/8" Combo Pack	1/1	2
260325	Battery Terminal, Wing Nut, 5/16" & 3/8" Combo	1/1	2



Mini Lamps Display

Part # DR1550

Part #	Description	Qty/ Pkg	# of Pkgs
511016	Mini Envelope, 12V, 1.25A, 15W	1	2
520053	Mini Bayonet, 12V, .12A, 1.7W, 1CP	2	10
520057	Mini Bayonet, 12V, .24A, 3.4W, 2CP	2	5
520068	Double Contact Bayonet, 12V, .59A, 8W, 4CP	2	5
520090	Double Contact Bayonet, 12V, .58A, 7.5W, 6CP	2	10
520093	Single Contact Bayonet, 12V, 1.04A, 13.3W, 15CP	2	5
520094	Double Contact Bayonet, 12V, 1.04A, 13.3W, 15CP	2	5
520097	Single Contact Bayonet, 12V, .69A, 9.3W, 4CP	2	5
520194	Wedge, 12V, .27A, 3.8W, 2CP	2	10
521003	Single Contact Bayonet, 12V, .94A, 12W, 15CP	2	5
521004	Double Contact Bayonet, 12V, .94A, 12W, 15CP	2	5
521034	Double Contact Index, 12V, 1.8/.59A, 32/3CP	2	5
521076	Double Contact Bayonet, 12V, 1.8A, 23.0W, 32CP	2	5
521140	Double Contact Bayonet, Red, 12V, 1.44A, 18.4W, 21CP	2	5
521141	Single Contact Bayonet, 12V, 1.44A, 18.4W, 21CP	2	5
521142	Double Contact Bayonet, 12V, 1.44A, 18.4W, 21CP	2	5
521157	Double Contact Index, 12V, 2.1/.59A, 32/3CP	2	5
521176	Double Contact Bayonet, 12V, 1.34/.59A 21/6CP	2	5
521416	Mini Bayonet, 12V, .8A, 10.2W, 8.CP	2	5
521816	Mini Bayonet, 12V, .33A, 4.3W, 3CP	2	10
521895	Mini Bayonet, 12V, .27A, 3.8W, 2CP	2	5
522112	Festoon, 12V, .97A, 15W, 12CP	2	10
522122	Festoon, 12V, .74A, 10W, 6CP	2	10
529102	Festoon, 12V, .8A, 10W, 8CP	2	10



Mini Lamps Display

Part # DR2550

Part #	Description	Qty/ Pkg	# of Pkgs
511016	Mini Envelope, 12V, 1.25A, 15W	1	2
520053	Mini Bayonet, 12V, .12A, 1.7W, 1CP	2	3
520057	Mini Bayonet, 12V, .24A, 3.4W, 2CP	2	3
520068	Double Contact Bayonet, 12V, .59A, 8W, 4CP	2	3
520090	Double Contact Bayonet, 12V, .58A, 7.5W, 6CP	2	3
520093	Single Contact Bayonet, 12V, 1.04A, 13.3W, 15CP	2	3
520094	Double Contact Bayonet, 12V, 1.04A, 13.3W, 15CP	2	3
520097	Single Contact Bayonet, 12V, .69A, 9.3W, 4CP	2	3
520194	Wedge, 12V, .27A, 3.8W, 2CP	2	3
521003	Single Contact Bayonet, 12V, .94A, 12W, 15CP	2	3
521004	Double Contact Bayonet, 12V, .94A, 12W, 15CP	2	3
521034	Double Contact Index, 12V, 1.8/.59A, 32/3CP	2	3
521076	Double Contact Bayonet, 12V, 1.8A, 23.0W, 32CP	2	3
521140	Double Contact Bayonet, Red, 12V, 1.44A, 18.4W, 21CP	2	3
521141	Single Contact Bayonet, 12V, 1.44A, 18.4W, 21CP	2	3
521142	Double Contact Bayonet, 12V, 1.44A, 18.4W, 21CP	2	3
521157	Double Contact Index, 12V, 2.1/.59A, 32/3CP	2	3
521176	Double Contact Bayonet, 12V, 1.34/.59A 21/6CP	2	3
521416	Mini Bayonet, 12V, .8A, 10.2W, 8.CP	2	3
521816	Mini Bayonet, 12V, .33A, 4.3W, 3CP	2	3
521895	Mini Bayonet, 12V, .27A, 3.8W, 2CP	2	3
522112	Festoon, 12V, .97A, 15W, 12CP	2	3
522122	Festoon, 12V, .74A, 10W, 6CP	2	3
529102	Festoon, 12V, .8A, 10W, 8CP	2	3

All displays come with matching header, hooks, planogram and re-order tags.



Marine Grade® Tinned Wire Display

Part # DR1218

Part #	Description	# of Pkgs
180003	35' 18 AWG (0.8mm ²), Black	4
180803	35' 18 AWG (0.8mm ²), Red	4
182003	25' 16 AWG (1mm ²), Black	8
182803	25' 16 AWG (1mm ²), Red	8
182303	25' 16 AWG (1mm ²), Green	4
182903	25' 16 AWG (1mm ²), White	4
184003	18' 14 AWG (2mm ²), Black	4
184803	18' 14 AWG (2mm ²), Red	8
184303	18' 14 AWG (2mm ²), Green	4
184903	18' 14 AWG (2mm ²), White	4
186003	12' 12 AWG (3mm ²), Black	4
186803	12' 12 AWG (3mm ²), Red	4



Marine Grade® Tinned Wire Display

Part # DR2218

Part #	Description	# of Pkgs
180003	35' 18 AWG (0.8mm ²), Black	2
180803	35' 18 AWG (0.8mm ²), Red	2
182003	25' 16 AWG (1mm ²), Black	2
182803	25' 16 AWG (1mm ²), Red	2
182303	25' 16 AWG (1mm ²), Green	2
182903	25' 16 AWG (1mm ²), White	2
184003	18' 14 AWG (2mm ²), Black	2
184803	18' 14 AWG (2mm ²), Red	2
184303	18' 14 AWG (2mm ²), Green	2
184903	18' 14 AWG (2mm ²), White	2
186003	12' 12 AWG (3mm ²), Black	2
186803	12' 12 AWG (3mm ²), Red	2

All displays come with matching header, hooks, planogram and re-order tags.

Countertop Display Replacement Headers



Part # ANCSHRINK



Part # ANCTERM



Part # ANCLUG



Part # ANCLAMP



Part # ANCWIRE




Part # ANCNMEA

Complete Wire Merchandiser

Part # DR1086

The DR1086 is Ancor's premier Marine Grade® Wire Merchandiser offering the most popular colors and sizes of primary wire, battery cable, duplex, triplex, coaxial, instrument, ribbon, and trailer cables. Also included are our top-selling, professional grade tools. The display comes complete with a planogram, hooks, and five heavy-duty wire baskets designed to dispense the spools of wire.



Part #	Description	# of Pkgs
Mini Spools		
180003	18 AWG, Black, 35ft	2
180803	18 AWG, Red, 35ft	2
180903	18 AWG, White, 35ft	2
182003	16 AWG, Black, 25ft	2
182103	16 AWG, Dark Blue, 25ft	2
182303	16 AWG, Green, 25ft	2
182803	16 AWG, Red, 25ft	2
182903	16 AWG, White, 25ft	2
183003	16 AWG, Yellow, 25ft	2
184003	14 AWG, Black, 18ft	2
184803	14 AWG, Red, 18ft	2
186003	12 AWG, Black, 12ft	2
186803	12 AWG, Red, 12ft	2
188003	10 AWG, Black, 8ft	2
188803	10 AWG, Red, 8ft	2
Wire & Cable		
102010	16 AWG, Black, 100ft	1
102110	16 AWG, Dark Blue, 100ft	1
102210	16 AWG, Brown, 100ft	1
102310	16 AWG, Green, 100ft	1
102710	16 AWG, Purple, 100ft	1
102810	16 AWG, Red, 100ft	1
102910	16 AWG, White, 100ft	1
103010	16 AWG, Yellow, 100ft	1
104010	14 AWG, Black, 100ft	1
104110	14 AWG, Dark Blue, 100ft	1
104210	14 AWG, Brown, 100ft	1
104310	14 AWG, Green, 100ft	1
104410	14 AWG, Grey, 100ft	1
104710	14 AWG, Purple, 100ft	1
104810	14 AWG, Red, 100ft	1
104910	14 AWG, White, 100ft	1
105010	14 AWG, Yellow, 100ft	1
106010	12 AWG, Black, 100ft	1
106110	12 AWG, Dark Blue, 100ft	1
106210	12 AWG, Brown, 100ft	1
106310	12 AWG, Green, 100ft	1
106810	12 AWG, Red, 100ft	1
106910	12 AWG, White, 100ft	1
107010	12 AWG, Yellow, 100ft	1
108010	10 AWG, Black, 100ft	1
108810	10 AWG, Red, 100ft	1
111010	8 AWG, Black, 100ft	1

Part #	Description	# of Pkgs
111310	8 AWG, Green, 100ft	1
111510	8 AWG, Red, 100ft	1
112005	6 AWG, Black, 50ft	1
112505	6 AWG, Red, 50ft	1
113005	4 AWG, Black, 50ft	1
113505	4 AWG, Red, 50ft	1
113905	4 AWG, Yellow, 50ft	1
114002	2 AWG, Black, 25ft	1
114502	2 AWG, Red, 25ft	1
114902	2 AWG, Yellow, 25ft	1
116005	1/0 AWG, Black, 50ft	1
116505	1/0 AWG, Red, 50ft	1
117005	2/0 AWG, Black, 50ft	1
117505	2/0 AWG, Red, 50ft	1
121310	12/2 AWG, Flat, 100ft	1
124525	Safety, 14/2 AWG, Flat, 250ft	1
124725	Safety, 16/2 AWG, Flat, 250ft	1
124910	Safety, 18/2 AWG, Flat, 100ft	1
131110	10/3 AWG, Flat, 100ft	1
131310	12/3 AWG, Flat, 100ft	1

Part #	Description	# of Pkgs
131510	14/3 AWG, Flat, 100ft	1
151510	RG 8X, White, 100ft	1
153010	20/3 AWG, Round, 100ft	1
153110	Bonded, 16/2 AWG, Flat, 100ft	1
154525	Bonded, 16/4 AWG, Flat, 250ft	1
Tools & Wire Management		
339066	Electrical Tape, 1/2" x 20' Assorted	2
701009	Stainless Steel Cut/Strip/Crimp Tool	2
702030	Tool #24-#12 Automatic Wire Stripper	2
703005	Wire & Cable Cutter	2
703010	Single Crimp Ratchet Tool	1
703030	Double Crimp Ratchet Tool	1
703075	Premium Battery Cable Stripper	2



Complete Electrical Merchandiser

Part # DR1088

The DR1088 is Ancor's premier merchandiser. Designed as an end cap or free standing gondola, this eye catching 4' wide x 6' high heavy-duty display provides the retail dealers with a complete selection of our most popular Marine Grade® products. The top section includes consumer packs of our most popular terminals, lugs, lamps, mini-spools, cable ties and heat shrink tubing products. The bottom section offers the most popular colors and sizes of primary wire, battery cable, duplex, and triplex to be sold by the foot. The DR1088 electrical merchandiser comes complete with a planogram, hooks, and three heavy-duty wire baskets designed to dispense the spools of wire.

Part #	Description	# of Pkgs
Mini Spools		
180003	18 AWG, Black, 35ft	2
180803	18 AWG, Red, 35ft	2
180903	18 AWG, White, 35ft	2
182003	16 AWG, Black, 25ft	2
182103	16 AWG, Dark Blue, 25ft	2
182303	16 AWG, Green, 25ft	2
182803	16 AWG, Red, 25ft	2
182903	16 AWG, White, 25ft	2
183003	16 AWG, Yellow, 25ft	2
184003	14 AWG, Black, 18ft	2
184803	14 AWG, Red, 18ft	2
186003	12 AWG, Black, 12ft	2
186803	12 AWG, Red, 12ft	2
188003	10 AWG, Black, 8ft	2
188803	10 AWG, Red, 8ft	1
Wire & Cable		
100010	18 AWG, Black, 100ft	1
100810	18 AWG, Red, 100ft	1
102010	16 AWG, Black, 100ft	1
102310	16 AWG, Green, 100ft	1
102810	16 AWG, Red, 100ft	1
102910	16 AWG, White, 100ft	1
104010	14 AWG, Black, 100ft	1
104310	14 AWG, Green, 100ft	1
104810	14 AWG, Red, 100ft	1
106010	12 AWG, Black, 100ft	1
106810	12 AWG, Red, 100ft	1
106910	12 AWG, White, 100ft	1
108010	10 AWG, Black, 100ft	1
108310	10 AWG, Green, 100ft	1
108810	10 AWG, Red, 100ft	1
111010	8 AWG, Black, 100ft	1
111510	8 AWG, Red, 100ft	1
113005	4 AWG, Black, 50ft	1
113505	4 AWG, Red, 50ft	1
114002	2 AWG, Black, 25ft	1
114502	2 AWG, Red, 25ft	1
121110	10/2 AWG, Flat, 100ft	1
121325	12/2 AWG, Flat, 250ft	1
121525	14/2 AWG, Flat, 250ft	1
121725	16/2 AWG, Flat, 250ft	1
121925	18/2 AWG, Flat, 250ft	1
131110	10/3 AWG, Flat, 100ft	1
131310	12/3 AWG, Flat, 100ft	1
131510	14/3 AWG, Flat, 100ft	1
Nylon Connectors & Terminals		
230100	Butt Connector, 22-18, 7pc	10
230110	Butt Connector, 16-14, 7pc	10
230120	Butt Connector, 12-10, 5pc	10
230203	Ring Terminal, 22-18 #10, 6pc	10
230213	Ring Terminal, 16-14 #10, 6pc	10
230216	Ring Terminal, 16-14 3/8", 5pc	10
230223	Ring Terminal, 12-10 #10, 5pc	10
230225	Ring Terminal, 12-10 5/16", 4pc	10
230226	Ring Terminal, 12-10 3/8", 4pc	10

Part #	Description	# of Pkgs
230312	Flanged Spade, 16-14 #8, 6pc	10
230313	Flanged Spade, 16-14 #10, 6pc	10
230323	Flanged Spade, 12-10 #10, 5pc	10
230615	Splice Connector, 18-14, 4pc	5
231418	Fully Insul Disc, Female, 16-14, 4pc	10
231419	Fully Insul Disc, Male, 16-14, 4pc	10
231428	Fully Insul Disc, Female, 12-10, 3pc	10

Heavy-duty Tinned Lugs

252235	#8 5/16", 2pc	10
252236	#8 3/8", 2pc	10
252244	#6 1/4"pc	10
252245	#6 5/16", 2pc	10
252246	#6 3/8", 2pc	10
252255	#4 5/16", 2pc	10
252256	#4 3/8", 2pc	10
252265	#2 5/16", 2pc	10
252266	#2 3/8", 2pc	10
252285	#1/0 5/16", 2pc	5
252286	#1/0 3/8", 2pc	5
252295	#2/0 5/16", 2pc	5
252296	#2/0 3/8", 2pc	5

260325	Lead Battery Terminal, 5/16" & 3/8" Combo Pack	2
--------	--	---

Adhesive Lined Heat Shrink Tubing

302103	3/16" x 3", Black, 3pc	10
303103	1/4" x 3", Black, 3pc	10
304103	3/8" x 3", Black, 3pc	5
305103	1/2" x 3", Black, 3pc	5
306103	3/4" x 3", Black, 3pc	5
326202	Battery Cable Tubing, 3/4" x 3", Black & Red	5

Adhesive Lined Heat Shrink Connectors & Terminals

309003	Butt Connector, 22-18, 3pc	10
309103	Butt Connector, 16-14, 3pc	10
309203	Butt Connector, 12-10, 3pc	10
309303	Butt Connector, #8, 3pc	10
310203	Ring Terminal, 22-18 #8, 3pc	10
310303	Ring Terminal, 22-18 #10, 3pc	10
311203	Ring Terminal, 16-14 #8, 3pc	10
311303	Ring Terminal, 16-14 #10, 3pc	10
311403	Ring Terminal, 16-14 1/4", 3pc	10
311503	Ring Terminal, 16-14 5/16", 3pc	10
311603	Ring Terminal, 16-14 3/8", 3pc	10
312203	Ring Terminal, 12-10 #8, 3pc	10
312303	Ring Terminal, 12-10 #10, 3pc	10
312403	Ring Terminal, 12-10 1/4", 3pc	10
312503	Ring Terminal, 12-10 5/16", 3pc	10
312603	Ring Terminal, 12-10 3/8", 3pc	10
316803	Disconnect, Female 22-18, 3pc	10
316903	Disconnect, Male 22-18, 3pc	10
317803	Disconnect, Female 16-14, 3pc	10
317903	Disconnect, Male 16-14, 3pc	10
320103	Butt Connector, Step-Down, 22-18/22-14, 3pc	10
320203	Butt Connector, Step-Down, 16-14/16-10, 3pc	10
321503	Ring Terminal, #8 5/16", 3pc	10
321603	Ring Terminal, #8 3/8", 3pc	10

Part #	Description	# of Pkgs
--------	-------------	-----------

Wire Management

199204	Cable Tie, Std, 8", Natural, 25pc	10
199206	Cable Tie, Std, 8", UVB, 25pc	10
199228	Cable Tie, Mounting, 8", UVB, 25pc	10
199246	Cable Tie, Std, 6", Natural, 25pc	10
199248	Cable Tie, Std, 6", UVB, 25pc	10
339066	Electrical Tape, 1/2" x 20' Assorted	2
400000	Nylon Clamps, Natural, 1/8"-1/2" Assorted, 54pc	3
403502	Stainless Steel Cushion Clamp, 1/2", 10pc	2
750000	Vinyl, Grommets, 1/4"-3/4" Assortment, 45pc	3

Mini Lamps

520090	Dbl Contact Bayonet, 12V, .58A, 7.5W, 6CP, 2pc	5
520194	Wedge, 12V, .27A, 3.8W, 2CP, 2pc	5
520906	Wedge, 12V, .69A, 9.0W 6CP, 2pc	5
521004	Dbl Contact Bayonet, 12V, .94A, 12W, 15CP, 2pc	5
529102	Festoon, 12V, .8A, 10W, 8CP, 2pc	5
529338	Dbl Contact Bayonet, 24V, .42A, 10W	5
529362	Halogen G-4, 12V, .83A, 10W	5
529368	Halogen G-4, 24V, .83A, 20W	5

Tools

701009	Stainless Steel Cut/Strip/Crimp Tool	1
702030	Tool #24-#12 Automatic Wire Stripper	1
703005	Wire & Cable Cutter	1
703010	Single Crimp Ratchet Tool	1
703030	Double Crimp Ratchet Tool	1
703024	Mini Butane Torch	1

Replacement Display Accessories

Part #	Description	# of Pkgs
DR0007	4" Basket Brackets	2 per
DR0008	6.5" Basket Brackets	2 per
DR0009	10.5" Basket Brackets	2 per
DR0010	4" Wire Basket	1 per
DR0011	8" Wire Basket	1 per
DR0012	12" Wire Basket	1 per
DR0020	48" Heavy-duty Gondola	1 per
DR0061	6" Metal Pegboard Hooks	120 per

48" Display Replacement Header



Part # ANCHHEADER

NMEA 2000 Planogram Assortment **NEW**

Part # 270400

Simple drop in NMEA 2000 store set. Kit includes everything needed to build a new NMEA network or expand on an existing network.

Part #	Description	# of Pkgs
270000	NMEA 2000 Power Cable With Tee - 1m	1
270010	NMEA 2000 Backbone Cable - 10m	1
270101	NMEA 2000 Single Tee Connector	1
270105	NMEA 2000 Female Terminator	1
270106	NMEA 2000 Male Terminator	1
270109	NMEA 2000 Field Servicable Connector, Female	1
270110	NMEA 2000 Field Servicable Connector, Male	1
270201	NMEA 2000 Single Device Starter Kit	1
270301	NMEA 2000 Drop Cable - 1 Meter	1
270305	NMEA 2000 Drop Cable - 5 Meter	1



Wire & Cable Technical Data

Using the wrong type of wire can cost you more in the long run. Insist on Marine Grade® Boat Cable by Ancor. It is UL approved for the corrosive marine environment and charter boat service. Marine Grade Boat Cable is specially designed to exceed all test standards for cold bend, moisture and oil resistance, heat shock and flammability. This ensures the safest, easiest to install, longest lasting and ultimately the least expensive electrical system you can buy. Only Ancor offers a complete line of Marine Grade Boat Cable for every need.

“Can I use ‘regular wire’ for my boat?” The answer to this common question is a qualified "yes." However, caution is advised and the installer must understand the circumstances in which SAE (Society of Automotive Engineering) J378, J1127 or J1128 wire can, and can not be used. Keep in mind that these wires are designed for "surface vehicles," not for the special

requirements of the marine industry. Even if tinned copper, they should not be run in bilge spaces or other areas subject to moisture from spray or dripping. They should not be run in engines spaces, unless marked "oil resistant" and "75°C". They should not be used in applications where subjected to vibration or frequent flexing and must never be used for 110 volt applications. For safety, use only wire which is marked with size, type and temperature rating.

Most importantly, SAE wire is up to 12% smaller than AWG Boat Cable which means that, in many applications, larger gauge wire must be used to stay within the voltage drop limits recommended by experts. The wire charts found in "Chapman's Piloting" and other publications are all for "AWG" wire like Ancor, not "SAE" type wire.

ABYC Recommended Usages

Color	Item	Use
Red	DC Positive Conductor	Positive Mains
Black or Yellow	DC Negative Conductor	Return, Negative Mains
Green or Green w/ Yellow Stripe	DC Grounding Conductor	Bonding System Bonding Wires (if insulated)
Light Blue	Oil Pressure	Oil Pressure Sender to Gauge
Dark Blue	Cabin & Instrument Lights	Fuse or Switch to Lights
Brown	Generator Armature	Generator Armature to Regulator
	Alternator Charge Light	Generator Terminal/Alternator Auxiliary Terminal to Light to Regulator
	Pumps	Fuse or Switch to Pumps
Grey	Navigation Lights	Fuse or Switch to Lights
	Tachometer	Tachometer Sender to Gauge
Orange	Accessory Feed	Ammeter to Alternator or Generator Output and Accessory Fuses or Switches
	Common Feed	Distribution Panel to Accessory Switch
Pink	Fuel Gauge	Fuel Gauge Sender to Gauge
Purple	Ignition	Ignition Switch to Coil & Electrical Instruments
	Instrument Feed	Distribution Panel to Electric Instruments
Brown w/ Yellow Stripe	Bilge Blowers	Fuse or Switch to Blower
Yellow w/ Red Stripe	Starting Circuit	Starting Switch to Solenoid
Tan	Water Temperature	Water Temperature Sender to Gauge
Green/Stripe (G/x) (except G/Y)	Tilt Down and/or Trim In	Tilt and/or Trim Circuits
Blue/Stripe (Bl/x)	Tilt Up and/or Trim Out	Tilt and/or Trim Circuits

Conductors Sized (AWG) for 3% Voltage Drop

Use 3% voltage drop for any "critical application" affecting the safety of the vessel or its passengers: bilge pumps, navigation lights, electronics, etc....

Length (feet): Determined by measuring the length of the conductor from the positive (+) power source connection to the electrical device and back to the negative (-) power source connection. Note that the power source connection may be either the battery, panelboard or switchboard.

Current (amps): Determined by adding the total amps on a circuit.

Conductor sizes not covered in the following tables may be calculated by using the following formula:

$$CM = \frac{K \times I \times L}{E}$$

After calculating the Circular Mil Area (CM), use the temperature rating chart to determine the proper conductor size (National Fire Protection Agency and Coast Guard require that the next larger conductor be used when the calculated CM area falls between the two conductor sizes).

CM = Circular Mil Area of Conductors

K = 10.75 (Constant representing the mil-foot resistance of copper)

I = Current - amps

L = Length - feet

E = Voltage drop at load
(drop x working voltage)

3% Voltage Drop at 12 Volts

Length	Current (Amps)												
	5	10	15	20	25	30	40	50	60	70	80	90	100
10' 3 m	18	14	12	10	10	8	6	6	6	6	6	4	4
15' 5 m	16	12	10	10	8	8	6	6	4	4	4	2	2
20' 6 m	14	10	10	8	6	6	6	4	4	2	2	2	2
25' 8 m	12	10	8	6	6	6	4	4	2	2	2	1	1
30' 9 m	12	10	8	6	4	4	4	2	2	2	2	1	1
40' 12 m	10	8	6	6	4	4	2	2	1	1/0	1/0	2/0	2/0
50' 15 m	10	6	6	4	4	2	2	1	1/0	2/0	3/0	4/0	4/0
60' 18 m	10	6	6	4	2	2	1	1/0	2/0	3/0	3/0	4/0	4/0
70' 21 m	8	6	4	2	2	1	1/0	2/0	3/0	3/0	4/0	4/0	
80' 24 m	8	6	4	2	2	1	1/0	2/0	3/0	4/0	4/0		
90' 27 m	8	4	2	2	1	1/0	2/0	3/0	4/0	4/0			
100' 30 m	6	4	2	2	1	1/0	2/0	3/0	4/0				
110' 33 m	6	4	2	2	1	1/0	2/0	3/0	4/0				
120' 36 m	6	4	2	1	1/0	2/0	3/0	4/0					
130' 40 m	6	2	2	1	1/0	2/0	3/0	4/0					
140' 43 m	6	2	2	1/0	2/0	3/0	4/0						
150' 46 m	6	2	1	1/0	2/0	3/0	4/0						
160' 49 m	6	2	1	1/0	2/0	3/0	4/0						
170' 52 m	6	2	1	2/0	3/0	3/0	4/0						

3% Voltage Drop at 24 Volts

Length	Current (Amps)												
	5	10	15	20	25	30	40	50	60	70	80	90	100
10' 3 m	18	18	16	14	12	12	10	10	10	8	8	8	6
15' 5 m	18	16	14	12	12	10	10	8	8	6	6	6	6
20' 6 m	18	14	12	10	10	10	8	6	6	6	6	4	4
25' 8 m	16	12	12	10	10	8	6	6	6	4	4	4	4
30' 9 m	16	12	10	10	8	8	6	6	4	4	4	2	2
40' 12 m	14	10	10	8	6	6	6	4	4	2	2	2	2
50' 15 m	12	10	8	6	6	6	4	4	2	2	2	1	1
60' 18 m	12	10	8	6	6	4	4	2	2	1	1	1/0	1/0
70' 21 m	12	8	6	6	4	4	2	2	1	1	1/0	1/0	2/0
80' 24 m	10	8	6	6	4	4	2	2	1	1/0	1/0	2/0	2/0
90' 27 m	10	8	6	4	4	2	2	1	1/0	1/0	2/0	2/0	3/0
100' 30 m	10	6	6	4	4	2	2	1	1/0	2/0	2/0	3/0	3/0
110' 33 m	10	6	6	4	2	2	1	1/0	1/0	2/0	3/0	3/0	4/0
120' 36 m	10	6	4	4	2	2	1	1/0	2/0	3/0	3/0	4/0	4/0
130' 40 m	8	6	4	2	2	2	1	1/0	2/0	3/0	3/0	4/0	4/0
140' 43 m	8	6	4	2	2	1	1/0	2/0	3/0	3/0	4/0	4/0	
150' 46 m	8	6	4	2	2	1	1/0	2/0	3/0	3/0	4/0	4/0	
160' 49 m	8	6	4	2	2	1	1/0	2/0	3/0	4/0	4/0	4/0	
170' 52 m	8	6	2	2	1	1	2/0	3/0	3/0	4/0	4/0		

3% Voltage Drop at 32 Volts

Length	Current (Amps)												
	5	10	15	20	25	30	40	50	60	70	80	90	100
10' 3 m	18	18	16	16	14	14	12	12	10	10	10	8	8
15' 5 m	18	16	14	14	12	12	10	10	8	8	8	6	6
20' 6 m	18	16	12	12	12	10	10	8	8	6	6	6	6
25' 8 m	18	14	12	12	10	10	8	8	6	6	6	6	4
30' 9 m	16	14	10	10	10	8	8	6	6	6	4	4	4
40' 12 m	16	12	10	10	8	8	6	6	4	4	4	2	2
50' 15 m	14	12	8	8	8	6	6	4	4	2	2	2	2
60' 18 m	14	10	8	8	6	6	4	4	2	2	2	1	1
70' 21 m	12	10	6	6	6	6	4	2	2	2	1	1	0
80' 24 m	12	10	6	6	6	4	4	2	2	1	1	0	0
90' 27 m	12	8	6	6	6	4	2	2	2	1	1/0	1/0	2/0
100' 30 m	12	8	6	6	4	4	2	2	1	1/0	1/0	2/0	2/0
110' 33 m	10	8	6	6	4	4	2	2	1	1/0	1/0	2/0	2/0
120' 36 m	10	8	6	4	4	2	2	1	1/0	1/0	2/0	2/0	3/0
130' 40 m	10	8	6	4	4	2	2	1	1/0	2/0	2/0	3/0	3/0
140' 43 m	10	6	6	4	2	2	1	1/0	1/0	2/0	3/0	3/0	3/0
150' 46 m	10	6	6	4	2	1	1	1/0	2/0	2/0	3/0	3/0	4/0
160' 49 m	10	6	4	4	2	1	1	1/0	2/0	3/0	3/0	4/0	4/0
170' 52 m	8	6	4	2	2	1	1	1/0	2/0	3/0	3/0	4/0	4/0

TECH tip

ABYC Recommends...

"Conductors used for panelboard or switchboard main feeders, bilge blowers, electronic equipment, navigation lights, and other circuits where voltage drop must be kept to a minimum, shall be sized for a voltage drop not to exceed three percent." ABYC 11.16.1.2.7.

Conductors Sized (AWG) for 10% Voltage Drop

Use 10% voltage drop for any "non-critical" applications: windlass, cabin lights, etc....

For Example...

Q: A bilge pump draws 10 amps. The positive run is 11 feet from the power panel, including the float switch. The negative run is only 10 feet. What size is the wire?

A: Use the formula to reach the correct answer:

$$CM = \frac{10.75 \times 10 \text{ (amps)} \times 21 \text{ (total length of run)}}{0.36 \text{ (3\% of 12V)}} = 6.271$$

Ankor cable specifications show that 12 AWG wire has a CM area of 6,500 and is the correct choice. However, SAE wire has a CM area of only 5,833. Under NFPA and USCG regulations, 10 SAE wire must be used.



ABYC Recommends...

"Conductors used for lighting, other than navigation lights, and other circuits where voltage drop is not critical, shall be sized for a voltage drop not to exceed 10 percent." ABYC 11.16.1.2.7.

10% Voltage Drop at 12 Volts

Length	Current (Amps)												
	5	10	15	20	25	30	40	50	60	70	80	90	100
10' 3 m	18	18	18	16	16	14	14	12	12	10	10	10	10
15' 5 m	18	18	16	14	14	12	12	10	10	8	8	8	8
20' 6 m	18	16	14	14	12	12	10	10	8	8	8	6	6
25' 8 m	18	16	14	12	12	10	10	8	8	6	6	6	6
30' 9 m	18	14	12	12	10	10	8	8	6	6	6	6	4
40' 12 m	16	14	12	10	10	8	8	6	6	4	4	4	4
50' 15 m	16	12	10	10	8	8	6	6	4	4	4	2	2
60' 18 m	14	12	10	8	8	6	6	4	4	2	2	2	2
70' 21 m	14	10	8	8	6	6	6	4	2	2	2	2	1
80' 24 m	14	10	8	8	6	6	4	4	2	2	2	1	1
90' 27 m	12	10	8	6	6	6	4	2	2	2	1	1	1/0
100' 30 m	12	10	8	6	6	4	4	2	2	1	1	1/0	1/0
110' 33 m	12	8	8	6	6	4	2	2	2	1	1/0	1/0	1/0
120' 36 m	12	8	6	6	4	4	2	2	1	1	1/0	1/0	2/0
130' 40 m	12	8	6	6	4	4	2	2	1	1/0	1/0	2/0	2/0
140' 43 m	10	8	6	6	4	2	2	1	1	1/0	2/0	2/0	2/0
150' 46 m	10	8	6	4	4	2	2	1	1/0	1/0	2/0	2/0	3/0
160' 49 m	10	8	6	4	4	2	2	1	1/0	2/0	2/0	3/0	3/0
170' 52 m	10	6	6	4	2	2	2	1	1/0	2/0	2/0	3/0	3/0

10% Voltage Drop at 24 Volts

Length	Current (Amps)												
	5	10	15	20	25	30	40	50	60	70	80	90	100
10' 3 m	18	18	18	18	18	18	16	16	14	14	14	12	12
15' 5 m	18	18	18	18	16	16	14	14	12	12	12	10	10
20' 6 m	18	18	18	16	16	14	14	12	12	10	10	10	10
25' 8 m	18	18	16	16	14	14	12	12	10	10	10	8	8
30' 9 m	18	18	16	14	14	12	12	10	10	8	8	8	8
40' 12 m	18	16	14	14	12	12	10	10	8	8	8	6	6
50' 15 m	18	16	14	12	12	10	10	8	8	6	6	6	6
60' 18 m	18	14	12	12	10	10	8	8	6	6	6	6	4
70' 21 m	16	14	12	10	10	8	8	6	6	6	6	4	4
80' 24 m	16	14	12	10	10	8	8	6	6	6	4	4	4
90' 27 m	16	12	10	10	8	8	6	6	6	4	4	4	2
100' 30 m	16	12	10	10	8	8	6	6	4	4	4	2	2
110' 33 m	14	12	10	8	8	8	6	6	4	4	2	2	2
120' 36 m	14	12	10	8	8	6	6	4	4	2	2	2	2
130' 40 m	14	12	10	8	8	6	6	4	4	2	2	2	2
140' 43 m	14	10	8	8	6	6	6	4	2	2	2	2	1
150' 46 m	14	10	8	8	6	6	4	4	2	2	2	2	1
160' 49 m	14	10	8	8	6	6	4	4	2	2	2	1	1
170' 52 m	12	10	8	6	6	6	4	2	2	2	2	1	1

10% Voltage Drop at 32 Volts

Length	Current (Amps)												
	5	10	15	20	25	30	40	50	60	70	80	90	100
10' 3 m	18	18	18	18	18	18	18	16	16	14	14	14	14
15' 5 m	18	18	18	18	18	18	16	14	14	14	12	12	12
20' 6 m	18	18	18	18	16	16	14	14	12	12	12	10	10
25' 8 m	18	18	18	16	16	14	14	12	12	10	10	10	10
30' 9 m	18	18	18	16	14	14	12	14	10	10	10	10	8
40' 12 m	18	18	16	14	14	12	12	10	10	8	8	8	8
50' 15 m	18	16	14	14	12	12	10	10	8	8	8	6	6
60' 18 m	18	16	14	12	12	10	10	8	8	8	6	6	6
70' 21 m	18	14	14	12	10	10	8	8	8	6	6	6	6
80' 24 m	18	14	12	12	10	10	8	8	6	6	6	6	4
90' 27 m	18	14	12	10	10	10	8	6	6	6	6	4	4
100' 30 m	16	14	12	10	10	8	8	6	6	6	4	4	4
110' 33 m	16	14	12	10	10	8	8	6	6	6	4	4	4
120' 36 m	16	12	10	10	8	8	6	6	6	4	4	4	2
130' 40 m	16	12	10	10	8	8	6	6	6	4	4	2	2
140' 43 m	14	12	10	8	8	8	6	6	4	4	2	2	2
150' 46 m	14	12	10	8	8	6	6	6	4	4	2	2	2
160' 49 m	14	12	10	8	8	6	6	4	4	2	2	2	2
170' 52 m	14	12	10	8	8	6	6	4	4	2	2	2	2

18-4/0 AWG Wire and Cable Specifications

AWG	mm ²	AWG CM area	SAE CM area	Ampacity Engine Space	
				Outside	Inside
18	0.8	1,600	1,537	20	17
16	1	2,600	2,336	25	21
14	2	4,100	3,702	35	30
12	3	6,500	5,833	45	38
10	5	10,500	9,343	60	51
8	8	16,800	14,810	80	68
6	13	26,600	24,538	120	102
4	21	42,000	37,360	160	136
2	34	66,500	62,450	210	178
1	42	83,690	77,790	245	208
1/0	53	105,600	98,980	285	242
2/0	68	133,100	125,100	330	280
3/0	85	167,800	158,600	385	327
4/0	107	211,600	205,500	445	378

Temperature Rating of Conductor Insulation

The Law

The Code of Federal Regulations (CFR) 183.425 Conductors

- (b) Except for intermittent surges each conductor must not carry a current greater than that specified for the conductor's gauge and temperature rating.
- (c) For conductors in engine spaces, amperages must be corrected by the appropriate correction factor in Note 1.

Due to engine heat, the ambient temperature in engine spaces is usually higher than in other spaces of the boat. Wiring in and passing through engine spaces must be able to operate at these higher ambient temperatures. The ampacity values are based on an ambient temperature of 86°F / 30°C which is considered reasonable for use on boats except in engine spaces. The correction factors in Note 1 converts the ampacities to acceptable values in an ambient temperature of 122°F / 50°C. This higher temperature has been selected as satisfactory for engine spaces. Note 1 is supplied to eliminate the need for calculating the corrections. The values are already corrected.

Conductor Size AWG	Ampacity Outside of Engine Space	Ampacity Inside of Engine Space (Note 1)
18	20	17
16	25	21
14	35	30
12	45	38
10	60	51
8	80	68
6	120	102
4	160	136
3	180	153
2	210	178
1	245	208
1/0	285	242
2/0	330	280
3/0	385	327
4/0	445	378

*De-rating for engine space is 0.85 for 221°F / 105°C rated wire.

Allowable Amperage of Conductors of 50 Volts or More

The current values shown in this chart and also on the wire and cable specifications chart do not consider voltage drop for conductors under 50 volts. The values shown on the ampacity table are the maximum safe amperages which the conductor can carry on a continuous basis. They do not apply to intermittent starting loads such as motor start currents. Since all Ancor Boat Cable is 105°C insulated, only that temperature rating is shown.

Due to the higher ambient temperatures in engine spaces and the heat retention of large wire bundles, a “correction factor” must be used to de rate the wire by increasing conductor size. This chart takes into consideration these factors and should be used to select conductor sizes for circuits over 50 volts. Note that for electrical systems under 50 volts, voltage drop is the controlling factor and the tables on 78 and 79 should be used.

Conductor Size AWG	2 Conductors 221°F (105°C) Engine Space		3 Conductors 221°F (105°C) Engine Space		4-6 Conductors 221°F (105°C) Engine Space		7-24 Conductors 221°F (105°C) Engine Space	
	Outside	Inside	Outside	Inside	Outside	Inside	Outside	Inside
18	20	17.0	14.0	11.9	12.0	10.2	10.0	8.5
16	25	21.3	17.5	14.9	15.0	12.8	12.5	10.6
14	35	29.8	24.5	20.8	21.0	17.9	17.5	14.9
12	45	38.3	31.5	26.8	27.0	23.0	22.5	19.1
10	60	51.0	42.0	35.7	36.0	30.6	30.0	25.5
8	80	68.0	56.0	47.6	48.0	40.8	40.0	34.0
6	120	102.0	84.0	71.4	72.0	61.2	60.0	51.0
4	160	136.0	112.0	95.2	96.0	81.6	80.0	68.0
3	180	153.0	126.0	107.1	108.0	91.8	90.0	76.5
2	210	178.5	147.0	125.0	126.0	107.1	105.0	89.3
1	245	208.3	171.5	145.8	147.0	125.0	122.5	104.1
1/0	285	242.3	199.5	169.6	171.0	145.4	142.5	121.1
2/0	330	280.5	231.0	196.4	198.0	168.3	165.0	140.3
3/0	385	327.3	269.5	229.1	231.0	196.4	192.5	163.6
4/0	445	378.3	311.5	264.8	267.0	227.0	222.5	189.1

Number of current carrying conductors:	Correction Factor
3	0.70
4 to 6	0.60
7 to 24	0.50
25 and above	0.40

This table is supplied to eliminate the need for calculating the corrections for multi-conductor cable bundles in the temperature rating chart. The values are already corrected.

Note: These tables only apply for 221°F (105°C) wire and other premium wire and should not be used for lesser grades of wire and cable.

Reprinted at the courtesy of the United States Coast Guard Electrical System Compliance Guideline.

* There is NO LIMIT on conductors in a bundle under 50 volts.

PN	Page	PN	Page	PN	Page	PN	Page	PN	Page
100010	10	102310	10	104710	10	107025	11	111525	11
100025	10	102325AA	10	104725	10	107040	11	111550	11
100050	10	102350	10	104750	10	107099	11	111599	11
100099	10	102399	10	104810	10	108002	11	111702	11
100110	10	102410	10	104825	10	108010	11	111705	11
100125	10	102425	10	104850	10	108025	11	111710	11
100150	10	102450	10	104899	10	108050	11	111725	11
100199	10	102499	10	104910	10	108099	11	111750	11
100210	10	102510	10	104925	10	108102	11	111799	11
100225	10	102525	10	104950	10	108110	11	111902	11
100250A	10	102550	10	104999	10	108125	11	111905	11
100299	10	102599	10	105010	10	108150	11	111910	11
100310	10	102610	10	105025	10	108199	11	111925	11
100319F	18	102625	10	105050	10	108202	11	111950	11
100320F	18	102650	10	105099	10	108210	11	111999	11
100325	10	102710	10	105810	11	108225	11	112002	11
100350	10	102725	10	105825	11	108250	11	112005	11
100399	10	102750	10	105840	11	108299	11	112010	11
100410	10	102799	10	106002	11	108302	11	112025	11
100425	10	102810	10	106010	11	108310	11	112050	11
100450	10	102825	10	106025	11	108325	11	112075	11
100499	10	102850	10	106040	11	108350	11	112302	11
100510	10	102899	10	106099	11	108399	11	112305	11
100525	10	102910	10	106102	11	108499	11	112310	11
100550	10	102925	10	106110	11	108502	11	112325	11
100599	10	102950	10	106125	11	108510	11	112350	11
100610	10	102999	10	106140	11	108525	11	112375	11
100625	10	103010	10	106199	11	108550	11	112502	11
100650	10	103025	10	106202	11	108599	11	112505	11
100699	10	103050	10	106210	11	108802	11	112510	11
100710	10	103099	10	106225	11	108810	11	112525	11
100725	10	103810	10	106240	11	108825	11	112550	11
100750	10	103825	10	106299	11	108850	11	112575	11
100799	10	103850	10	106302	11	108899	11	112702	11
100810	10	103910	10	106310	11	108902	11	112705	11
100825	10	103925	10	106325	11	108910	11	112710	11
100850	10	103950	10	106340	11	108925	11	112725	11
100899	10	104010	10	106399	11	108950	11	112750	11
100910	10	104025	10	106499	11	108999	11	112775	11
100925	10	104050	10	106502	11	109002	11	112902	11
100950	10	104099	10	106510	11	109010	11	112905	11
100999	10	104110	10	106525	11	109025	11	112910	11
101010	10	104125	10	106540	11	109050	11	112925	11
101025	10	104150	10	106599	11	109099	11	112950	11
101050	10	104199	10	106602	11	109302	11	112975	11
101099	10	104210	10	106610	11	109310	11	113002	12
101810	10	104225	10	106625	11	109325	11	113005	12
101825	10	104250	10	106640	11	109350	11	113010	12
101850	10	104299	10	106702	11	109399	11	113025	12
101910	10	104310	10	106710	11	111002	11	113050	12
101925	10	104325	10	106725	11	111005	11	113502	12
101950	10	104350	10	106740	11	111010	11	113505	12
102010	10	104399	10	106802	11	111025	11	113510	12
102025	10	104410	10	106810	11	111050	11	113525	12
102050	10	104425	10	106825	11	111099	11	113550	12
102099	10	104450	10	106840	11	111302	11	113902	12
102110	10	104499	10	106899	11	111305	11	113905	12
102125	10	104510	10	106902	11	111310	11	113910	12
102150	10	104525	10	106910	11	111325	11	113925	12
102199	10	104550	10	106925	11	111350	11	113950	12
102210	10	104599	10	106940	11	111399	11	114002	12
102225	10	104610	10	106999	11	111502	11	114005	12
102250	10	104625	10	107002	11	111505	11	114010	12
102299	10	104650	10	107010	11	111510	11	114025	12

PN	Page	PN	Page	PN	Page	PN	Page	PN	Page
114040	12	119505	12	124925	14	153110	16	186003	11
114502	12	119510	12	124950	14	153125	16	186303	11
114505	12	119525	12	124999	14	153150	16	186803	11
114510	12	119902	12	126310	14	153510	18	186903	11
114525	12	119905	12	126325	14	153530	18	187003	11
114540	12	119910	12	126350	14	153710	18	188003	11
114902	12	119925	12	126510	14	153725	18	188803	11
114905	12	120705	14	126525	14	153910	18	189130	13
114910	12	120710	14	126550	14	154010	19	189131	13
114925	12	120905	14	126710	14	154030	19	189134	13
114940	12	120910	14	126725	14	154510	19	189135	13
115002	12	120925	14	126750	14	154525	19	189136	13
115005	12	121110	14	130705	15	155010	16	189137	13
115010	12	121125	14	130710	15	155050	16	189140	13
115030	12	121140	14	130902	15	156410	17	189141	13
115502	12	121180	14	130905	15	156425	17	189144	13
115505	12	121310	14	130910	15	156450	17	189145	13
115510	12	121325	14	131110	15	156610	17	189146	13
115530	12	121350	14	131130	15	156625	17	189147	13
115902	12	121510	14	131150	15	158010	16	189303	16
115905	12	121525	14	131151	16	158025	16	189800	18
115910	12	121550	14	131302	15	158099	16	189849	18
115930	12	121599	14	131310	15	160010	17	199200	41
116002	12	121602A	16	131325	15	160099	17	199201	41
116005	12	121610	16	131370	15	160110	17	199202	41
116010	12	121625	16	131510	15	160199	17	199203	41
116025	12	121710	14	131525	15	160210	17	199204	41
116502	12	121725	14	131550	15	160299	17	199205	41
116505	12	121750	14	131590	15	170002	17	199206	41
116510	12	121799	14	131710	15	170010	17	199207	41
116525	12	121802	16	131725	15	170025	17	199208	41
116902	12	121810	16	131750	15	180003	10	199209	41
116905	12	121825	16	131799	15	180103	10	199210	41
116910	12	121910	14	133310	15	180203	10	199211	41
116925	12	121925	14	133325	15	180303	10	199212	41
117002	12	121950	14	133510	15	180403	10	199213	41
117005	12	122010	16	133525	15	180503	10	199214	41
117010	12	122025	16	133590	15	180603	10	199215	41
117020	12	122050	16	133710	15	180703	10	199216	41
117502	12	123705	14	133725	15	180803	10	199217	41
117505	12	123710	14	141410	16	180903	10	199218	41
117510	12	123905	14	141425	16	181003	10	199219	41
117520	12	123910	14	142410	17	182003	10	199220	41
117902	12	123950	14	142425	17	182103	10	199221	41
117905	12	124102	14	142499	17	182203	10	199222	41
117910	12	124110	14	142610	17	182303	10	199223	41
117920	12	124125	14	142625	17	182403	10	199224	42
118002	12	124140	14	142650	17	182503	10	199225	42
118005	12	124180	14	142810	17	182603	10	199226	42
118010	12	124302	14	150102	17	182703	10	199227	42
118015	12	124310	14	150110	17	182803	10	199228	42
118502	12	124325	14	150510	18	182903	10	199229	42
118505	12	124350	14	150525	18	183003	10	199230	42
118510	12	124502	14	151025	18	184003	10	199231	42
118515	12	124510	14	151050	18	184103	10	199232	42
118902	12	124525	14	151510	18	184203	10	199233	42
118905	12	124550	14	151525	18	184303	10	199234	42
118910	12	124599	14	151550	18	184403	10	199235	42
118915	12	124702	14	151560	18	184503	10	199236	42
119002	12	124710	14	151710	18	184603	10	199245	42
119005	12	124725	14	151725	18	184703	10	199246	41
119010	12	124750	14	151750	18	184803	10	199247	41
119025	12	124799	14	153010	16	184903	10	199248	41
119502	12	124910	14	153050	16	185003	10	199249	41

PN	Page	PN	Page	PN	Page	PN	Page	PN	Page
199250	42	199342	43	210302	30	220227	29	230165	31
199251	42	199343	43	210303	30	220302	30	230166	31
199252	42	199344	41	210311	30	220303	30	230201	29
199253	42	199345	41	210312	30	220312	30	230202	29
199254	41	199346	41	210313	30	220313	30	230203	29
199257	42	199347	41	210321	30	220322	30	230204	29
199258	42	199348	41	210322	30	220323	30	230205	29
199259	41	199349	41	210323	30	220602	31	230206	29
199260	41	199350	41	210510	31	220612	31	230211	29
199261	42	199351	41	210520	31	220615	31	230212	29
199262	42	199352	41	210602A	31	220622	31	230213	29
199263	42	200250	32	210612	31	220708	31	230214	29
199264	43	200258	32	210613	31	220709	31	230215	29
199265	43	200259	32	210615	31	220718	31	230216	29
199266	43	202175	32	210622	31	220719	31	230221	29
199267	43	202176	32	210708	31	220808	30	230222	29
199268	43	203100	32	210709	31	220809	30	230223	29
199269	43	210100	30	210718	31	220818	30	230224	29
199274	43	210110	30	210719	31	220819	30	230225	29
199275	43	210120	30	210808	30	220828	30	230226	29
199276	43	210130	31	210809	30	220829	30	230227	29
199277	43	210140	31	210818	30	221408	30	230233	29
199278	43	210150	31	210819	30	221409	30	230234	29
199279	43	210161	30	210828	30	221418	30	230235	29
199280	43	210162	30	210829	30	221419	30	230236	29
199281	43	210163	30	211408	30	221428	30	230237	29
199282	43	210164	31	211409	30	221429	30	230243	29
199283	43	210165	31	211418	30	222100	30	230244	29
199284	43	210166	31	211419	30	222110	30	230245	29
199285	43	210201	29	211428	30	222120	30	230246	29
199300	44	210202	29	211429	30	222130	31	230247	29
199301	44	210203	29	211480	31	222140	31	230253	29
199302	44	210204	29	211490	31	222150	31	230254	29
199303	44	210205	29	211601	30	222161	30	230255	29
199304	44	210206	29	211611	30	222162	30	230256	29
199305	44	210211	29	211621	30	222163	30	230257	29
199306	44	210212	29	220002	55	222203	29	230301	30
199307	44	210213	29	220003	55	222213	29	230302	30
199308	44	210214	29	220004	55	222223	29	230303	30
199309	44	210215	29	220011	27	222233	29	230311	30
199310	44	210216	29	220012	27	222234	29	230312	30
199311	44	210221	29	220020	55	222235	29	230313	30
199312	44	210222	29	220100	30	222236	29	230321	30
199313	44	210223	29	220110	30	222237	29	230322	30
199314	44	210224	29	220120	30	222243	29	230323	30
199315	44	210225	29	220161	30	222244	29	230510	31
199316	44	210226	29	220162	30	222245	29	230520	31
199317	44	210227	29	220163	30	222246	29	230602	31
199318	43	210233	29	220164	31	222247	29	230612	31
199319	43	210234	29	220202	29	222253	29	230613	31
199320	43	210235	29	220203	29	222254	29	230615	31
199321	43	210236	29	220204	29	222255	29	230622	31
199322	43	210237	29	220205	29	222256	29	230708	31
199323	43	210243	29	220206	29	222257	29	230709	31
199324	42	210244	29	220212	29	230100	30	230718	31
199325	42	210245	29	220213	29	230110	30	230719	31
199328	42	210246	29	220214	29	230120	30	230808	30
199329	42	210247	29	220215	29	230130	31	230809	30
199333	43	210253	29	220216	29	230140	31	230818	30
199334	43	210254	29	220222	29	230150	31	230819	30
199336	43	210255	29	220223	29	230161	30	230828	30
199337	43	210256	29	220224	29	230162	30	230829	30
199339	43	210257	29	220225	29	230163	30	231408	30
199340	43	210301	30	220226	29	230164	31	231409	30

PN	Page	PN	Page	PN	Page	PN	Page	PN	Page
231418	30	244256	33	252266	33	270111	21	306648	38
231419	30	244265	33	252267	33	270112	21	306903	38
231428	30	244266	33	252271	33	270113	21	306906	38
231429	30	244275	33	252274	33	270114	21	306924	38
231480	31	244276	33	252275	33	270201	22	306948	38
231490	31	244285	33	252276	33	270202	22	307103	38
231601	30	244286	33	252277	33	270203	23	307106	38
231611	30	244295	33	252281	33	270300	20	307124	38
231621	30	244296	33	252284	33	270301	20	307148	38
242130	34	244715	33	252285	33	270302	20	307602	38
242140	34	244716	33	252286	33	270305	20	307603	38
242150	34	244725	33	252287	33	270400	76	307606	38
242160	34	244726	33	252291	33	301103	38	307624	38
242170	34	249101	19	252294	33	301106	38	307648	38
242180	34	249102	19	252295	33	301124	38	307903	38
242190	34	249103	19	252296	33	301148	38	307906	38
242233	33	249104	19	252297	33	301503	38	307924	38
242234	33	249105	19	252715	33	301506	38	307948	38
242235	33	249106	19	252716	33	302103	38	309000	27
242236	33	249107	19	252717	33	302106	38	309001	27
242237	33	249108	19	252725	33	302124	38	309002	27
242243	33	249109	19	252726	33	302148	38	309003	27
242244	33	249110	19	252727	33	302603	38	309025	27
242245	33	249111	19	255101	47	302606	38	309099	27
242246	33	249112	19	260010	35	302624	38	309101	27
242247	33	249113	19	260012	35	302648	38	309102	27
242253	33	249114	19	260100	35	303103	38	309103	27
242254	33	249115	19	260200	35	303106	38	309125	27
242255	33	249116	19	260322	35	303124	38	309199	27
242256	33	249117	19	260325	35	303148	38	309201	27
242257	33	249118	19	260350	35	303602	38	309202	27
242264	33	249119	19	260381	35	303603	38	309203	27
242265	33	249120	19	260405	34	303606	38	309225	27
242266	33	249121	19	260505	35	303624	38	309299	27
242267	33	249122	19	262245	34	303648	38	309302	27
242274	33	250101	47	262246	34	304103	38	309303	27
242275	33	252130	34	262255	34	304106	38	309325	27
242276	33	252140	34	262256	34	304124	38	310203	26
242277	33	252150	34	262265	34	304148	38	310225	26
242284	33	252160	34	262266	34	304503	38	310299	26
242285	33	252170	34	262275	34	304506	38	310303	26
242286	33	252180	34	262276	34	304602	38	310325	26
242287	33	252190	34	262285	34	304603	38	310399	26
242294	33	252231	33	262286	34	304606	38	310403	26
242295	33	252233	33	262295	34	304624	38	310425	26
242296	33	252234	33	262296	34	304648	38	310499	26
242297	33	252235	33	262715	34	305103	38	310503	26
242715	33	252236	33	262716	34	305106	38	310525	26
242716	33	252237	33	262725	34	305124	38	310599	26
242717	33	252241	33	262726	34	305148	38	310603	26
242725	33	252243	33	270000	20	305602	38	310625	26
242726	33	252244	33	270001	20	305603	38	310699	26
242727	33	252245	33	270002	20	305606	38	311203	26
244233	33	252246	33	270005	20	305624	38	311225	26
244234	33	252247	33	270010	20	305648	38	311299	26
244235	33	252251	33	270101	21	306103	38	311303	26
244236	33	252253	33	270103	21	306106	38	311325	26
244243	33	252254	33	270104	21	306124	38	311399	26
244244	33	252255	33	270105	21	306148	38	311403	26
244245	33	252256	33	270106	21	306503	38	311425	26
244246	33	252257	33	270107	21	306602	38	311499	26
244253	33	252261	33	270108	21	306603	38	311503	26
244254	33	252264	33	270109	21	306606	38	311525	26
244255	33	252265	33	270110	21	306624	38	311599	26

PN	Page	PN	Page	PN	Page	PN	Page	PN	Page
311603	26	320225	27	348010	40	520194	62	710030	54
311625	26	320303	27	356803	28	520906	62	710040	54
311699	26	320325	27	356825	28	521004	62	711000	55
312203	26	320803	28	357803	28	521142	62	750000	46
312225	26	320825	28	357825	28	521157	62	760375	46
312299	26	320899	28	400000	45	521158	62	760500	46
312303	26	320903	28	401122	45	521164	62	764998	46
312325	26	320925	28	401182	45	522112	63	765000	46
312399	26	320999	28	401251	45	522122	63	765002	46
312403	26	321303	26	401252	45	522129	63	765004	46
312425	26	321325	26	401255	45	529095	63	765006	46
312499	26	321403	26	401312	45	529102	63	765010	46
312503	26	321425	26	401372	45	529300	62	765012	46
312525	26	321503	26	401375	45	529333	63	ANCHEADER	75
312599	26	321525	26	401432	45	529337	63	ANCLAMP	72
312603	26	321603	26	401502	45	529338	63	ANCLUG	72
312625	26	321625	26	401622	45	529340	62	ANCNMEA	72
312699	26	321703	26	401752	45	529341	62	ANCSHRINK	72
313203	26	321725	26	401892	45	529355	63	ANCTERM	72
313225	26	326103	39	401912	45	529361	63	ANCWIRE	72
313299	26	326106	39	401932	45	529362	63	DR1086	73
314203	26	326124	39	402252	45	529367	63	DR1088	74
314225	26	326148	39	402312	45	529368	63	DR1218	72
314299	26	326202	39	402372	45	529370	63	DR1230	68
314303	26	326603	39	402502	45	529385	63	DR1243	69
314325	26	326606	39	402622	45	529386	63	DR1425	70
314399	26	326624	39	402752	45	529405	64	DR1550	71
315203	26	326648	39	402892	45	531025	64	DR2218	72
315225	26	326899	28	403182	45	531050	64	DR2230	68
315299	26	326903	39	403252	45	531075	64	DR2243	69
315303	26	326906	39	403312	45	532025	64	DR2425	70
315325	26	326924	39	403372	45	532050	64	DR2550	71
315399	26	327103	39	403502	45	533050	64	P33406	47
316803	28	327106	39	403562	45	700103	57	P33407	47
316825	28	327124	39	403622	45	700115	57	P33412	47
316899	28	327148	39	403752	45	701009	50	SPC103	18
316903	28	327202	39	403872	45	702007	50	SPK1614	28
316925	28	327603	39	403892	45	702008	50	SPK2218	28
316999	28	327606	39	403902	45	702027	56	SPKKIT	28
317803	28	327624	39	404152	45	702030	51		
317825	28	327648	39	404172	45	702031	51		
317899	28	327899	28	404202	45	702032	51		
317903	28	327903	39	404252	45	702033	51		
317925	28	327906	39	404302	45	703005	50		
317999	28	327924	39	404352	45	703006	50		
318803	26	330101	47	452251	46	703007	50		
318825	26	331066	40	452381	46	703010	52		
318899	26	332066	40	452385	46	703015	53		
318903	26	333066	40	452501	46	703023	56		
318925	26	334066	40	452505	46	703024	56		
318999	26	335066	40	452751	46	703030	52		
319803	26	336066	40	452755	46	703035	53		
319825	26	336899	28	452900	46	703040	52		
319899	26	337066	40	452905	46	703041	53		
319903	26	337899	28	453382	46	703042	53		
319925	26	338066	40	453386	46	703050	52		
319999	26	339066	40	453502	46	703060	56		
320000	27	341010	40	453506	46	703072	58		
320003	27	342010	40	453752	46	703073	58		
320025	27	343010	40	453756	46	703075	51		
320101	47	344010	40	453901	46	703079	59		
320103	27	345010	40	453906	46	703112	54		
320125	27	346010	40	520090	62	710010	54		
320203	27	347010	40	520097	62	710020	54		

Ingress Protection (IP) Ratings Guide















Example:

An IP65 rating can be determined using the adjacent table and example:

- The first number of the rating example, 6, in the gray column means the enclosure is dust tight
- The second number of the rating example, 5, in the blue column means the enclosure is protected against jets of water

The IP rating system was established by the International Electrotechnical Commission (IEC), an organization for international standards and conformity assessment. The IEC collaborates closely with the International Organization for Standardization (ISO). A complete description of the IP ratings and associated tests is found in IEC Publication 529. Although these ratings were initially developed as a way to classify enclosures, they now provide a convenient, practical way to compare levels of sealing. Many electrical products have an Ingress Protection (IP) rating which identifies the environmental factors needing consideration prior to the product's installation.

This is important when deciding when to mount products in a dry and clean environment versus a wet and/or dusty environment. The IP rating indicates the degree of protection provided. The numbers following IP represent levels of sealing and can range from no protection to full protection against dust and water. The table provides a description of the protection at each level.

SOLIDS		WATER	
1	 <p>Protected against a solid object greater than 50 mm such as a hand.</p>	1	 <p>Protected against vertically falling drops of water. Limited ingress permitted.</p>
2	 <p>Protected against a solid object greater than 12 mm such as a finger.</p>	2	 <p>Protected against vertically falling drops of water with enclosure tilted up to 15 degrees from the vertical. Limited ingress permitted.</p>
3	 <p>Protected against a solid object greater than 2.5 mm such as a screwdriver.</p>	3	 <p>Protected against sprays of water up to 60 degrees from the vertical. Limited ingress permitted for three minutes.</p>
4	 <p>Protected against a solid object greater than 1 mm such as a wire.</p>	4	 <p>Protected against water splashed from all directions. Limited ingress permitted.</p>
5	 <p>Dust Protected. Limited ingress of dust permitted. Will not interfere with operation of the equipment. Two to eight hours.</p>	5	 <p>Protected against jets of water. Limited ingress permitted.</p>
6	 <p>Dust tight. No Ingress of dust. Two to eight hours.</p>	6	 <p>Water from heavy seas or water projected in powerful jets shall not enter the enclosure in harmful quantities.</p>
		7	 <p>Protection against the effects of immersion in water between 15 cm and 1 m for 30 minutes.</p>
		8	 <p>Protection against the effects of immersion in water under pressure for long periods.</p>

Rating Example:

IP65

INGRESS PROTECTION