

SPECIFICATIONS

FEATURES / SPECS	
MOTOR	1.8HP PERMANENT MAGNET
SWITCH	250A SEALED CONTACTOR
CONTROLLER	1) HANDLEBAR MOUNTED MINI-ROCKER SWITCH INCLUDED 2) HAND HELD CONTROLLER WITH FEMALE PLUG AND WIRING HARNESS INCLUDED 3) WIRELESS AVAILABLE 20156 OPTIONAL
BATTERY LEADS	6 GA
GEAR TRAIN	3 STAGE PLANETARY
GEAR RATIO	136:1
CLUTCH	FREESPOOLING
BRAKE	AUTOMATIC LOAD HOLD MECHANICAL IN DRUM
DRUM DIA X L	2 X 4.8" (51 X 122mm)
WIRE ROPE	7/32" X 55' (5.5mm X 16.8m)
SYNTHETIC ROPE	6mm X 50'
OVERALL DIMENSIONS (LxWxH)	16.3 X 4.6 X 4.6" (415 X 117 X 117mm)
MOUNTING BOLT PATTERN	6.6 X 3" (168 X 76mm)
WARRANTY	2 YEAR LIMITED

PULL, SPEED, AMPS

LINE PULL LBS	LINE SPEED FT/MIN	CURRENT A
0	19.8	11
1000	10.9	40
2000	7.6	70
3000	5.9	95
4000	3.6	310

LINE PULL AND ROPE CAPACITY IN LAYER

LAYER	RATED LINE PULL LBS	TOTAL ROPE ON DRUM FT
1	4000	13.1
2	3520	28.2
3	3098	45.9
4	2726	55