

^{самбо}

Excellent durability and traction

One of the best trail tracks ever offered and still a bestseller today, with rigid, hard-wearing lugs for mile after mile of dependable use. A wide range of sizes fits many different snowmobiles. This is the benchmark model for high-performance trail tracks, with excellent durability and traction on groomed or hard-pack snow.

- Rigid lugs provide superior handling, acceleration, and braking on groomed trails
- Narrow lug base for reduced rolling resistance and maximum top speed
- Angled profiles for aggressive forward and lateral bite



RipSaw II

All-around performer in all types of snow

Designed for all-around trail performance – excellent traction on both hard-pack and loose, less-compacted snow with ride comfort features.

- Tapered outside lug edges for less side bite when cornering
- Sharp angled lugs for excellent bite on hard-pack snow
- Cupped center and full outer lugs for traction on loose, less-compacted snow
- Lug design generates less noise for improved rider comfort on hard-packed groomed trails

MODEL	DIMENSIONS	LUG HEIGHT	WEIGHT	DRIVE PITCH	CLIP CONFIG.	MODEL	DIMENSIONS	LUG HEIGHT	WEIGHT	DRIVE PITCH	CLIP CO	NFIG.
9001H	13.5" x 128" (34 cm x 325 cm)	1.25" (32 mm)	34 lb (15.5 kg)	2.52" (64 mm)	Every 3 rd / closed windows	9156H	15" x 120" (38 cm x 305 cm)	1.25" (32 mm)	36 lb (16.25 kg)	2.86" (73 mm)	Full	
9006H	15" X 144" (38 cm x 366 cm)	1.25" (32 mm)	45 lb (20.5 kg)	2.52" (64 mm)	Full	9158H	15" x 120" (38 cm x 305 cm)	1" (25 mm)	32 lb (14.5 kg)	2.86" (73 mm)	Full	
9040H	15" x 128" (38 cm x 325 cm)	1.25" (32 mm)	41 lb (18.5 kg)	2.52" (64 mm)	Full	9209H	15" x 120" (38 cm x 305 cm)	1.25" (32 mm)	37 lb (16.75 kg)	2.86" (73 mm)	Full	
9146H	15" x 121" (38 cm x 307 cm)	1.25" (32 mm)	35 lb (16 kg)	2.52" (64 mm)	Every 3 rd / open windows	9210H	15" x 120" (38 cm x 305 cm)	1" (25 mm)	33 lb (15 kg)	2.86" (73 mm)	Full	
9148H	15" x 120" (38 cm x 305 cm)	1" (25 mm)	32 lb (14.5 kg)	2.86" (73 mm)	Full	9214H	15" x 121" (38 cm x 307 cm)	1.25" (32 mm)	41 lb (18.5 kg)	2.52" (64 mm)	Full	
9149H	15" x 120" (38 cm x 305 cm)	1.25" (32 mm)	35 lb (16 kg)	2.86" (73 mm)	Full	9215H	15" x 128" (38 cm x 325 cm)	1.25" (32 mm)	43 lb (19.5 kg)	2.52" (64 mm)	Full	
9968H	15" x 121" (38 cm x 307 cm)	1.25" (32 mm)	40 lb (18.25 kg)	2.52" (64 mm)	Full	9216H	15" x 136" (38 cm x 345 cm)	1.25" (32 mm)	45 lb (20.5 kg)	2.52" (64 mm)	Full	
9968H144	15" x 121" (38 cm x 307 cm)	1.25" (32 mm)	38 lb (17.25 kg)	2.52" (64 mm)	Full	9223H	15" x 137" (38 cm x 348 cm)	1.25" (32 mm)	42 lb (19 kg)	2.86" (73 mm)	Full	
9969H	15" x 136" (38 cm x 345 cm)	1.25" (32 mm)	43 lb (19.5 kg)	2.52" (64 mm)	Full	9224H	15" x 137" (38 cm x 348 cm)	1" (25 mm)	38 lb (17.25 kg)	2.86" (73 mm)	Full	
						9237H	15" x 129" (38 cm x 328 cm)	1.25" (32 mm)	39 lb (17.75 kg)	2.86" (73 mm)	Full	
						9325H	15" X 129" (38 cm x 328 cm)	1" (25 mm)	35 lb (15.87 kg)	2.86" (73 mm)	Full	

🔺 Embedded sharp tip lug studs 📗 Single-ply construction 🛛 Enhanced stud easy tracks