



Can-Am Defender 1000/800

Read before Installation

This product is designed for use on ATVs and/or RUVs to increase ground clearance and fender clearance. Purchasers should be aware that use of this product may increase the frequency of required maintenance, part wear, and will raise the center of gravity on your ATV and/or RUV, increasing risk of roll-over, injury and death on all types of terrain. It is your responsibility to always inform other operators and passengers of this vehicle about the added risks.

High Lifter Products, products are designed to best fit users ATV/RUV under stock conditions. Adding, modifying, or fabricating any OEM or aftermarket parts will void warranty. High Lifter Products, products could interfere with other aftermarket accessories. If the user has aftermarket products on machine, contact High Lifter Products to verify that they will work together. Adding aftermarket suspension components and/or more aggressive tires can cause breakage of other OEM driveline components such as differentials, axles or drive shafts.

We recommend that wider tires and/or wheel spacers be used to achieve a wider stance and to improve stability of the ATV and/or RUV. Riders should be advised that the handling characteristics of a taller ATV and/or RUV are different and require extra care when riding, particularly on side hills or off-camber situations. If you further raise the center of gravity by adding taller tires, heavy loads to racks or seats, or by any other means, the ATV and/or RUV must be operated with even more care, at slower speeds and on relatively flat ground. All turns should be done at a slow speed, even on level ground.

Operation of an ATV and/or RUV with or without modified suspension components, while or shortly after consuming alcohol or drugs, subjects the rider to the risk of serious bodily harm or possible death. This risk is compounded if the rider does not wear an approved helmet and other safety gear. High Lifter urges that all approved safety gear be worn when riding an ATV and/or RUV as a driver or passenger.

By purchasing and installing High Lifter Products, products, user agrees that should damages occur, High Lifter Products will not be held responsible for loss of time, use, labor fees, replacement parts, or freight charges. High Lifter Products will not be held responsible for any direct, indirect, incidental, special, or consequential damages that result from any product purchased from High Lifter Products. The total liability of seller to user for all damages, losses, and causes of action, shall not exceed the total purchase price paid for the product that gives rise to the claim.

Dealers and other Installers

You are responsible for informing your customer and end user of the information contained above and the increased potential hazards of operating an ATV and/or RUV equipped with modified suspension components. If you install any suspension modifying components, it is your responsibility to also install the warning label prominently in view of the driver and in prominent view of the driver and passenger on RUVs and multi-passenger ATVs. They should also be instructed to notify anyone operating the vehicle, as well as any passengers, that said vehicle is modified.

As discussed above, it is critically important that they be instructed in the need for slower speed operation, regardless of terrain, after this lift kit is installed.

Parts Diagram

**Front Spring
Spacer (2ea) 45Y**



**10mm x 60mm Bolt
(4ea) MCS1060**



**Spacer (2ea)
4Y**



**10mm Lock
Nut (4ea)
MLN10-1.5**



**Rear Lift Bracket
Left (2ea) 54K-L**



**Rear Lift Bracket
Right (2ea) 54K-R**



Front Lift Installation


1. Place transmission in park. Place jack under center of front end and lift until front wheels clear the ground. Be careful to properly secure and support so that A-arms and shocks can droop to full extension.
2. Remove front wheels and front shocks from the UTV.
3. For the next step you will need a spring compressor!!! You cannot install the brackets without a spring compressor.
4. Place the shock in the compressor or attach the compressor so that you can compress the spring and remove the retaining clip that holds the springs in place.
5. Remove the clip.




6. Remove the spring.



7. Slide the spring lift bracket onto the shock.




8. Place the spring back on the shock.



9. Compress the spring and place retaining clip back on the shock.



10. Place the shock back on the UTV. Torque bolts to factory specification.



11. Place tires and wheels back on the UTV. Torque lugs to factory specifications.

Rear Installation

1. Place the transmission in park. Place a jack under the center of the UTV and lift until the rear wheels clear the ground. Be careful to support the UTV properly so that it is securely supported so that the suspension can droop to full extension.
2. Remove the rear wheels.
3. Disconnect the bottom of the shock from the control arm.




4. Attach the lift bracket to the shock mount. There are left and right brackets and they will nest against the shock mount tabs.



5. Insert the 10mm x 60mm bolt through the bracket and into the shock mount tab.



6. Place the spacer between the shock mount tabs and push the bolt all the way through.




7. Attach the second lift bracket to the shock mount tab, securing it in place with a 10mm lock nut.



8. Connect the bottom of the shock to the lift brackets.



9. Secure the shock to the brackets using a 10mm x 60mm bolt and 10mm lock nut.



10. Repeat steps for the opposite side.

11. Place wheels back on the UTV and torque lugs to factory specifications.

Thank You
For choosing

High Lifter
PRODUCTS



High Lifter Lifetime Warranty

From the beginning, High Lifter has engineered and manufactured some of the toughest, most durable products on the market. That's why this product comes with a Lifetime Warranty. It's our promise that High Lifter will never let you down.

- The **Lifetime Warranty** covers products sold to the original purchaser only and is not transferable. The term of the warranty is for the lifetime of the vehicle in question.
- Normal wear and tear items and finishes, such as, but not limited to: Heim joints, tie rod ends, ball joints, bearings, seals, bushings, bushing sleeves, zinc plating, powder coating, or chipping and discoloration of any finish is not covered.
- High Lifter will ship the replacement product after the returned product has been inspected by High Lifter staff.
- The warranty shall not include claims for damages, installation time or labor charges, economic losses, inconvenience, transportation, towing, down time, direct or indirect or consequential damages or delay resulting from any defect.
- The warranty does not apply to products that have been improperly applied or improperly installed.