Install Instructions

PRP Seats Polaris RZR PRO XP Front Door Bag Installation



Parts

Α.



Read through all of the instructions completely before beginning the install.

Parts Included:

A. 2 x PRP Front Door Bags for RZR PRO XP (Driver and Passenger)

Remove all parts from the box and unwrap completely using the packaging to lay out the pieces.

Tools Needed: (not included)


T-40 Torx Socket

Time:

Approx 10 minutes.




Install Instructions for PRP Seats Pro XP Front Door Bag



 Remove the stock bolts from the door (shown in picture).

Use a T-40 Socket to remove the 11 bolts that connect the door's metal frame to the outside plastic panel.

Once the bolts are removed, take off the plastic panels.



2. Select the appropriate door bag for the door you are installing on (Driver or Passenger).

The bottom storage compartment on each bag has a foam cushion inside it. Remove this foam cushion while you install. Simply open the zipper and pull the foam out.



3. Place the bag in-between the metal frame and the plastic panel.

Push upper and lower storage compartments through the open sections in the frame.



4. Line up the cut-holes on the bags liner, with the corresponding bolt holes on the frame and plastic panel. Re-install the bolts so that the bag is secured between the door's frame and plastic panel.

TIP: Start by the door latch, then re-install the bolts one by one (The bolts tend to fall out if you place them in loose all in at once).







- 5. Once the bag is secured, place the foam back into the lower storage compartment. This provides a cushioned Knee Pad for when the ride gets rough!NOTE: If you would like even more storage space, you can choose to leave the foam out. Then just use the lower section as another storage compartment.
- 6. Do the same steps for the bag on the other side... and you're all set! If you have any questions or experience

Thank you! Ride Safe!